



C420 Impulse Heat Sealer

Product description	Desktop impulse heat sealer for fast, professional sealing of PE, PP, PA and PVC foils and thinner, double-coated materials
Product features	Adjustable sealing time Manual seal bar closure Sealing wire tensioning unit, for consistent seal Integrated safety film slitting knife One-piece extruded aluminium body for added strength and safety No mechanical switches, for optimum reliability Max. sealing thickness equivalent to 2 layers of 30mu PVC
Technical data	
~ seal length	420mm
~ seal width	2.5mm
~ max. film width	400mm
~ max. cutting length	400mm
~ max. seal thickness	Polythene - 200mu bag, total 400mu Polypropylene - 80mu bag, total 160mu PVC - 30mu bag, total 60mu
~ dimensions	650 x 100 x 175mm
Power requirements	
~ supply	230V, 50/60Hz
~ consumption	248w
Packing data	
~ packed dimensions	675 x 133 x 200mm
~ packed weight	4.5kg
Spares kit	
~ HA001336	Contains - 1 x element wire, 1 x lower teflon, 1 x upper teflon
Options	
~ CI-420	Available in stainless steel for food handling or corrosive environments

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.