

Contents

A comprehensive product index can be found on page 114

Pacpl	.US [®]
-------	------------------

industrial packaging products

5

Tenza[®]

packing list, postal and plastic bag products

21

Safeguard®

hand strapping tools, strapping and consumables

31

Optimax®

optimum quality packaging machinery

51

Xtegra®

tamper evident and security packaging solutions

71

Transpal®

transit and palletisation products

84

Pacplan[®]

order fulfilment and warehousing products

97

Stronghold®

stapling tools, staples and accessories

109



Pacplus® Hand Held Tape Dispensers

PG50B

Our most popular pistol grip tape dispenser





Standard 75mm Pistol Grip Tape Dispenser

PD712

Standard 50mm

Pistol Grip Tape

Dispenser with

Rubber Roller

Features > Takes 132mtr tapes

> 75mm core > Adjustable brake

> Replaceable blade

Features

- > Takes 132mtr tapes > 75mm core
- > Adjustable brake > Static charge tape grip

Replacement blades: RB75 box 10 Replacement tape flaps: RTF75 box 10

NR50

Features

> 75mm spring

loaded core
Note: only suitable for
use with 50mm wide,
75mm core tapes

Noise Reducing

50mm Pistol Grip Tape Dispenser







ET50B

50mm Pistol Grip

Tape Dispenser

Features > Takes all 100mtr

tapes on 50mm (2") core > Takes some 150mtr tapes on 50mm core

> Adjustable brake > Heavy duty coarse

toothed blade

PD717

Budget 50mm Pistol Grip Tape

> Metal frame > Takes 132mtr tapes

> 75mm core > Adjustable brake

Dispenser

Features

Heavy Duty

PD705 Foam Grip 50mm

Dispenser

Features Takes 132mtr tapes

Pistol Grip Tape

> 75mm core > Adjustable brake



PD728

Noise Reducing

Tape Dispenser

75mm spring

loaded core Note: only suitable for use with 50mm wide, 75mm core tapes

Features

75mm Pistol Grip











50mm Filament Tape Dispenser

> 75mm core > Replaceable blade















EHD50

Heavy Duty, All Metal 50mm Pistol Grip Tape Dispenser

Features

- > Takes 132mtr tapes > Suction strip
- > Blade saver cap







Replacement blades: RB728 box 10 Replacement tape flaps: RTF728 box 10





- > Metal frame
- construction
 > Takes 132mtr tapes
- > Adjustable brake









- > Replaceable tape flap



Standard 50mm Pistol Grip Tape Dispenser with Plastic Roller























PDFT50

- > 50mm tape width





HSD50B

PDFT75

75mm Filament

Tape Dispenser

75mm tane width

> 75mm core > Replaceable blade

Heavy Duty 50mm Pistol Grip Tape Dispenser

- > 75mm core
- Takes 132mtr tapes > Retractable blade



PD707P Standard 50mm

Pistol Grip Tape Dispenser

- Features
 > Metal frame construction
 > 75mm core
 > Takes 132mtr tapes
- Adjustable brake > Retractable blade

















> For 50mm wide 75mm core tapes > Takes 66mtr and 132mtr tapes

- > Adjustable brake
- > Safety blade cap
- Static charge tape gripDouble edged, replaceable blade













Features > Takes 132mtr tapes > 75mm core > Adjustable brake > Replaceable blade



- Features



Features







Pacplus® Hand Held Tape Dispensers

HPG75B

Heavy Duty 75mm Pistol Grip Tape Dispenser

Features

- > Takes 132mtr tapes
- 75mm core
- > Metal adjustable brake
- > Heavy duty coarse-toothed replaceable blade



RB100 box 10 Replacement tape flaps: RTF100 box 10 PD771

PG100B

Tape Dispenser

100mm

Features > Takes 66mtr tapes > 75mm core > Adjustable brake

Pistol Grip

Extra Heavy Duty 100mm Pistol Grip Tape Dispenser

- Features > Double metal frame > Takes 132mtr tapes
- > 75mm core
- > Fixed brake



100



Duty 75mm Pistol Grip Tape Dispenser

Features

- Double side frame
- > Takes 66mtr tapes > 75mm core
- > Fixed brake











Budget 75mm Pistol Grip Tape Dispenser



HHD50

50mm Compact Carton Sealer

Features

- > Hand pressure
- regulates tension > 50mm tape width
- > 75mm core

D225

25mm Enclosed

Metal Carton

Sealer

Features

> For 25mm

packing tape.



CWF25 25mm Filament

Tape Dispenser

Features

- For crossweave
- & filament tape > Hand pressure
- regulates tension > 25mm tape width > 75mm core

D250

50mm Enclosed

Metal Carton

Sealer

Features

> For 50mm

packing tape.



100





> Takes 132mtr tapes

> 75mm core > Adjustable brake



Features > Metal frame

> Enclosed metal dispenser for 25mm crossweave reinforced tape.

Replacement blades: RBRE25 box 10








Replacement blades: RBRE50 box 10

50mm Filament

Enclosed metal

reinforced tape.

dispenser for















D238

38mm Enclosed Metal Carton Sealer

Features

> For 38mm packing tape.

Replacement blade: RBD38 box 10



PD918 Double Sided

Solid Adhesive Tape Dispenser

Features

- > For 12mm & 19mm double sided tapes Takes 33mtr tapes
- > 25mm core > Trigger activated feed/brake/cutter



PD931

Polypropylene Tape Dispenser Features

- 25mm double sided tissue and polypropylene tapes
- (max. outer diameter 155mm) > 75mm core

> Cutting blade

PD932 Double Sided Tissue &

Polypropylene Tape Dispenser Features

- Suitable for 50mm double sided tissue and polypropylene tapes
- Takes 50mtr tapes (max. outer diameter 155mm)
- > 75mm core > Cutting blade







pagalus













Double Sided Tissue &

Suitable for

Takes 50mtr tapes









Pacplus® Bag Neck Sealers & Bench Tape Dispensers

PD222T

Our most popular bag neck sealer

- > Durable metal frame
- > 9-12mm tape width > Takes 132mtr tanes
- > 7mm throat
- > Trimming blade for excess bag neck
- > Can be fixed to any horizontal or vertical surface





PD283

Heavy Duty Bag Neck Sealer

- > Heavy duty metal frame > 25mm tape width > Takes 132mtr tapes
- > 75mm core
- > 12mm throat
- Replaceable trimming blade for excess bag neck
- > Can be fixed to any horizontal or vertical surface

Replacement blades: RBBN25 Replacement trimming blade: RB2838



BN25

Metal Wide Tape Bag Neck Sealer

- > Metal frame
- > 12mm throat > 16mm tape width > Takes 132mtr
- tapes



Replacement blades RBBN25 box 10



PLBW9

Plastic Dispenser

- > Economy model > Plastic frame
- > 9-12mm tape width
 Takes 132mtr
- tapes > 75mm core
- > 12mm throat









PD223T

Stainless Steel Bag Neck Sealer

- > Ideal for food processing and corrosive environments > 12mm throat
- > 9-12mm tape width > Takes 132mtr tapes
- > 75mm core
- Can be fixed to any horizontal or vertical surface
- > Trimming blade for excess bag neck

Replacement blades: RBBN9 box 10 Replacement trimming blade: RB2228 box 10







Metal Bag Neck Sealer



- > Durable metal frame construction
- > 9-12mm tape width > Takes 132mtr tapes
- > 75mm core
- > Can be fixed to any vertical or horizontal surface
- > Replaceable blade









Metal Wide Neck Bag Sealer



- > Extra heavy duty construction > 9-15mm tape width > Takes 132mtr tapes

- 75mm core
- > 16mm throat
- > Easy tape loading mechanism
- > Adjustable brake > Replaceable blade
- > Packed 6 per carton





PD326

> Economy model

- > 19-25mm tape width
- > Takes 33mtr and 66mtr tapes 25mm & 75mm interchangeable

B2



Bench Dispenser

> Heavy duty construction > Weighted base for

added stability > 25mm tape width

> Takes 66mtr tapes

> 25mm and 75mm

> Integral pen holder > Replaceable blade

interchangeable cores





EXINCTIX

PD32640

Interchangeable Core Bench Dispenser Interchangeable Core Bench Dispenser

- > Economy model > 19-25mm tape width
- Takes 33mtr and 66mtr tapes
- > 25mm & 75mm interchangeable



No blades available

BTD25









Plastic Bench Dispenser

> Heavy duty > 19-25mm tape

width Takes 33mtr and

66mtr tapes 25mm & 75mm interchangeable











Pacplus® Bench Tape Dispensers

BD50 Our Best Selling Heavy II Bench Tape Dispenser

Features

- Metal frameTape bridge for easy operation
- > Dual core takes 2x25mm or 1x50mm
- tape width
- > 75mm core > Takes 132mtr tapes
- > Blade protection attachment > Replaceable blade



PD331P

Heavy Duty Bench Dispenser

- Heavy duty metal frame25mm tape width
- Takes 66mtr tapes
- 75mm core
- Blade protection attachment
- > No blades available



PD317

Standard Bench Dispenser

Features

- Plastic desk dispenser19-25mm tape width
- > Takes 33mtr tapes
- 25mm core > No blades available





HMB50

Replacement blades: RBBD50 box 10

Bench Dispenser

Features

- > Heavy duty metal frame
- > Dual core takes 2x25mm or 1x50mm tanes
- > Takes 132mtr tapes
- > 75mm core
- > Non-slip rubber base
 > Can be fixed to any horizontal or vertical surface

Replacement blades: RBHMB box 10



PD330

Manual Pre-set Length Bench Dispenser

- Manual feed with variable feed increments up to 75mm
- Suitable for filmic tape to 25mm wide on 75mm core
- > Integral pen/scissors holder
- > No blades available



CBD50

Clamp-on Bench Dispenser

- > Clamp-on dispenser requires no tools or fixings > Metal frame allows clamping from either side > Dual core takes 2x25mm or1x50mm tape width
- > Takes 132mtr tanes





PD380

Manual Pre-set Length Bench Dispenser

- > Manual pre-set tape feed
- Variable tape feed increments up to 200mm
 Suitable for filmic tape to 75mm wide

- > 75mm core > No blades available



PD351

75mm or 3 x 25mm Bench Dispenser

- > Metal frame > 3x25mm or 1x75mm tape widths
- > Takes 66mtr tapes
- > 75mm core
- > Blade protection attachment
- > No blades available



PS2A

Electronic Pressure Sensitive Tape Dispenser

- Features > Suitable for filmic, masking and reinforced tapes
- > 6-25mm tape widths
- Dispenses lengths from 20-999mm
- > Takes 66mtr tapes > 75mm core Available only on request, no sale or return Check delivery









High Capacity and Printed Message Adhesive Tapes

Umax

Tape Systems

Maximise productivity with Umax tapes and dispensers

Features

- > High volume roll
- > 25mm core

Benefits

- > Reduced roll change
- > Improved productivity
- > Less waste
- > Less storage

UMAXIMISE

on cartons sealed per roll

UMAXIMISE

on reduced downtime

UMAXIMISE

on tape storage space

UMAXIMISE

on reduced packaging waste

LN150-B

Low Noise Buff Tape

LN150-C

Low Noise Clear



UN150-B

Buff Tape

>25 micron thick

>25 micron thick

>50mm wide

pacelus

pacalus

umax"

>25mm core

UN150-C

Clear Tape



UN200-B

Buff Tape

Clear Tape

BT50B

Umax Tape

Dispenser

UN200-0



>25 micron thick

>50mm wide >25mm core

UMAXKIT Umax Dispenser and Tapes Kit Discover the benefits of using Umax tapes with this handy starter kit! > BT50B Carton Sealer > 1 roll LN150-C clear tape

> Compatible with all Umax tapes > Hinged blade protector > 25mm core

- > 50mm tape width



Bonus Tape

Tape Systems



BBON-2 Hotmelt Buff Tape

CBON-2 Hotmelt Clear Tape



Solvent Buff Tape CBON-1

BBON-1

Solvent Clear Tape





>50mm wide

>28 micron thick

>50mm wide







Bonus Tape Silent Dispenser

- > Adjustable brake > 38mm core

Replacement blades: RB707 box 10 RB707 box 10 Replacement tape flaps: RTF707 box 10







Printed Message Tapes

- > 14 printed message tapes available from stock
- > An essential method of communicating handling instructions to package handlers
- Low-noise premium quality tape
- > Highly visible message > 50mm x 66mtr roll



Sold only in	full case quantities		A
Code	Message	Таре	kg/ case
TW60FRA-V	Fragile	Vinyl	6.7
TW60FRA	Fragile	Polypropylene	6.7
TW60CCSS	Contents Checked Security Sealed	Polypropylene	6.7
TW60GHWC	Glass Handle With Care	Polypropylene	6.7
TW60CPMT	Caution	Polypropylene	6.7
TW60REJ	Reject	Polypropylene	6.7
TW60AWI	Awaiting Inspection	Polypropylene	6.7
TW60HAN	Handle With Care	Polypropylene	6.7
TW60QCH	Q.C. Hold	Polypropylene	6.7
TW60QCI	Q.C. Inspected	Polypropylene	6.7
TW60QCR	Q.C. Rejected	Polypropylene	6.7
TW60QUA	Quarantine	Polypropylene	6.7
TW60TWU	This Way Up	Polypropylene	6.7
TW60SEC	Security	Polypropylene	6.7

Non-Adhesive & Adhesive Tapes

Underground Warning Tapes

- > Non-adhesive polythene
- > Highly visible
- > Alert contractors of the presence and nature of buried pipes and cables
- > 150mm width
- > 365mtr length





Code	Message	kg/ roll
CBT150-EC	Caution Electric Cable	2.5
CBT150-FO	Caution Fibre Optic	2.5
CBT150-GM	Caution Gas Main	2.5
CBT150-SL	Caution Street Light	2.5
CBT150-TC	Caution Telephone Cable	2.5
CBT150-WP	Caution Water Pipe	2.5

PP Hotmelt Machine

- > 28mu polypropylene carrier
- > Suitable for use with machine tapers
- > Hotmelt adhesive
- > 48mm roll width
- > 990mtr length for reduced downtime
- > Available in a selection of colours



Code	Colour	kg case
BMP48	Buff	12.6
CMP48	Clear	12.6
BLUMP48	Blue	12.6
REDMP48	Red	12.6
YELMP48	Yellow	12.6
GMP48	Green	12.6
WHIMP48	White	12.6
BLKMP48	Black	12.6
Rolls per cas	se	

PP Low Noise Acrylic

- > 25-35mu polypropylene carrier
- > Better for the environment



Barrier Tapes

- > Non-adhesive polythene
- > Highly visible
- > Rapidly deployed
- > Convenient dispenser carton
- > 30mu thick
- > 70mm width
- > 500mtr length
- > 10 rolls per outer case



Code	Colours	kg/ roll
PBT70RW	Red/white	0.9
PBT70YB	Yellow/black	0.9

PVC Solvent

- > 35mu vinyl carrier
- > Solvent adhesive for more aggressive adhesion
- > Better for freezer/coldstore environments
- > Available in buff, clear and a selection of colours & widths
- > 75mm tape core

For product codes, use the colour code followed by the width code (e.g. 9mm red tape is RVT9)



Colou Code	r Colour	Width Code Roll Width	9 9mm	12 12mm	25 25mm	50 48mm	75 75mm
BVT	Buff				•	•	•
CVT	Clear		•	•	•	•	•
WVT	White		•	•	•	•	•
RVT	Red		•	•	•	•	
BLVT	Blue		•	•	•	•	
DBLV	r Dark Blue	2				•	
YVT	Yellow		•	•	•	•	
GVT	Green		•	•	•	•	
OVT	Orange					•	
BKVT	Black				•	•	
Rolls	per case)	192	144	72	36	24
	ķ	ig ise	9.6	9.8	9.8	8.9	9.5

PP Hotmelt

- > 28mu polypropylene carrier
- > Solvent-free hotmelt adhesive > Better for the environment


> 66mtr length, 75mm tape core To select tape, choose colour ref. and add tape width (e.g. BHP25 is 25mm buff)




Code	Colour				
BHP	Buff				
CHP	Clear				
Rolls p	per case	144	72	36	24
	kg case	6.7	5.5	5.9	5.8

PP Acrylic

- > 25mu polypropylene carrier
- > Low-cost option for high volume use > Acrylic adhesive better for the environment
- BULK QUANTITY DISCOUNTS AVAILABLE
- BBP48-132, BCP48132 132mtr, all other tapes -66mtr
- > 75mm tape core





Adhesive Tapes

PP Solvent

- > 28mu polypropylene carrier
- > Thicker 28mu carrier film, 66mtr length & 75mm core > Solvent adhesive for more aggressive adhesion
- > Better for freezer/coldstore environments

Sold only in full case quantities

Code Size/colour	kg	Code Size/Colour	kg
BSP50 48mm Buff	6.5	BSP75 75mm Buff	6.5
CSP50 48mm Clear	6.5	CSP75 75mm Clea	r 6.5
Rolls per case		Rolls per case	

Polycoated Cloth

- > Laminated polycoated cloth carrier
- > Synthetic rubber adhesive
- > Waterproof and weather resistant
- > Easy-tear
- > 50mtr length, 75mm tape core
- > 60 cases per pallet
- > Bulk quantity discounts
- > Special roll widths available on request



				kg
Code	Colour	Width	Rolls/case	caśe
PCT25-S	Silver	25mm	24	10.3
PCT50-B	Black	50mm	24	12.8
PCT50-W	White	50mm	24	12.8
PCT50-S	Silver	50mm	24	12.8
PCT75-B	Black	75mm	16	11.9
PCT75-W	White	75mm	16	11.3
PCT75-S	Silver	75mm	16	10.4
PCT90-B	Black	90mm	12	9.7
PCT90-W	White	90mm	12	9.7
PCT90-S	Silver	90mm	12	9.7

Aluminium Foil

- > Solvent-acrylic adhesive
- > Waterproof and heat resistant
- > Extensively used in construction and installation
- > Silicon release liner
- > 45mtr length, 75mm tape core
- > Available in 30mu and 40mu thicknesses



Code	Width	Thickness	Rolls/case	kg case
AFT25	25mm	30mu	48	9.5
AFT38	38mm	30mu	36	10.8
AFT50	50mm	30mu	24	9.5
AFT2540	25mm	40mu	48	12.7
AFT3840	38mm	40mu	36	14.4
AFT5040	50mm	40mu	24	12.7

PP Economy Acrylic

- > 23mu polypropylene carrier
- > Acrylic adhesive > Better for the environment
- > 48mm width, 75mm tape core
- > 66mtr length



Kraft Paper

- > Solvent adhesive for longerlasting adhesion
- > Easy-tear, high quality kraft paper carrier
- > Ideal for perfectly finished
- packing and presentation
 > Widely used in picture framing etc.
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg
ECO25	25mm	72	9.0
ECO38	38mm	48	9.0
ECO50	50mm	36	9.0
ECO75	75mm	24	9.0

Pacplus® Masking

- > High quality crêpe paper
- > General purpose usage masking, packing, draughtsmanship
- > Hotmelt adhesive
- > Residue-free removal
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg
MSK12	12mm	144	9.22
MSK19	19mm	96	8.92
MSK25	25mm	72	9.18
MSK38	38mm	48	9.24
MSK50	50mm	36	9.86
MSK75	75mm	24	9.0
MSK100	100mm	18	8.66

Tesa® Masking


- > Recognised Tesa® brand product
- > General purpose usage masking, packing, draughtsmanship
- > Solvent adhesive
- > Residue-free removal
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg case
4323-12	12mm	144	9.28
4323-19	19mm	96	9.12
4323-25	25mm	72	9.28
4323-38	38mm	48	9.28
4323-50	50mm	36	9.06
4323-75	75mm	24	9.18
4323-100	100mm	18	9.52

Coloured PP Acrylic

- > 28mu polypropylene carrier
- > Bold solid colours
- > Useful for colour-coding components, products or packages during stages of production or processing > 50mm width, 75mm tape core
- > 66mtr lenath







9.02 9.60

Double-Sided Adhesive Tapes

Finger Lift

- > Synthetic rubber adhesive
- > 12mm wide double-sided tape
- > 18mm wide release liner for easy removal after tape application
- > Suitable for bonding paper and board products
- > 50mtr length, 75mm tape core
- > 40 rolls per case



Polypropylene Solvent

Rolls/case

- > Longer-lasting adhesion
- > Suitable for general industrial use including carpet fitting
- > 25mtr length, 75mm tape core



Code	Width	Rolls/case	kg
TD112DE	12mm/18mr	m 40	4.2

Transfer (Solid Adhesive)

- > Carrier-free solvent-acrylic adhesive
- > Suitable for use with Pacplus PD918 Dispenser
- > 33mtr length, 75mm tape core



Code	Width	Rolls/case	kg
TRN12	12mm	72	5.06
TRN19	19mm	36	5.08

Tissue Carrier

- > Synthetic rubber-resin adhesive
- > Easy-tear
- > Tissue paper carrier
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg
TD125	25mm	144	9.26
TD150	50mm	96	21.87

Polypropylene Hotmelt

- > Suitable for general purpose use
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg
DST12	12mm	144	18.5
DST19	19mm	96	19.0
DST25	25mm	72	16.7
DST50	50mm	36	17.0

uPVC Acrylic

- > Heavy duty uPVC carrier
- > Permanently bonds to most substrates
- > High resistance to ageing caused
- by temperature and UV exposure > 50mtr tape length, 75mm tape core



Code	Width	Rolls/case	kg
DST9V	9mm	128	18.9
DST25V	25mm	48	19.9
DST50V	50mm	24	17.0

50mm Cloth Carrier

Width

25mm

- > Strong synthetic rubber-resin adhesive
- > Water resistant

Code

Cod

DST25-25

DST50-25

- > Suitable for flooring and heavy duty industrial applications
- > 50mtr length, 75mm tape core



de	Width	Rolls/case	kg
250	50mm	24	16.4

Polyester Premium Acrylic

- > Acrylic/solvent blend adhesive
- > Ideal for mounting onto ABS plastics in industrial applications
- > 50mtr length, 75mm tape core



Code	Width	Rolls/case	kg
DST4965	50mm	24	16.8


Polyethylene Foam Pads

- > High-tack acrulic, solvent-based adhesive
- > Pre-cut pads on the roll
- Suitable for mounting onto uneven surfaces
- > Used for graphics and display mounting

Code	Width	Thickness	Pads/roll	kg
DFP12	12 x 25mm	1.6mm	2,500	4.10
DFP25	25 x 25mm	1.6mm	1,250	4.10

Polyethylene Foam

- > High-tack acrylic-solvent adhesive
- > 12 rolls/carton
- > Suitable for mounting onto uneven surfaces
- > Used for graphics and display mounting



Adhesive Tapes & Banding Machine

Crossweave Reinforced

- > Synthetic rubber-resin adhesive
- High bond strength
- > Optimum tear resistance
- > Lateral and longitudinal glassfibre reinforcement
- > Available in a range of widths from 12-75mm
- > 50mtr lenath

Code	Width	Rolls/case	kg
CRT12	12mm	72	5.7
CRT19	19mm	48	6.1
CRT25	25mm	36	6.6
CRT38	38mm	24	6.2
CRT50	50mm	18	6.6
CRT75	75mm	12	6.1

Monoweave Reinforced

- > Synthetic rubber-resin adhesive
- > High bond strength
- > Good tear resistance
- > Lower-cost alternative to crossweave tane
- > Longitudinal glassfibre reinforcement
- > 50mtr length

Code	Width	Rolls/case	kg
MONO25	25mm	36	6.16
MONO50	50mm	18	6.22

Strapping Tape

- > High-strength tensilised polypropylene carrier
- > Synthetic rubber-resin adhesive
- > 19mm width
- > 66mtr length
- > Available in black and orange
- > 96 rolls per case



Code	Colour	Thickness	kg ctn/96
ST1966-BLK	Black	97mu	12.5
ST1966-OR	Orange	72mu	9.6

Stationery

- > Solvent-free acrylic adhesive
- High transparency easy-tear polypropylene carrier
- > Suitable for general office use

> Available in black and white

- > 25mm width
- > 66mtr length

Code	Width	Rolls/case	kg case
CST25	25mm	72	6.16



Hook & Loop Tape

- > Self adhesive hook and loop fasteners
- > Hotmelt pressure-sensitive adhesive
- > 20mm tape width
- > 5mtr length
- > Supplied as a set of
- > 1 roll hook tape > 1 roll of loop tape
- > Available in black and white

Code	Colour	per 2 foll set
HLSA-20B	Black	15.0
HLSA-20W	White	15.0

AX30 Bandina Machine



Features:

- > Compact desktop design
- > 300 x 200mm arch > Three-point tension control
- > Microprocessor driven
- pre-programmed settings Three cycle initiation options:
- 1. Auto start
- 2. Manual button start
- 3. Foot switch

- > Simple and reliable to use > Suitable for banding all printed
- material including banknotes

Specifications

- > Arch Dimensions (W x D x H): 300 x 200mm
- > Tape width: 30mm
- > Cycle time: 3.0-3.3 seconds @50Hz
- > Power supply: 220V 50/60Hz

Banding Tapes

- > Available in plastic and paper
- > Use with AX30 banding machine for secure and attractive banding of all printed materials

Туре

> Packed 10 per case



10.2



Code	Colour	per 2 roll set
HLCA-19B	Black	15.0
HLCA-19W	White	15.0



Pacplus® Heat Sealer & Shrink Film Systems

KITIB450 Maintenance Kit

KITIB800 Maintenance Kit

> 1 x element wire > 1 x lower teflon

> 2 x upper teflon > 1 x 10A fuse



IBAR450 Sealer

> 1 x element wire > 1 x lower teflon > 2 x upper teflon > 1 x 10A fuse > Dimensions: 310 x 630 x 150mm

> Max. film width: 450mm > Power supply: 240V 50Hz > Power usage: 350W

> Sealing timer: 1.0 – 3.0 seconds



IBAR800 Sealer

310 x 980 x 250mm > Dimensions:

> Max. film width: 800mm > Power supply: 240V 50Hz > Power usage: 700W

> Sealing timer: 1.0 – 3.0 seconds



LBS300 L-Bar Heat Sealer





HABSTD Hot Air Gun Stand

Holds the HAB1500 at a convenient angle for repeat use

Reduces the risk of burn damage and injury



HABSTD Hot Air Gun Stand

(All ordered separately)

PHS Hand Held Heat Sealers

- > Up to 2 x 200mu (800g) film thickness
- > 150mm max. seal width
- > Available in flat or crimp

Benefits:

- > Portable heat sealing for items too large for bench mounted sealers
- > Capable of sealing a wide range of substrates, including barrier foil such as coffee bags




Code	Description	kg
PHS150	Flat sealer, suitable for polythene bags and tubing	1.22
PHS150C	Crimp sealer for cellophane, polypropylene, barrier foil and other laminates	1.22

AMI Automatic Impulse Heat Sealers

Features:

- > Electronic timer
- Electromagnetically controlled sealing head
- > Footpedal included as standard
- > Up to 2 x 150mu (600g) film thickness

- > Consistent seal integrity
- Reduced risk of operator error
- > Heavy duty sealing



Code	Description	kg	*Parts kit includes:
AMI-450	450mm wide seal	22.0	> 2 x elements
AMI-600	600mm wide seal	25.0	> 2 x silicon pads > 1 x teflon roll
AMI450KIT	Parts kit for AMI-450*	0.22	> 2 x lower teflon strips
AMI-600KIT	Parts kit for AMI-600*	0.22	2 A tower tenon surps

CCHS Constant Heat Sealers

Features:

- > Freestanding
- > Treadle-operated sealing head

- > Hands-free operation facilitates sealing of large bagged products
- > Constant heat gives higher temperatures needed for foil lined bags
- > Excellent for sealing plain and gusseted foil bags.

Specifications:

> Temperature range: 30-200°C > Max seal thickness: 2 x 0.25mm > Seal width: 10mm



Pacplus® Impulse Heat Sealers

Pacplus Impulse Heat Sealers



Code	Size	kg	Code	kg	Kits for IS-Type impulse heat sealers with integral cutter contain:
IS200C	200mm (with cutter)	3.85	IS2KIT	0.02	> 1 blade
IS300C	300mm (with cutter)	5.0	IS3KIT	0.02	> 2 elements
IS400C	400mm (with cutter)	6.12	IS4KIT	0.02	> 3 upper teflons
IS500C	500mm (with cutter)	8.2	IS5KIT	0.02	> 1 lower teflon
IS200	200mm (without cutter)	3.85	KIT200	0.02	Kits for IS-Type impulse heat sealers without integral cutter contain:
IS300	300mm (without cutter)	5.0	KIT300	0.02	> 2 elements
IS400	400mm (without cutter)	6.12	KIT400	0.02	> 3 upper teflons
IS500	500mm (without cutter)	8.2	KIT500	0.02	> 1 lower teflon

PSFS400 PVC Shrink Film System

PSFS400 System

- > Contains:
- > IS400RW Round Wire Sealer
- > HAB1500 Hot Air Shrink Gun
- > 450WB Film Unroller
- > Ideal for low-volume and entry-level use



RW400KIT

IS400RW Repair Kit

- > Contains:
- > 2 x replacement wires
- > 1 x lower teflon
- > 1 x upper teflon



IS400RW

Round Wire Sealer





Optimax[®] C-type and heavy duty S-type impulse heat sealers are designed for higher volume usage.

Find them on pages 62 and 63





Polythene Layflat Tubing



Code	Roll width	Average length/roll	kg
PT252	2"	335mtr	2.46
PT253	3"	335mtr	3.22
PT254	4"	335mtr	4.0
PT255	5"	335mtr	5.0
PT256	6"	335mtr	6.0
PT258	8"	335mtr	8.0
PT259	9"	335mtr	9.0
PT2510	10"	335mtr	10.0
PT2512	12"	335mtr	12.0
PT3150	12"	150mtr	5.5
PT2515	15"	335mtr	15.0
PT2518	18"	466mtr	25.0
PT2524	24"	349mtr	24.0
PT2536	36"	233mtr	26.3
PT2536BK	36" Blk	233mtr	26.3

> 125mu (500 gauge)

Code	Roll width	Average length/roll	kg
PT502	2"	168mtr	2.0
PT503	3"	168mtr	3.24
PT504	4"	168mtr	4.0
PT506	6"	168mtr	6.0
PT507	7"	168mtr	7.0
PT508	8"	168mtr	8.0
PT509	9"	168mtr	9.0
PT5010	10"	168mtr	10.0
PT5012	12"	168mtr	12.0
PT5024	24"	183mtr	24.0

Anti-Static Layflat Tubing



Code	Roll width	kg
AST2512-150	12"	5.86
AST256-150	6"	2.96

Polyolefin Shrink Film

- Approved for food industries and cold storage
 Suitable for wrapping irregular shapes and bundling multiple items
 Easily recyclable
- > Doesn't discolour or become brittle with age
- > Quantity prices apply to mixed-size orders

Code	Folded/ unfolded width	Roll length	Thickness	kg
PLO-25	250/500mm	1335mtr	15mu	10.1
PLO-30	300/600mm	1335mtr	15mu	11.4
PLO-35	350/700mm	1335mtr	15mu	13.6
PLO-3019	300/600mm	1070mtr	19mu	12.4

PVC Shrink Film

- > 19 mu thickness > 600mtr roll length > High film clarity > Low shrink temperature
- > Fast seal/shrink cycle
- > Quantity prices apply to mixed-size orders



Code	Size	kg
PVC20	200/400mm x 600mtr	4.6
PVC25	250/500mm x 600mtr	5.7
PVC30	300/600mm x 600mtr	6.9
PVC35	350/700mm x 600mtr	7.6
PVC40	400/800mm x 600mtr	8.8
PVC45	450/900mm x 600mtr	9.8
PVC50	500/1000mm x 600mtr	10.9

TLD40 Layflat Tubing Dispenser

- > Adjustable from 400–1050mm.
 - > Will hold up to 40kg





- > Also suitable for polythene layflat tubing

Cod	le Roll width	kg
300	300mm	1.7
450	WB 450mm	2.4
600	IWB 600mm	2.8

Pacplus® Knives and Cutters



Every feature of the Cruze Cutter has been designed to make it the best film and tape slitter on the market.



Wide body with textured panels, four finger grips and thumb rest give highly controllable and comfortable left and right handed use, regardless of hand size.



Large tape slitter easily perforates carton tape seals without risking damage to contents.



Curved jaws lift the film to prevent snagging on underlying surfaces and protect the film slitting blade from damage or causing injury.



Pen clip and eyelet keep the CX3 within easy reach at all times, either in a pocket or on a lanyard.



> Packed 12 per box



BNL/BNR Safety Cutters

- Features
 > BNL for left-handed users
 BNR for right-handed users > Blade retracts as contact with
- surface is lost
- > Eyelet for lanyard > 12 per box





PDC18 18mm Snap-off Blade Knife

- Features > Heavy duty knife > Lockable blade
- > 12 per box > 20 boxes per outer case



9mm Snap-off Blade Knife

> Heavy duty knife > Lockable blade > Eyelet for lanyard > 24 per box

RB9 replacement blades

> 12 boxes per outer case

MCO

Multipurpose Carton Opener

Features

- > Carton opener > Staple remover
- String and plastic strap slitter
- > Film cutter
- > 12 per box



BNL.RB replacement blades

CPK18

18mm Snap-off Blade Knife

- > Heavy duty knife > Lockable blade
- > Eyelet for attachment to lanyard > 12 per box
- > 12 boxes per outer case



BSC

Box Cutter

- > Concealed slitter blade > Retractable hooked blade
- > 12 per box



SX5 Safety Cutter

RB18 replacement blades

- > For paper and lightweight sheet material
- > 12 per box > 12 boxes per outer case



BDP100 Utility Knife Blade Dispenser

- > Contains 100 blades > Stores and dispenses blades safely
- > 40 dispensers per outer









Pacplus® Knives and Cutters

SNL/SNR Safety Cutters

- Features > SNL- for left-handed users
- SNR for right-handed users > Blade retracts as contact with surface is lost > Eyelet for lanyard

- > 10 cutters per box > 5 boxes (50 cutters) per outer

Replacement blades SNR-RB



Metal Retractable Knife

- > Heavy duty metal knife > Lockable blade
- > Eyelet for lanyard > 12 knives per box
- > 12 boxes (144 knives) per outer

Replacement blades Pack of 10 RCB Dispenser of 100 BDP100



CHS Safety Cutter

- > Lockable, auto-retractable blade
- > 3 pre-set cutter depth adjustments

> 10 per box





EST Safety Cutter

- Features > Lockable, auto-retractable blade
- > Flat head facilitates straight line
- > 3 pre-set cutter depth adjustments > Colour may vary



ACK

- **Features** > Assists accurate slitting

Safety Corner Cutter

- of carton corners > Heavy duty knife
- > Lockable blade
- 12 per box
- > 20 boxes per outer



FET Safety Cutter

- Features > Lockable, auto-retractable blade
- > Metal head for reduced friction
- > 3 pre-set cutter depth adjustments > 10 per box





EST-G Safety Cutter

- > Lockable, auto-retractable blade > Flat head facilitates straight line cutting
- > 3 pre-set cutter depth adjustments
- > Colour may vary > 5 per box



ACK-G

Replacement blades 152.6LA

Safety Corner Cutter

Features

- > Assists accurate slitting of carton corners
- > Heavy duty knife > Lockable blade





FET-G Safety Cutter

Features

- Lockable, auto-retractable blade
- > Metal head for reduced friction wear
- > 3 pre-set cutter depth adjustments
- > 10 per box



Replacement blades BGSKRB



MA1

Replacement blades BGSKRB

Multi-Function Cutter

Features

- > Ideal for cutting stretchfilm and
- plastic strapping Integral thumbnail tape cutter
- > Eyelet for lanyard > 12 per box

Replacement blades MA1-RB



FSC

Multi-Function Cutter

- > Ideal for cutting stretchfilm and
- plastic strapping
 > Integral thumbnail tape cutter
- > Eyelet for lanyard > 10 per box





MSC

Box Cutter

Features

- Concealed slitter blade
- > Retractable hooked blade > 12 per box



RCB

Utility Knife Blade Pack

Features

- > Translucent plastic container > Contains 5 blades





RB9

9mm Snap-off Blades

Features

- > Translucent plastic container
- > Contains 10 blades
- > 24 packs per box > 10 boxes per outer



RB18 18mm Snap-off Blades

- Features > Translucent plastic container
- > Contains 10 blades



KNLRB-10 18mm Utility Knife Blades

- Features
 > Translucent plastic container
- > Contains 10 blades









Pacplus® Knives, Lanyards, Scissors and Tape Measures

LDK9 9mm Snap-off Blade Knife Features > Lockable blade > 24 knives per box > 20 boxes (480 knives) per outer

MDC18 18mm Snap-off Blade Knife

Features

- > Lockable blade > 24 knives per box
- > 20 boxes (480 knives) per outer



KNL/KNR Budget Safety Cutters

Features

- Features
 > KNL for left-handed users
 KNR for right-handed users
 > Blade retracts as contact with
 surface is lost
- > Eyelet for lanyard > 12 cutters per box
- > 20 boxes (240 cutters) per outer



Replacement blades KNLRB-10

EFC12 Stretchfilm Cutter

Replacement blades RB9

- > For cutting stretchfilm, bubble film and shrinkfilm
- > 12 per box



MLY Metal Retractable Lanyard

- > Metal chain retracts into metal
- lanyard casing > Belt hook

Replacement blades RB18


> 10 per box



LY1 Plastic Lanyard

Features

- > 10 per box > 25 boxes (250 lanyards) per outer



TM5

5mtr Tape Measure



SG160 General Purpose Scissors

Features > Packed 25 per box



SG220

Industrial Serrated Blade Scissors

Features

> Packed 25 per box



Knife/Cutter Blades

Code	Compatible with	Blades per pack
152.6LA	CHS, FET, EST, ACK	100
BGSKRB	ACK-G, EST-G, FET-G	10
489-3-10	FSC	10
489-3-100	FSC	100
BDP100	MRK	100
BNLRB	BNL, BNR	100
KNLRB-10	KNL, KNR	10
MA1-RB	MA1	10
RB18	CPK18, MDC18, PDC18	10
RB9	CPK9, LDK9	10
RCB	MRK	5
SNR-RB	SNL, SNR	100

SG230

Industrial Comfort Grip Scissors

Features > Packed 25 per box





Sub-brands

- > Tenzalopes®-packing list envelopes and associated products
- > Tenzalopes® Green the oxy-biodegradable alternative to Tenzalopes®
- > Tenzapac® plastic bag products
- > Tenzapost® postal products

tenza®



? a

Tenzalopes® Envelopes & Documents Enclosed Wallets

4.7

Tenzalopes® Packing List Envelopes

> Unprinted self-adhesive clear plastic envelopes

Code	Internal size (mm)	Qty per box	kg/ box
A7PL	113 x 100	1,000	1.9
A6PL	165 x 122	1,000	3.4
A5PL	225 x 165	1,000	5.8
A4PL	318 x 235	500	5.8
DLPL	225 x 122	1,000	4.6



Tenzalopes® Documents Enclosed Wallets

- > Printed self-adhesive clear plastic wallets > Printed **DOCUMENTS ENCLOSED**
- Internal Qty per box Code size (mm) **A7DE** 113 x 100 1,000 1.9 1.000 3.4 **A6DF** 165 x 122 **A5DE** 225 x 165 1,000 5.8 **A4DE** 318 x 235 5.8 500




Tenzalopes® Documents Enclosed Wallets (French)

1,000

- > Printed self-adhesive clear plastic wallets
- > Printed DOCUMENTS CI-INCLUS

DLDE 225 x 122

Code	Internal size (mm)	Qty per box	kg/ box
A7DC	113 x 100	1,000	1.9
A6DC	165 x 122	1,000	3.4
A5DC	225 x 165	1,000	5.8
A4DC	318 x 235	500	5.8
DLDC	225 x 122	1,000	4.7



Tenzalopes® Penalty Charge & Parking Charge Notice Wallets

- > Low tack adhesive
- > Standardised message and graphics, suitable for use in any location

Code	Internal size (mm)	Qty per box	kg/ box
PCNE	130 x 120	1,000	2.0
PCNE-2	136 x 100	1,000	2.0





PCNF-2



Biodegradable Packing List Envelopes

Qty per box

1,000 1.000

1,000

500

1,000

> Plain self-adhesive clear plastic wallets

Internal

A6GRPL 165 x 122 **A5GRPL** 225 x 165

A4GRPL 318 x 235

DLGRPL 225 x 122

size (mm) **A7GRPL** 113 x 100

Code



ALTERNATIVE
kg/ box
1.9
3.3
5.8





Biodegradable **Documents Enclosed Wallets**

> Printed self-adhesive clear plastic wallets > Printed **DOCUMENTS ENCLOSED**

Code	Internal size (mm)	Qty per box	kg/ box
	113 x 100	1,000	1.9
A6GRDE	165 x 122	1,000	3.3
A5GRDE	225 x 165	1,000	5.8
A4GRDE	318 x 235	500	5.7
DLGRDE	225 x 122	1,000	4.7



Tenzalopes® Pouch Tape



- > Pouch Tape is more cost-effective, faster to use in a busy environment and produces less packaging waste than traditional Documents Enclosed wallets. The pouches are created from a single layer of non-adhesive film with a border of adhesive surrounding the pouch area.
- > This eliminates the need for a dual film layer or peelable backing sheet.
- > Approx. 330 pouches per roll

Code	Internal size (mm)	Qty per box	kg/ box
PT150	144 x 200	12	6.6

PLPT Pouch Tape Dispenser



> Accurate and rapid dispenser for Tenzalopes® PT150 Pouch Tape



Tenzapac® Polythene Bags

Heavy Duty Plain Grip Seal Bags



0.10

酒川

> /5mu									
Code	Size (inches)	Qty per outer	Qty per pack	kg pačk	Code	Size (inches)	Qty per outer	Qty per pack	kg pack
MT20-75	5 x 8	1,000	1,000	2.2	MT50-75	9 x 14	1,000	1,000	6.6
MT30-75	7 x 10	1,000	1,000	5.4	MT60-75	12 x 16	500	500	10.2
MT40-75	8 x 12	1,000	1,000	8.6	MT70-75	10 x 18	500	500	9.3

Extra Heavy Duty Plain Grip Seal Bags

> 87.5	mu (350g)								
Code	Size (inches)	Qty per outer	Qty per pack	kg pack	Code	Size (inches)	Qty per outer	Qty per pack	
WT10	3.5 x 4.5	12,000	1,000	2.2	WT50	9 x 14	1,000	1,000	
WT20	5 x 8	4,000	1,000	5.4	WT60	12 x 16	500	500	
WT30	7 x 10	2,000	1,000	8.6	WT70	10 x 18	500	500	
WT40	8 x 12	2,000	1,000	10.8					

Premium Duty Plain Grip Seal Bags

> 45m	าบ				> 50m	าบ			
Code	Size (inches)	Qty per outer	Qty per pack	kg pack	Code	Size (inches)	Qty per outer	Qty per pack	
SG0	1.5 x 2.5	50,000	1,000	0.4	SG10	7.5 x 7.5	6,000	1,000	
SG1	2.25 x 2.25	40,000	1,000	0.5	SG11	C5 6 x 9	6,000	1,000	
G2	2.25 x 3	30,000	1,000	0.6	SG12	8 x 11	4,000	1,000	
SG3	3 x 3.25	20,000	1,000	0.8	SGA4	C4 9 x 12.75	2,000	1,000	
G4	3.5 x 4.5	20,000	1,000	1.0	SG13	12.75 x 12.75	2,000	1,000	
G5	4.5 x 4.5	20,000	1,000	1.5	SG14	10 x 14	2,000	1,000	
G6	4 x 5.5	16,000	1,000	1.5	SG15	11 x 16	1,000	1,000	
SG7	5.5 x 5.5	8,000	1,000	2.1	SG16	C3 13 x 18	1,000	1,000	
SG8	3 x 7.5	12,000	1,000	1.5	SG17	15 x 20	1,000	1,000	
SG9	5 x 7 5	8 000	1.000	2.5					

Premium Duty Write-On Grip Seal Bags

> 45m	าน					> 50mu				318
Code	Size (inches)	Qty per outer	Qty per pack	P	kg back	Code	Size (inches)	Qty per outer	Qty per pack	kg
SG020	1.5 x 2.5	50,000	1,000	C).4	SG129	7.5 x 7.5	6,000	1,000	3.9
SG120	2.25 x 2.25	40,000	1,000	C	0.6	SG130 C5	6 x 9	6,000	1,000	4.0
SG121	2.25 x 3	30,000	1,000	C	0.7	SG131	8 x 11	4,000	1,000	6.7
SG122	3 x 3.25	20,000	1,000	1	1.0	SG132 C4	9 x 12.75	2,000	1,000	9.0
SG123	3.5 x 4.5	20,000	1,000	1	1.5	SG133	10 x 14	2,000	1,000	10.2
SG124	4.5 x 4.5	20,000	1,000	1	1.7	SG134	11 x 16	1,000	1,000	13.0
SG125	4 x 5.5	16,000	1,000	1	1.6	SG135 C3	13 x 18	1,000	1,000	16.7
SG126	5.5 x 5.5	8,000	1,000	2	2.5	SG136	15 x 20	1,000	1,000	21.4
SG127	3 x 7.5	12,000	1,000	2	2.1	MB70	6"x 9" + 6"x 8"			7.0
SG128	5 x 7.5	8,000	1,000	2	2.8	Specimen	pouch	4,000	1,000	
SG105	2 x 9	16,000	1,000	1	1.4	Bags				

Standard Duty Plain Grip Seal Bags

> 40r	nu				> 45mu				1
Code	Size (inches)	Qty per outer	Qty per pack	kg pačk	Code	Size (inches)	Qty per outer	Qty per pack	kg pačk
LG0	1.5 x 2.5	50,000	1,000	0.4	LG10	7.5 x 7.5	4,000	1,000	3.9
LG1	2.25 x 2.25	40,000	1,000	0.5	LG11	6 x 9	4,000	1,000	3.6
LG2	2.25 x 3	30,000	1,000	0.6	LG12	8 x 11	3,000	1,000	5.7
LG3	3 x 3.25	20,000	1,000	0.8	LGA4	9 x 12.75	2,000	1,000	7.6
LG4	3.5 x 4.5	16,000	1,000	1.4	LG13	12.75 x 12.75	1,000	1,000	11.7
LG5	4.5 x 4.5	12,000	1,000	1.4	LG14	10 x 14	2,000	1,000	8.9
LG6	4 x 5.5	10,000	1,000	1.5	LG15	11 x 16	1,000	1,000	11.1
LG7	5.5 x 5.5	8,000	1,000	1.9	LG16	13 x 18	1,000	1,000	16.6
LG8	3 x 7.5	12,000	1,000	1.4	LG17	15 x 20	1,000	1,000	19.5
LG9	5 x 7.5	6,000	1,000	2.4					

Standard Duty Write-On Grip Seal Bags

> 40mu			
Code	Size (inches)	Qty per outer	Qty per pack
LG020	1.5 x 2.5	50,000	1,000
LG120	2.25x2.25	40,000	1,000
LG121	2.25 x 3	30,000	1,000
LG122	3 x 3.25	20,000	1,000
LG123	3.5 x 4.5	16,000	1,000
LG124	4.5 x 4.5	12,000	1,000
LG125	4 x 5.5	10,000	1,000
LG126	5.5 x 5.5	8,000	1,000
LG127	3 x 7.5	12,000	1,000
LG128	5 x 7 5	4 000	1 000



Premium Duty Plain Slider Grip Seal Bags



Code	Size (mm)	Qty per pack	kg pačk
SLG10	250 x 175	250	2.3
SLGA4	225 x 315	250	3.0
SLG2015	5 200 x 150	300	2.1
SLG2216	5 220 x 160	300	2.4
SLG2432	2 240 x 320	300	4.4

		_	
Code	Size (mm)	Qty per pack	kg pack
SLG2517	250 x 175	300	2.7
SLG3223	320 x 230	300	3.9
SLG3625	360 x 250	300	4.8
SLG3925	390 x 250	300	5.2

Clear Self Seal Bags

- > 40mm self adhesive flap
- > 6mm diameter vent holes

Code	Size (mm)	Qty per pack	kg pačk
SSP10	100 x 100	1,000	1.3
SSP12	120 x 200	1,000	2.4
SSP15	150 x 250	1,000	4.3
SSP16	160 x 220	1,000	4.0
SSP20	200 x 280	1,000	5.7
SSP22	220 x 310	1,000	7.2
SSP23	230 x 340	1,000	8.1

Code	Size (mm)	Qty per pack	kg pack
SSP25	250 x 180	1,000	5.2
SSP26	260 x 400	1,000	11.1
SSP30	300 x 420	1,000	13.2
SSP35	350 x 450	1,000	16.5
SSP40	400 x 600	1,000	24.6
SSP45	450 x 700	250	8.4

Clear Self Seal Bags with Child Warning Notice

- > 50mm self adhesive flap
- > 6mm diameter vent holes

Code	Size (mm)	Qty per pack	kg pack
CWSSP20	200 x 280	1,000	6.0
CWSSP23	230 x 340	1,000	8.3
CWSSP26	260 x 400	1,000	11.0

1	Code	Size (mm)	Qty per pack	kg pačk
	CWSSP30	300 x 420	1,000	12.8
	CWSSP35	350 x 450	1,000	15.4
	CWSSP45	450 x 700	250	8.0

Clear Drawstring Bags

> 50mu			
Code	Size (mm)	Qty per pack	k
PDB10	100 x 150	1,000	2.
PDB15	150 x 210	1,000	4.
PDB25	250 x 370	1,000	9.





Tenzapac® Polythene Bags



> 25mu (100 gauge)

Code	Width (inches)	Height (inches)	Thickness (gauge)	Qty per pack	kg pačk
PB7910	7	9	100	1,000	1.7
PB81010	8	10	100	1,000	2.5
PB101210	10	12	100	1,000	3.2
PB101510	10	15	100	1,000	4.3
PB121510	12	15	100	1,000	4.8
PB121810	12	18	100	1,000	5.6
PB152010	15	20	100	1,000	5.7
PB182410	18	24	100	1,000	5.8
PB243610	24	36	100	1,000	11.3

> 30mu (120 gauge)

Code	Width (inches)	Height (inches)	Thickness (gauge)	Qty per pack	kg pačk
PB4612	4	6	120	1,000	8.0
PB61012	6	10	120	1,000	2.0
PB7912	7	9	120	1,000	2.1
PB81012	8	10	120	1,000	2.7
PB101212	10	12	120	1,000	4.1
PB121812	12	18	120	1,000	7.8
PB182412	18	24	120	500	7.4
PB202412	20	24	120	500	8.2
PB364812	36	48	120	125	7.4

Medium Duty

> 50-62.5mu (200-250 gauge)

Code	Width (inches)	Height (inches)	Thickness (gauge)	Qty per pack	kg
PB4820	4	8	200	1,000	2.0
PB6820	6	8	200	1,000	2.6
PB61020	6	10	200	1,000	3.6
PB7920	7	9	200	1,000	3.8
PB81020	8	10	200	1,000	3.9
PB81220	8	12	200	1,000	4.7
PB101220	10	12	200	500	3.3
PB101520	10	15	200	500	4.1
PB121520	12	15	200	500	4.6
PB121820	12	18	200	500	5.9
PB152020	15	20	200	500	8.6
PB182420	18	24	200	500	12.54
PB203020	20	30	200	500	16.3
PB364820	36	48	200	100	9.5
PB4625	4	6	250	1,000	1.7
PB5725	5	7	250	1,000	2.6
PB81025	8	10	250	1,000	4.6
PB81425	8	14	250	1,000	7.6
PB101225	10	12	250	1,000	6.9
PB121825	12	18	250	1,000	7.8
PB122425	12	24	250	1,000	10.4
PB162025	16	20	250	500	5.7
PB202425	20	24	250	250	6.9
PB364825	36	48	250	100	10.5

Heavy Duty

> 100-200mu (400-800 gauge)

Code	Width (inches)	Height (inches)	Thickness (gauge)	Qty per pack	kg pack
PB4640	4	6	400	1,000	2.5
PB6840	6	8	400	500	2.5
PB61040	6	10	400	500	3.5
PB81040	8	10	400	500	4.4
PB101240	10	12	400	250	3.4
PB101540	10	15	400	250	4.2
PB121840	12	18	400	250	6.1
PB152040	15	20	400	100	6.55
PB182440	18	24	400	200	9.3
PB203040	20	30	400	100	6.7
PB243640	24	36	400	100	9.8
PB7950	7	9	500	1,000	4.0
PB81250	8	12	500	500	6.3
PB81550	8	15	500	250	4.1
PB101250	10	12	500	500	7.8
PB121850	12	18	500	500	14.0
PB182050	18	20	500	100	4.8
PB182450	18	24	500	200	11.6
PB203050	20	30	500	100	7.8
PB243650	24	36	500	100	13.3
PB305050	30	50	500	50	10.0
PB364850	36	48	500	50	11.5
PB254080	25	40	800	50	10.8



> 12mu				
Code	Size (mm)	Gusset (mm)	Qty per pack	kg
GPB3070-12	300 x 700	200	1,000	8.2
GPB4050-12	400 x 500	300	1,000	7.8
GPB4090-12	400 x 900	300	1,000	14.6
GPB60120-12	600 x 1200	500	500	15.3
GPB60130-12	600 x 1300	400	1,000	14.2
GPB6060-12	600 x 600	400	250	6.0

Code	Size (mm)	Gusset (mm)	Qty per pack	kg
GPB60100-40-30	600 x 1000	400	500	27.0

> 50mu

Code	Size	Gusset	Qty per		
	(mm)	(mm)	pack		kg pačk
GPB120230-80-50	1200 x 2300	800	50	2	22.5
GPB120180-80-50	1200 x 1800	800	50	2	24.0
GPB2050-10-50	200 x 500	100	1,000	1	14.6
GPB2560-15-50	250 x 600	50	500	1	10.4
GPB3070-20-50	300 x 700	200	500	1	16.0
GPB40110-30-50	400 x 1100	300	500	3	35.0
GPB60100-40-50	600 x 1000	400	250	1	16.9
GPB6060-40-50	600 x 600	400	250	1	15.2
GPB6080-40-50	600 x 800	400	250	3	33.3
GPB70140-50-50	700×1400	500	150	2	22.3
GPB80120-40-50	800 x 1200	400	150	2	20.3

> 100mu

Code	Size	Gusset	Qty per	<u>A</u>
	(mm)	(mm)	pack	kg pack
GPB100180-70-100	1000 x 1800	700	40	22.0
GPB1020-5-100	100 x 200	50	500	2.9
GPB120230-80-100	1200 x 2300	800	25	21.0
GPB120180-80-100	1200 x 1800	800	25	17.0
GPB1535-8-100	150 x 350	80	500	5.0
GPB2050-10-100	200 x 500	100	500	14.7
GPB2560-15-100	250 x 600	150	250	11.0
GPB3070-20-100	300 x 700	200	250	16.0
GPB4090-30-100	400 x 900	300	250	29.0
GPB40110-30-100	400 x 1100	300	250	35.0
GPB60100-40-100	600 x 1000	400	125	23.0
GPB60120-50-100	600 x 1200	500	125	30.0
GPB70140-50-100	700 x 1400	500	75	23.0
GPB80120-40-100	800 x 1200	400	75	20.0
GPB80160-60-100	800 x 1600	600	75	31.0
GPB90180-70-100	900 x 1800	700	40	16.0

> 150mu

Code	Size	Gusset	Qty per	<u>A</u>
	(mm)	(mm)	pack	kg pack
GPB120180-80-150	1200 x 1800	800	25	25.5
GPB4090-30-150	400 x 900	300	150	26.1
GPB4050-30-150	400 x 500	300	150	17.0
GPB60120-50-150	600 x 1200	500	60	22.0
GPB60100-40-150	600 x 1000	400	75	21.0
GPB80160-60-150	800 x 1600	600	40	24.8
GPB80140-60-150	800 × 1400	600	40	21.0

Tenzapac® Anti-Static Packaging

Polypropylene Clear Self Seal Silver Anti-static Bags



- > 40mu
- Silver antistatic clear polypropylene film
 40mm resealable self-adhesive flap
- > 6mm diameter vent holes

Code	Size (mm)	Qty per pack	kg pačk
SPP0406	40 x 60	1,000	0.3
SPP0507	50×70	1,000	0.4
SPP0518	50 × 180	1,000	0.8
SPP0608	60×80	1,000	0.5
SPP0624	60 x 240	1,000	1.3
SPP0710	70×100	1,000	0.6
SPP0812	80 x 120	1,000	1.0
SPP0818	80 x 180	1,000	1.3
SPP1010	100 × 100	1,000	0.9
SPP1015	100 × 150	1,000	1.4
SPP1020	100×200	1,000	1.8
SPP1025	100 x 250	1,000	2.3
SPP1122	110×220	1,000	2.0
SPP1212	125 x 125	1,000	3.5
SPP1218	120 x 180	1,000	1.7
SPP1270	125×700	1,000	9.4
SPP1318	130 x 180	1,000	2.1
SPP1518	150 x 180	1,000	2.6
SPP1520	155×200	1,000	2.9
SPP1525	150×250	1,000	3.2
SPP1532	150 x 320	1,000	3.9
SPP1622	160×220	1,000	3.0

Code	Size (mm)	Qt pa	y per ck	kg pack	
SPP1624	165 x 240	1,0	000	3.4	
SPP1825	180 x 250	1,0	000	3.8	
SPP2228	220 x 280	1,0	000	5.2	
SPP2231	220 x 310	1,0	000	5.8	
SPP2235	220 x 350	1,0	000	6.4	
SPP2332	230 x 320	1,0	000	6.2	
SPP2525	250 x 250	1,0	000	4.7	
SPP2535	250 x 350	1,0	000	7.0	
SPP2738	270 x 380	1,0	000	8.3	
SPP3040	300 x 400	1,0	000	10.9	
SPP3045	300 x 450	1,0	000	9.2	
SPP3340	330 x 400	1,0	000	10.6	
SPP3545	350 x 450	1,0	000	16.5	
SPP4060	400 x 600	1,0	000	20.0	
SPP4570	450 x 700	2	50	9.3	
Gussetted	Gussetted 50mu Bags				
Code	Size (mm)	Gusset (mm)	Qty per pack		
SPP27389	5 270 x 380	60	1,000	9.8	

1,000

12.8



SPP3040S 300 x 400 60

Dissipative Packaging

Tenzapac® Anti-Static Packaging & Bubble Film Bags

Features:

- > Amine-free
- > Suitable for packing non-sensitive components in a static-controlled environment
- > No protection against contact ESD (electrostatic discharge)

LDPE Grip Seal

> 200g, pink-tinted low density polythene > Unprinted

Code	Size	Qty/box	kg box
AS6	4" x 5.5"	1,000	1.9
AS9	5" x 7.5"	1,000	3.0
AS11	6" x 9"	1,000	4.0
AS12	8" x 11"	1,000	6.5

LDPE Bubble Film Pouches

> With 30mm self-adhesive lip

Code	Size (mm)	Qty/box	kg
ASBP1	100 x 135	750	2.6
ASBP2	130 x 185	500	2.3
ASBP3	180 x 235	300	2.8
ASBP4	230 x 285	300	2.6
ASBP5	280 x 360	150	2.5
ASBP6	305 x 435	150	3.8
ASBP7	380 x 435	100	2.2

Open Ended Bags

> 200g, pink-tinted low density polythene > Printed with ESD warning

Code	Size	Qty/box
PB68-AS	6" x 8"	1,000



Pacplus® Anti-Static Layflat Tubing

Find it on page 17

Standard (Non Anti-Static) **Bubble Film Products**

SBDP300

Bubble Box

- > 300mm wide bubble film
- > Convenient dispenser box



Bubble Pouches

Code	Internal size (mm)	Qty per case	kg
BP1	100 x 135	750	2.6
BP2	130 x 185	500	2.3
BP3	180 x 235	300	2.8
BP4	230 x 285	300	2.6
BP5	280 x 360	150	2.5
BP6	305 x 435	150	3.8
BP7	380 x 435	100	2.2



Tenzapost® Protective Mailing Products

Jiffy® Padded Bags

> The original protective postal bag





Jiffy® Mailmiser® Bubble Bags

> Premium white bubble lined postal bags



Code	Internal size (mm)	Qty per case	kg
PB00	107 x 235	200	9.0
PB0	132 x 235	200	10.8
PB1	164 x 285	100	7.8
PB2	196 x 285	100	7.8
PB3	196 x 350	100	10.0
PB4	221 x 350	100	9.7
PB5	247 x 387	100	12.8
PB6	298 x 464	50	9.7
PB7	336 x 489	50	11.4
PB8	437 x 665	50	19.7

Code	Internal size (mm)	Qty per case	kg case
MM000V	V 90 x 145	150	1.7
MM00W	115 x 195	100	1.4
MMOW	140 x 195	100	1.6
MM1W	170 x 245	100	2.6
MM2W	205 x 245	100	2.7
MM3W	205 x 320	50	1.4
MM4W	230 x 320	50	1.8
MM5W	260 x 345	50	2.1
MM6W	290 x 445	50	2.9
MM7W	340 x 445	50	3.3

Jiffy® Airkraft Bags

> Lightweight white bubble lined postal bags



|--|

Code	Internal size (mm)	Qty per case	kg
JL000	90 x 145	150	1.2
JL00	115 x 195	100	1.2
JL0	140 x 195	100	1.2
JL1	170 x 245	100	1.7
JL2	205 x 245	100	1.9
JL3	205 x 320	50	1.5
JL4	230 x 320	50	1.4
JL5	260 x 345	50	1.7
JL6	290 x 445	50	2.3
11.7	3/10 v /1/15	50	2.5

PMS1728 3-ply Paper Mailing Sacks

- Strong, gusseted sacks13" x 28" with 4" gusset100 sacks per pack

Polythene Mailing Bags





Polythene Mailing Envelopes

CPMA4

- > Clear 37mu polythene > 225 x 315mm (ideal for A4 documents)
- > 35mm peel and seal flap
- > 1,000 per box





Code	Internal size (mm)	Qty per Box	kg
MBG-170-230	170 x 230	500	2.0
MBG-230-320	230 x 320	500	3.7
MBG-250-350	250 x 350	500	4.8
MBG-300-350	300 x 350	500	5.2
MBG-305-405	305 x 405	500	6.0
MBG-320-440	320 x 440	500	6.8
MBG-330-485	330 x 485	250	7.7
MBG-350-475	350 x 475	500	8.1
MBG-400-525	400 x 525	250	5.1
MBG-425-600	425 x 600	250	6.8
MBG-525-600	525 x 600	100	3.0
MBG-550-750	550 x 750	100	3.9
MBG-600-900	600 x 900	100	5.1
MBG-850-1050	850 x 1050	100	8.4







Safeguard® Tensioners for Plastic Strapping





CHD

Heavy Duty 25mm Tensioner









- Tensions up to 25mm composite and woven
- > CHD-RA attachment (optional) for round and irregular packs

 > Use sheradised or galvanised



- Irregular Pack
- Attachment for CHD







Features

- > Attaches to CHD tool for strapping round and
- irregular packs
 > Suitable for 12-16mm strap

Tensioner not included



safeguard" CHD-RA19

Irregular Pack Attachment for CHD







- > Attaches to CHD tool for strapping round and irregular packs
 > Suitable for 19mm strap

Tensioner not included





HDP40

Heavy Duty 40mm Tensioner







Features

- > Tensions up to 40mm composite and woven > Good for heavy duty
- applications
 > Extended handle for higher tensioning















Improved Product Design

Six-point windlass for easy loading

HPT50

Heavy Duty 19mm







- > Tensions up to 19mm
- polypropylene
 > Good for high strap tension
- > Brass bushings for extended tool life





OXT38

Heavy Duty 42mm Tensioner









- > Tensions up to 19-42mm composite and woven cord poluester
- > Advanced patented design for use in heavy duty
- applications
 > Use sheradised or galvanised buckles





Heavy Duty 19mm Tensioner

Features

- > Tensions up to 19mm
- composite and woven > Innovative gripper
- mechanism
 > Unique windlass return for
- faster, easier strap loading > Use sheradised or galvanised huckles





Heavy Duty 19mm Tensioner



- > Tensions up to 19mm
- polypropylene and polyester Innovative gripper
- mechanism > Unique windlass return for faster, easier strap loading







Extra Heavy Duty 32mm Tensioner



- > Tensions up to 19-32mm woven cord and composite
- polyester

 > Patented vertical gripper for
 easier strap release and improved grip





































Features

- > Tensions up to 19mm polypropylene > Best selling tensioner > Exceptional value for money





ST20

Standard Duty 19mm Tensioner

- > Tensions up to 9-19mm composite and woven > Top selling tensioner > Exceptional value for









TB301C Medium Duty 19mm Tensioner polypropylene > Chrome plated



Features > Tensions up to 19mm hotmelt

> Simple to use > Integral cutting blade



TS3215 Budget 16mm Tensioner

PP

polypropylene > Entry level, low cost tool















НМ









Safeguard® Sealers for Plastic Strapping





Heavy Duty 12mm Offset Sealer



- Offset jaws give high seal efficiency
 For 12mm polypropylene
- and polyester > Use 12mm SER12-SG serrated seals



Saleguard"

OFH16 Heavy Duty 16mm Offset Sealer

Features

- Features
 Offset jaws give high seal efficiency
 For 16mm polypropylene and polyester
 Use 16mm SER16-SG serrated seals



Saleguard" PSH₁₂

Heavy Duty 12mm Sealer

Features

- > High seal efficiency > For 12mm polypropylene > Use 12mm **S034**, **S01232** or **SC12** seals





















Heavy Duty 16mm Sealer

- > High seal efficiency > For 16mm polypropylene > Use 16mm **SO16** or SO1632 seals

12mm Sealer



Saleguard*

00S12

Heavy Duty



- Jaw configuration automatically orientates with seal
- > For 12mm polypropylene
- and polyester > Use 12mm SER12-SG serrated seals



Saleguard"

00S16 Heavy Duty 16mm Sealer



- Features > Jaw configuration automatically orientates with seal
- > For 16mm polypropylene
- and polyester > Use 16mm **SER16-SG** serrated seals



















QOS19 Heavy Duty

19mm Sealer

automatically orientates with seal

with seal

> For 19mm polypropylene
and polyester

> Use 19mm SER19-SG
serrated seals





KNS12 Medium Duty

12mm Offset Jaw Sealer



- > Offset jaws give high seal efficiency > For 12mm polypropylene
- and polyester > Use 12mm SER12-SG
- serrated seals





KNS16 Medium Duty 16mm Offset Jaw Sealer

- Features > Offset jaws give high seal efficiency > For 16mm polypropylene
- and polyester > Use 16mm SER16-SG serrated seals



































Standard 12mm Sealer

Features

- Single notch action releases the sealer more easily from tightly strapped round
- packs > For 12mm polypropylene > Use 12mm **SO34, SO1232** or **SC12** serrated seals



saleguard" SGP16

Standard 16mm Sealer

- > Single notch action releases the sealer more easily from tightly strapped round
- packs
 > For 16mm polypropylene
 > Use 16mm **SO16** or **SO1632** seals



 Single notch action releases the sealer more easily from KSP12

tightly strapped round packs
> For 12mm polypropylene
> Use 12mm S034, S01232
or SC12 serrated seals













Sealer

Budget 12mm







Standard 12mm Combination Tool



> For 12mm polypropylene > Use **SO34** semi-open seals



Saleguard"

SPC16

Standard 16mm Combination Tool



> For 16mm polypropylene > Use **SO16** semi-open seals



B12

Budget 12mm Combination Tool

- > Popular, low-cost tool > For 12mm polypropylene > Use **\$034** semi-open seals

















Heavy Duty 12mm Combination Tool

Features

- > Single lever windlass
- mechanism > Suitable for very high
- tension strapping > For 0.5-0.9mm thick, 12mm
- polypropylene or polyester > Use 12mm **SER12-SG** serrated seals







LPC16

Heavy Duty 16mm Combination Tool

Features

- > Single lever windlass
- mechanism
 > Suitable for very high
- tension strapping > For 0.5-0.9mm thick, 16mm
- polypropylene or polyester > Use 16mm **SER16-SG** serrated seals





RSK12

Medium Duty 12mm Combination Tool

Features > For 0.4-0.9mm thick,12mm

- polypropylene or polyester > No manual adjustment
- required between thicknesses > Use 12mm SER12-SG
- serrated seals































Safeguard® Combination Tools and Dispensers for Plastic Strap-



RSK16

Medium Duty 16mm Combination Tool



- For 0.4-0.9mm thick,16mm polypropylene or polyester
- No manual adjustment required between thicknesses
 > Use 16mm SER16-SG
- serrated seals



Safeguard ...

SHC12

Heavy Duty 12mm Combination Tool

> Improved Product Design

> Includes plastic seal

tote
Strapping reel and seals
not included



- > Exceptionally high tension, particularly with polyester > Ideal for vertical and horizontal operation
- of 0.5-0.9mm thick, 12mm polypropylene or polyester Use 12mm SER12-SG serrated seals



saleguard' SHC16

Heavy Duty 16mm Combination Tool

- Exceptionally high tension, particularly with polyester
- > Ideal for vertical and horizontal operation
- > for 0.5-0.9mm thick, 16mm polypropylene or polyester
 > Use 16mm SER16-SG serrated seals



















> Includes plastic seal

tote
Strapping reel and seals
not included

CSD3

Static dispenser









CSM20

Mobile dispenser









PCS6

Static dispenser









PD40

Mobile dispenser

> Includes plastic seal tote
Strapping reel and seals
not included





Code









RTBOX-L PTD406

R/PIN-1 Replacement Coil Retaining Pin

> Fits all Safeguard® strapping

Replacement Tool Boxes

Description RTBOX-S PD40, PMC80, CSD3, CSM20



PSD4

Static dispenser











PMC80

Mobile dispenser









Mobile dispenser







> Includes plastic seal

tote
Strapping reel and seals
not included



dispensers



> Fits PD40 and CSM20 dispensers









PET









Kitstart™ Plastic Strapping Kits

BSK600

12mm Buckle & Strap Box Kit

Contents

- > 12mm x 600mtr black
- strapping in dispenser box > 200 **PB12W** 12mm plastic

- > Handy and portable > Ideal for low-medium use > No strapping tools required





PPSK8

12mm Tensioner & Sealer Kit

Contents

- > PSD4 static dispenser > TST30 12mm tensioner
- > **SGP12** 12mm sealer > **TT45BLK** 12mm x 1500mtr
- strapping > 500 **SO34** 12mm seals



SBX600

12mm Seal & Strap Box Kit

- 12mm x 600mtr black strapping in dispenser box
 250 **S034** 12mm seals

Renefits

- > Handy and portable
- > Ideal for low-medium use > Ideal refill pack for **PPSK5**





PPSK44

12mm Combination Tool Kit

- > PSD4 static dispenser > B12 12mm combination tool > TT45BLK 12mm x 1500mtr
- strapping > 2,000 **S034** 12mm seals



PPSK5

12mm Tensioner & Sealer Starter Kit

- Contents > TST30 12mm tensioner
- > **SGP12** 12mm sealer > 12mm x 600mtr black
- strapping in dispenser box > 250 **SO34** 12mm seals



PPSK10

12mm Tensioner & Sealer Kit

- PD40 mobile dispenser
- > TST30 12mm tensioner > SGP12 12mm sealer
- > TT45BLK 12mm x 1500mtr
- strapping > 500 **SO34** 12mm seals



PPSK6

12mm Combination Tool Starter Kit

- Contents > B12 12mm combination
- tool > 12mm x 600mtr black
- strapping in dispenser box > 250 **S034** 12mm seals



PPSK20

12mm Combination Tool Kit

- > PD40 mobile dispenser
- > SPC12 12mm combination
- > TT45BLK 12mm x 1500mtr
- strapping > 500 **SO34** 12mm seals



PPSK7

12mm Combination Tool Kit

Contents

- > **B12** Combination Tool > **TT40BLK** 12mm x 2000mtr strapping
 > PSD4 static dispenser
 > 250 SO34 12mm semi open



CSK

13mm Bale Press Polyester Starter Kit

- > 13mm x 500mtr WP40PB bale press polyester strapping > 200 **CB4G** metal buckles



Kitstart™ Plastic Strapping Kits

Woven Polyester Mobile Dispenser Starter Kits

WPSK13_{13mm kit}

- > WPH40 13mm x1100mtr strap > 1,000 CB4G metal buckles
- > CSM20 mobile dispenser > CST20 tensioner

> WPH55 16mm x 600mtr strap > 1,000 CB5G metal buckles

WPSK16_{16mm kit}

- CSM20 mobile dispenser
- > CST20 tensioner



WPSK19 19mm kit

- > WPH65 19mm x 500mtr strap > 1,000 CB6G metal buckles
- > CSM20 mobile dispenser
- > CST20 tensioner



Extruded Polyester Mobile Dispenser Starter Kits

EXPSK13

Standard 13mm Tensioner & Sealer Kit

- > PTR25G 12.5mm x 1600mtr extruded polyester strap
- > PD40 mobile dispenser > HPT50 tensioner
- > OFH12 sealer
- > 1,000 SER12-SG serrated seals



EPK13

Standard 13mm Combination Tool Kit

- **Contents** > **PTR25G** 12.5mm x 1600mtr extruded polyester strap
- > PD40 mobile dispenser
- > RSK12 combination tool > 1,000 SER12-SG serrated seals



EXPSK16

Standard 16mm Tensioner & Sealer Kit

- > PTR45G 15.5mm x 1200mtr
- extruded polyester strap > PD40 mobile dispenser
- > HPT50 tensioner > OFH16 sealer
- > 1.000 SER16-SG serrated seals



EPK16

Standard 16mm Combination Tool Kit

- Contents > PTR45G 15.5mm x 1200mtr
- extruded polyester strap > PD40 mobile dispenser
- > RSK16 combination tool > 1,000 SER16-SG serrated seals





Safeguard® Polypropylene Hand and Machine Strapping

Polypropylene Hand Strapping

- > Volume rates apply to mixed-grade orders of polypropylene strapping
 > Hand strapping packed 1 coil per case

Code	Strap width	Strap thickness	Strap Colour	Coil length	Breaking strain	Coils per pallet	Core	k
TT40BLK	12mm	0.55mm	Black	2,000mtr	145kg	60	Plastic reel	9
TT40W	12mm	0.55mm	White	2,000mtr	145kg	60	Plastic reel	ç
TT5078BLK	12mm	0.8mm	Black	1,200mtr	235kg	60	Plastic reel	ç
TT45BLK	12mm	0.7mm	Black	1,500mtr	185kg	60	Plastic reel	8
TT50BLK	12mm	0.8mm	Black	1,300mtr	220kg	60	Plastic reel	9
TT50W	12mm	0.8mm	White	1,300mtr	220kg	60	Plastic reel	g
TT4470BLK	12mm	0.63mm	Black	1,800mtr	175kg	60	Plastic reel	10
TT505BLK	12mm	0.8mm	Black	1,000mtr	260kg	60	Plastic reel	8
TT512BLU	12mm	0.8mm	Blue	1,200mtr	270kg	60	Plastic reel	7
TT5076BLK	12mm	0.76mm	Black	1,400mtr	205kg	60	Plastic reel	ç
TT55BLK	12mm	0.9mm	Black	1,000mtr	300kg	60	Plastic reel	ç
TT55BLU	12mm	0.9mm	Blue	1,000mtr	300kg	60	Plastic reel	8
TT55Y	12mm	0.9mm	Yellow	1,000mtr	300kg	60	Plastic reel	g
TT60BLK	15mm	0.75mm	Black	1,200mtr	250kg	60	Plastic reel	7
TT65BLK	15mm	0.85mm	Black	1,000mtr	300kg	60	Plastic reel	7
TT70BLK	16mm	0.96mm	Black	750mtr	420kg	60	Plastic reel	9
CC1240WH	12mm	0.55mm	White	2,000mtr	130kg	48	200 x 150	7
CC1245WH	12mm	0.7mm	White	1,300mtr	185kg	48	200 x 150	6
CC1245BLK-150	12mm	0.7mm	Black	1,500mtr	185kg	48	200 x 150	7
CC12467BLK	12mm	0.8mm	Black	1,000mtr	220kg	48	200 x 150	5
CC1250WH	12mm	0.8mm	White	1,300mtr	220kg	48	200 x 150	7
CC1255WH	12mm	0.9mm	White	1,000mtr	300kg	48	200 x 150	6
CC1650BLU	16mm	0.8mm	Blue	800mtr	350ka	48	200 x 150	E

Polypropylene Machine Strapping

- > Volume rates apply to mixed-grade orders of
- polypropylene strapping

 > Machine strapping packed 2 coils per case *packed 1/box

Code	Strap width	Strap thickness	Strap colour	Coil length	Breaking strain	Coils per pallet	Core	kg/ case
MS540BLU	5mm	0.4mm	Blue	6,500mtr	60kg	60	200 x 190	22.8
MS540W	5mm	0.4mm	White	6,500mtr	60kg	60	200 x 190	18.7
MS6W	6mm	0.55mm	White	5,000mtr	80kg	60	200 x 190	20.0
MS7W	7mm	0.63mm	White	5,000mtr	100kg	60	200 x 190	23.8
MS7BLU	7mm	0.63mm	Blue	5,000mtr	100kg	60	200 x 190	23.5
MS1537W	9mm	0.55mm	White	3,700mtr	100kg	60	200 x 190	21.2
MS15W	9mm	0.55mm	White	4,000mtr	110kg	60	200 x 190	22.0
MS15BLU	9mm	0.55mm	Blue	4,000mtr	110kg	60	200 x 190	21.6
MS2084W	9mm	0.60mm	White	3,300mtr	110kg	60	200 x 190	18.4
MS20W	9mm	0.63mm	White	4,000mtr	140kg	60	200 x 190	24.1
MS5033W	12mm	0.63mm	White	2,500mtr	150kg	60	200 x 190	18.5
MS30W	12mm	0.63mm	White	2,500mtr	170kg	60	280 x 190	20.5
MS35W	12mm	0.55mm	White	2,500mtr	145kg	60	280 x 190	19.8
MS4693W	12mm	0.55mm	White	2,700mtr	135kg	60	200 x 190	18.1
MS40W	12mm	0.55mm	White	3,000mtr	145kg	60	200 x 190	20.4
MS40BLK	12mm	0.55mm	Black	3,000mtr	145kg	60	200 x 190	21.3
MS45BLU	12mm	0.55mm	Blue	3,000mtr	145kg	60	200 x 190	20.6
MS50BLU	12mm	0.63mm	Blue	3,000mtr	170kg	60	200 x 190	23.8
MS50BK-HE	12mm	0.63mm	Black	3,000mtr	165kg	60	200 x 190	23.8
MS50W	12mm	0.63mm	White	3,000mtr	170kg	60	200 x 190	23.8
MS55BLK	12mm	0.80mm	Black	1,500mtr	260kg	60	200 x 190	17.2
MS127BLK	12mm	0.70mm	Black	2,200mtr	190kg	60	200 x 190	21.3
MS128BLK	12mm	0.80mm	Black	2,000mtr	270kg	60	200 x 190	22.6
MS60BLU	12mm	0.85mm	Blue	2,000mtr	260kg	60	200 x 190	23.4
MS60Y	12mm	0.85mm	Yellow	2,000mtr	270kg	48	406 x 150	20.0
MS840BLU*	12mm	0.80mm	Blue	1,500mtr	230kg	48	406 x 150	12.3
MSP1208BLU*	12mm	0.80mm	Blue	2,000mtr	230kg	48	406 x 150	19.4
MSP1275BLK	12mm	0.75mm	Black	1,600Mtr	240kg	60	280 x 190	18.0



Safeguard® Polyester & Polypropylene Strapping

Polyester Strapping
- the strong, safer alternative to steel



Code	Strap width	Strap thickness	Colour & texture	Coil length	Breaking strain	Coils per pallet	kg/ coil
PT1175G	10.8mm	0.75mm	Green embossed	2,300mtr	310kg	48	20.0
ST1617	10.5mm	0.52mm	Green smooth	3,200mtr	245kg	48	25.6
PT1253G	12mm	0.5mm	Green embossed	3,000mtr	215kg	48	19.9
PT20G	12.5mm	0.6mm	Green embossed	2,500mtr	270kg	48	21.6
PT30G	12.5mm	0.7mm	Green embossed	2,000mtr	350kg	48	20.3
PT35G	12mm	0.85mm	Green embossed	1,800mtr	360kg	48	22.2
PT2252-1.1T	12mm	1.1mm	Green embossed	1,300mtr	540kg	48	20.0
PT1560G	15.5mm	0.6mm	Green embossed	2,000mtr	410kg	48	21.9
PT40G	15.5mm	0.7mm	Green embossed	1,750mtr	440kg	48	23.7
PT40G-S	15.5mm	0.7mm	Green smooth	1,750mtr	440kg	48	25.3
02PET158	15.5mm	0.85mm	Green embossed	1,500mtr	550kg	48	24.1
BKPET158	15.5mm	0.85mm	Black embossed	1,500mtr	550kg	48	24.1
PT50G	15.5mm	0.9mm	Green embossed	1,500mtr	560kg	48	24.6
PT60G	15.5mm	1.1mm	Green embossed	1,000mtr	720kg	48	22.0
PT70G	19mm	0.8mm	Green embossed	1,200mtr	660kg	48	24.3
PT90G	19mm	1.0mm	Green smooth	1,000mtr	850kg	48	26.4
PT90G-E	19mm	1.0mm	Green embossed	1,000mtr	820kg	48	23.2

Plastic Reel

Coc	de	Strap width	Strap thickness	Colour & texture	Coil length	Breaking strain	Coils per pallet	kg/ coil
PTF	R1250G	12.5mm	0.55mm	Green embossed	1,250mtr	270kg	60	10.4
PTF	R25G	12.5mm	0.55mm	Green embossed	1,600mtr	270kg	60	13.0
PTF	R25BLK	12.5mm	0.55mm	Black embossed	1,600mtr	270kg	60	13.8
PTF	R30BLK	12mm	0.8mm	Black embossed	1,000mtr	390kg	60	10.4
PTF	R45G	15.5mm	0.7mm	Green embossed	1,200mtr	440kg	60	16.5
PTF	R50BLK	16mm	0.9mm	Black embossed	750mtr	580kg	60	12.7

Hylastic High Performance Polypropylene Strapping

Cardboard core

Code	Strap width	Strap thickness	Colour & texture	Coil length	Breaking strain	Coils per pallet	kg/ coil
HYS654	9mm	0.46mm	Black smooth	3,430mtr	135kg	48	13.2
HY714	11.1mm	0.51mm	Black smooth	3,200mtr	180kg	48	18.4
HY716	10.8mm	0.63mm	Black smooth	2,438mtr	225kg	48	18.4
HY718	11.1mm	0.76mm	Black smooth	2,134mtr	270kg	48	17.5

Safeguard® Polyester Strapping

Woven Cord Polyester Strapping

- > 78mm cardboard core
- > Sold 2 coils per case (*WPH105 sold 8 per case)
- > Use with Safeguard® strapping buckles for optimum system strength



Code	Strap width	Strap length	Breaking strain	System strength	,	kg/ case
WPH40	13mm	1,100mtr	375Kg	638Kg		31.0
WPH50	16mm	850mtr	450kg	765kg		30.6
WPH55	16mm	600mtr	600Kg	1,020Kg		27.0
WPH60	19mm	600mtr	550Kg	935Kg		24.0
WPH65	19mm	500mtr	725Kg	1,235Kg		25.0
WPH75	19mm	500mtr	1,100Kg	1,870Kg		24.8
WPH85	25mm	500mtr	950Kg	1,615Kg		33.2
WPH95	32mm	300mtr	1,500Kg	2,550Kg		31.4
WPH105	*38mm	100mtr	2,000Kg	3,400Kg		35.6

Composite Polyester Strapping



The Composite Advantage

Composite strapping features a plastic coating that increases its abrasion-resistance and rigidity, making it easier to feed through a pallet frame.

- > Plastic coated cord polyester
- > 200 x 190mm cardboard core
- > Sold 2 coils per case (*CPS105 sold singly)
- > Best choice for highly-abrasive surfaces
- High rigidity for through-pallet feeding
 Use with Safeguard® strapping buckles for optimum system strength



> Non-woven, monofilament strap

> 78mm cardboard core > Individually boxed

Code	Strap width		Breaking strain	System strength	kg/ case
CPS40	13mm	1,100mtr	290Kg	493Kg	21.0
CPS50	16mm	850mtr	410Kg	697Kg	20.9
CPS60	19mm	700mtr	450Kg	765Kg	21.4
CPS65	19mm	650mtr	550Kg	935Kg	24.4
CPS85	25mm	500mtr	785Kg	1,335Kg	18.7
CPS105*	34mm	400mtr	1,400Kg	2,380Kg	16.7

Hotmelt Cord Polyester Strapping 🔆



The Hotmelt Advantage

Hotmelt cord strapping has a higher break strain and system strength than composite (see foot of page to find out about break strain and system strength).



> Use with **Safeguard**® strapping buckles

Code	Strap width	Strap length	Breaking strain	System strength	kg/ case
HMP40	13mm	1,100mtr	375Kg	638Kg	14.3
HMP131	5 13mm	1,500mtr	375Kg	638Kg	16.0
HMP45	13mm	750mtr	510Kg	867Kg	15.3
HMP50	16mm	850mtr	450Kg	765Kg	13.4
HMP55	16mm	600mtr	620Kg	870Kg	12.3
HMP60	19mm	600mtr	550Kg	935Kg	12.0
HMP161	2 16mm	1,200mtr	450Kg	765Kg	16.5
HMP65	19mm	500mtr	725Kg	1,232Kg	12.0
HMP85	25mm	500mtr	950Kg	1,300Kg	15.7

Bale Press Strapping

- > 60 x 160mm cardboard core
- > Sold in cases of 4 coils



Code			Breaking strain		kg/ case
WP30PB	9mm	500mtr	280Kg	160mm	6.3
WP40PB	13mm	500mtr	375Kg	180mm	9.1
WP50PB	16mm	425mtr	450Kg	210mm	14.0

Softex™ Woven Cord Polyester Strapping

- > A softer and more flexible strap
- > 76mm cardboard core
- > Sold in cases of 2 coils



Code		Strap length	Breaking strain	System strength	kg, cas
SWP55	16mm	600mtr	620Kg	1,054Kg	12.8
SWP65	19mm	500mtr	740Kg	1,258Kg	13.3



Break Strain or System Strength - what's the difference?

Break strain is the force required to break a length of strap. Safeguard* strap strength is routinely calibrated in break strain.

System strength is the maximum force sustainable by the combination of plastic strapping and buckles, which give a higher-efficiency join than metal seals or friction welding.



Safeguard® Seals and Buckles for Plastic Strapping

Superior quality Safeguard[®] strapping Seals

Made from higher quality steel, Safeguard® seals are subjected to stringent quality control procedures, to guarantee consistent and superior seal integrity.

Upgrade to Safeguard® now for the very best in seal performance and peace of mind.



> Equivalent to KONRAD

> 1,000 per box

> 1,000 per box

SER12-SG

12 x 0.8 x 30mm serrated seals



PET





SER16-SG

16 x 0.8 x 30mm serrated seals







> Equivalent to KONRAD

> 1,000 per box

SER19-SG

19 x 31 x 0.8mm serrated seals





> 1,000 per box

> 1.000 per box







S01232-SG

12 x 32 x 0.6mm semi-open seals







SO16-SG

16 x 25 x 0.5mm semi-open seals







S01632-SG

16 x 32 x 0.6mm semi-open seals







S034-SG 12 x 25 x 0.5mm

semi-open seals











Colour

White

Black

> Plastic buckles for 12mm polypropylene strapping

> Available in white or black standard and white heavy duty







2.1

2.1

23



- > High-grip sherardised surface
- > Enhanced weather resistance
- > Suitable for woven and hotmelt polyester

Code	Strap width	Wire ø	Box Qty	kg /box
CB4S	13mm	3.0mm	1,000	8.4
CB5S	16mm	3.5mm	1,000	10.4
CB6S	19mm	3.8mm	1,000	21.3
CB8S	25mm	5.0mm	400	15.0
CB10S	35mm	7.0mm	250	23.7









> Weather-resisting galvanised surface > Suitable for composite polyester and some polypropylene

Code	Strap width	Wire ø	Box Qty		kg /box
CB4G	13mm	3.0mm	1,000		8.0
CB5G	16mm	3.5mm	1,000	1	12.2
CB6G	19mm	3.8mm	1,000	1	18.4
CB8G	25mm	5.0mm	500	2	20.1
CDIOC	2 E.m.m.	7.0~~	250	-	220

Code

PB12W

PB12BK

PB12W-HD White

Strap Feed Tool



- High speed manual feeding of strap through any pallet frame
- Ergonomic head design rides over pallet runners and prevents jamming
- > Sturdy fibreglass guide rod > Suitable for PET, PP and cord
- strapping > Takes all strap widths and thicknesses
- > Head dimensions (LxWxH) 145 x 81 x 43mm
- > Total length 1823mm

PALP1 Pallet Probe



- > The quick and easy method for feeding strap under pallets
- > Suitable for all plastic and metal strapping up to 19mm wide > Overall length 1400mm
- Price each



Optimax[®] strapping machines and powered tools are ideal for higher volume and automated strapping requirements.

Find them on pages 52 - 57

















Strapping Seals and Safeguard® Plastic Edge Protectors

These strapping seals offer cost savings where the quality and performance of genuine Safeguard® seals is not a significant factor.



> 2,000 per box

SC12

12 x 25 x 0.5mm closed seals



> 2,000 per box S016

16 x 25 x 0.5mm semi-open seals











> 2,000 per box



SO10




10 x 25 x 0.5mm

semi-open seals










5034 12 x 25 x 0.5mm semi-open seals











16 x 32 x 0.6mm semi-open seals





Safeguard® Plastic Edge Protectors



Code	Description	Usable width	Qty per box	kg /box
CPS	Small plastic edge protectors, 28 x 25mm	19mm	2,000	3.3
CPS-E	Small embossed plastic edge protectors	19mm	2,000	3.8
CPL	Large plastic edge protectors, 37mm x 32mm	30mm	1,000	4.1
CPL-SPIKE	Large plastic edge protectors with spike, 37 x 32mm	30mm	2,000	7.5
CPL-X	Super large edge protectors, 48mm x 42mm	40mm	1,000	8.2
CPX	Extra large plastic edge protectors, 57mm x 48mm	50mm	1,000	5.1





Marine .	/
	-/



- > Handy dispenser carton > Perforated roll
- > Extruded profile 38 x 66mm > 550 protectors per roll



Safeguard® Tensioners and Sealers for Steel Strapping



Extra Heavy Duty 32mm Round Pack Tensioner







- > For steel up to 32mm
- > For round and irregular strapping























Tensions up to 680ka Lightweight design and ergonomic handles No power cords or pneumatic hoses One-touch operation buttons
Ideal for both flat and round

pack applications > Includes 18V Li-ion

battery/charger > Please specify strap width

on ordering Cordless Single Reverse 19 or 32mm Notch Sealer

ST



> Lightweight design and ergonomic handles

No power cords or pneumatic hoses

One-touch operation buttons

> LED task light > Ideal both for flat and round

pack applications
> Includes 18V Li-ion battery /charger > Please specify strap width

on ordering > Use **Lap-Over** seals













> Use LAP32-SG lap-over seals

strain
> Ideal for heavy usage

DNSA32

safeguard"

Heavy Duty 32mm Double Notch Side Action Sealer





safeguard"

Action Sealer

DNSA19

Heavy Duty 19mm

Double Notch Side









safeguard"

Action Sealer

DNSA25

Heavy Duty 25mm

Double Notch Side







> For steel up to 25mm > Double notch seal for better

grip > Side action reduces operator

> Use LAP25-SG lap-over seals

strain
> Ideal for heavy usage







Features

> For steel up to 19mm
> Double notch seal for better

grip > Side action reduces operator

> Use LAP19-SG lap-over seals

strain
> Ideal for heavy usage

SAS19

Heavy Duty 19mm Single Notch Side Action Sealer

- > Side action reduces operator
- > Ideal for heavy usage > Use LAP19-SG lap-over seals



Features

Heavy Duty 25mm Single Notch Side Action Sealer

- release
- > Side action reduces operator
- > Ideal for heavy usage > Use LAP25-SG lap-over seals



SAS32

Heavy Duty 32mm Single Notch Side Action Sealer



- > For steel up to 32mm > Single notch seal for easier
- > Side action reduces operator
- strain
- > Ideal for heavy usage > Use LAP32-SG lap-over seals



















Saleguard* SRD12

Heavy Duty 13mm Single Notch Sealer

Features

- > For steel up to 13mm > Single notch seal for easier
- release > Ideal for heavy usage > Use LAP13-SG lap-over seals



Saleguard"

SRD16 Heavy Duty 16mm Single Notch Sealer

Features

- > For steel up to 16mm Single notch seal for easier release
 Ideal for heavy usage
 Use LAP16-SG lap-over seals





SRD19

Heavy Duty 19mm Single Notch Sealer



- > For steel up to 19mm > Single notch seal for easier
- release
 > Ideal for heavy usage
 > Use LAP19-SG lap-over seals

























Safeguard® Sealers and Combination Tools for Steel Strapping







Heavy Duty 12mm Sealless Combination Tool



- Features > For flat strapping width steel up to 12mm > No separate seals required > Reversible punching dies extend tool life
- > Suitable for high tensile and regular strap



Saleguard"

OHT16

Heavy Duty 16mm Sealless Combination Tool





- Features > For flat strapping width steel
- up to 16mm

 No separate seals required

 Reversible punching dies
 extend tool life
- > Suitable for high tensile and regular strap



Saleguard"

OHT19

Heavy Duty 19mm Sealless Combination Tool

- Features > For flat strapping width steel
- up to 19mm

 No separate seals required

 Reversible punching dies
 extend tool life
- > Suitable for high tensile and regular strap









Heavy Duty 12mm Sealless Combination Tool

Features

- > For flat strapping width steel up to 12mm
- No separate seals requiredReversible punching dies extend tool life
 > Seals and cuts regular strap
- up to 0.6mm thick





QST16

Heavy Duty 16mm Sealless Combination Tool

- > For flat strapping width steel up to 16mm
- No separate seals requiredReversible punching dies
- extend tool life > Seals and cuts regular strap up to 0.6mm thick



QST19

Heavy Duty 19mm Sealless Combination Tool

Features

- > For flat strapping width steel up to 19mm
- > No separate seals required > Reversible punching dies
- extend tool life
 > Seals and cuts regular strap up to 0.6mm thick























Saleguard" TLN13

Light Duty 12-16mm Combination Tool



- > For steel 12-16mm > Use TLN13S and TLN16S



- > For steel up to 19mm > Use **TLN19S** seals



- > PVC handle grips > Cuts steel up to 0.9 x 32mm
- SSC04 Steel Strapping









SSC06 Steel Strapping Cutter



- Features > Cuts steel up to 0.9 x 32mm
- Rubber pads either side of blade gently release strap ends after cutting





SSC08

Saleguard"

TLN19

ST

Light Duty 19mm

Combination Tool

Heavy Duty Steel Strapping Cutter



- > Cuts steel up to 1.2 x 32mm Rubber pads either side of blade gently release strap ends after cutting
 Low profile bottom jaw for
- easy insertion under strap





SSC10 Extra Heavy

Duty Cutter

- Features > Cuts steel up to 1.3 x 50mm
- > Popular in timber and dockyard industries















SD32

Mobile Dispenser



- > Strap width adjustment up to 32mm to keep coil intact > Includes separate
- plastic tote for seals and tools Strapping reel and seals not included



HDMW60

Mobile Dispenser





- > Integral large capacity storage bin > Strap guide keeps strap end in convenient position for use
- > Large diameter wheels for uneven surfaces Strapping reel and seals not included



Mobile Dispenser







- Separate metal tote for seals and tools
- > Strap guide keeps strap end in convenient position for use Strapping reel and seals not included



NSD800

Narrow Aisle Dispenser



















> Ideal for use between timber stacks and

other narrow-access

adjustment 12-32mm to keep coil intact

situations > Strap width

Kitstart™ Steel Strapping Kits and Safeguard® Steel Strapping

Heavy Duty Steel Strapping Tensioner/Sealer Starter Kits

TSSK13 13mm kit.

TSSK16 16mm kit

TSSK19_{19mm kit}

- Contents > 1 coil 13mm ribbon wound steel strapping > SD32 mobile dispenser
- > TS12 steel stranning sealer
- > TLS20 steel strapping tensioner > 2.000 13mm snap-on seals

SSC04 strap cutter recommended (not included)



- Contents > 1 coil 16mm ribbon wound steel strapping
- SD32 mobile dispenser
 TS16 steel strapping sealer
- > TLS20 steel strapping tensioner
- > 2.000 16mm snap-on seals

SSC04 strap cutter recommended (not included)



- Contents > 1 coil 19mm ribbon wound steel strapping
- > SD32 mobile dispenser
- > TS19 steel strapping sealer
- > TLS20 steel strapping tensione > 2.000 19mm snap-on seals

SSC04 strap cutter recommended (not included)





Heavy Duty Steel Strapping Sealless Combination Tool Starter Kits

SCSSK13 13mm kit

> QST12 sealless combination tool SSC04 strap cutter recommended (not included)

> 1 coil 13mm ribbon wound steel strapping

SCSSK16 16mm kit

- > 1 coil 16mm ribbon wound steel strapping
- > SD32 mobile dispenser > QST16 sealless combination tool

SSC04 strap cutter recommended (not included)

> 1 coil 19mm ribbon wound steel strapping

SCSSK19 19mm kit

- > SD32 mobile dispenser > QST19 sealless combination tool SSC04 strap cutter recommended (not included)







Ribbon Wound

- > Lower coil weight for easy handling
- > Premium quality steel

> SD32 mobile dispenser

- > Extensive range
- > Vast stocks held







Zinc coated ribbon wound

Code	Strap width	Strap thickness	Туре	Coil length	Breaking strain	Coil per pallet	kg/ coil
RW13	13mm	0.5mm	Black	395mtr	560Kg	31	20.0
RW16	16mm	0.5mm	Black	395mtr	720Kg	25	25.0
RW19	19mm	0.5mm	Black	395mtr	850Kg	21	30.0
RW19Z	19mm	0.5mm	Zinc coated	395mtr	850Kg	21	30.0
RW19-06	19mm	0.6mm	Black	336mtr	1000Кд	21	30.0
RW25	25mm	0.8mm	Black	258mtr	1700Kg	18	41.0
RW32	32mm	0.8mm	Black	240mtr	2040Kg	22	48.0
RWS13	13mm	0.5mm	Black	320mtr	560Kg	36	16.5
RWS16	16mm	0.5mm	Black	332mtr	720Kg	30	21.0
RWS19	19mm	0.5mm	Black	316mtr	850Kg	25	24.0

Mill Wound

- > High coil capacity for reduced downtime
- > Premium quality steel > Extensive range
- > Vast stocks held



across the width of the 63.5mm (2.5") core.





DOLLAR.	
Zinc coate	d mill wound

Black steel mill wound

Code	Strap width	Strap thickness	Туре	Coil length	Breaking strain	Coils per pallet	kg/ coil
MW13	13mm	0.5mm	Black	1010mtr	570Kg	12	50.0
MW13Z	13mm	0.5mm	Zinc coated	1010mtr	570Kg	12	50.0
MW16	16mm	0.5mm	Black	800mtr	730Kg	12	50.0
MW16Z	16mm	0.5mm	Zinc coated	800mtr	730Kg	12	50.0
MW19	19mm	0.5mm	Black	675mtr	870Kg	12	50.0
MW19Z	19mm	0.5mm	Zinc coated	675mtr	870Kg	12	50.0
MW19-06	19mm	0.6mm	Black	560mtr	1000Kg	12	50.0
MW19-06Z	19mm	0.6mm	Zinc coated	560mtr	1000Kg	12	50.0

Safeguard® Steel Strapping Seals

Safeguard® Seals

Superior quality Safeguard® strapping seals

Made from higher quality steel, Safeguard® seals are subjected to stringent quality control procedures, to guarantee consistent and superior seal integrity.

Upgrade to Safeguard® now for the very best in seal performance and peace of mind.



> 2,000 per box LAP16-SG

13 x 25 x 0.7mm lap-over seal











> 2,000 per box





19 x 25 x 0.7mm lap-over seal











25 x 57 x 0.9mm




> 1,000 per box



LAP32-SG-500 32 x 57 x 0.9mm > 500 per box





SOS13-SG

13 x 25 x 0.5mm snap-on seal














19 x 25 x 0.5mm







Standard Seals

Standard strapping seals offer cost savings where the quality and performance of genuine Safeguard® seals is not a significant factor.



TLN13S-1000 > 1,000 per box

TLN tool







16mm seals for TLN tool







TLN19S-1000 > 1,000 per box

19mm seals for







13 x 25 x 0.7mm lap-over seals





> 2,000 per box

LAP16 16 x 25 x 0.7mm lap-over seals





> 2,000 per box











SOS13 13 x 25 x 0.5mm

snap-on seals



SOS16 16 x 25 x 0.5mm snap-on seal

ST



> 2,000 per box

SOS19 19 x 25 x 0.5mm

snap-on seals

> 2,000 per box





Safeguard® Stainless Steel Strapping

Stainless Steel Strapping

- > Ribbon wound
- > High resistance to corrosion
- > Enhanced weather resistance
- > Suitable for use in food processing, marine and medical installation > Use Safeguard® SBK buckles and Safeguard® SBT tensioner






					0
Code	Strap width	Strap thickness	Coil length	Steel type	kg/ coil
SSB12	12mm	0.726mm	30mtr	Grade 201 stainless	2.3
SSB16	16mm	0.726mm	30mtr	Grade 201 stainless	2.9
SSB19	19mm	0.726mm	30mtr	Grade 201 stainless	3.4

Buckles for Stainless Strapping

Features

- > Knockdown buckles for use with SSB stainless steel strapping system
- > Requires **SBT** tensioner > High resistance to corrosion, ideal for food























optima

optimum quality packaging machinery

- > strapping machines
- > pallet and parcel strappers
- > pallet stretch wrappers
- > shrink wrappers
- > premium quality impulse heat sealers
- > cardboard shredders
- > case tapers





51

Optimax® Battery Powered Strapping Tools



ZXTBAT-R Replacement 18V Li-ion Battery for ZXT12, ZXT16 and ZXT19 Tools (black/red battery casing)



ZXTBAT

Replacement 18V Li-ion Battery for older versions of the ZXT tool (black/yellow battery casing)





optima Optimax® Battery Powered Strapping Tools

TVX12-Li | TVX16-Li

Friction Weld Battery Powered Strapping Tools



Improved Li-ion





The TVX Li-ion battery powered tool is one of the fastest on the market - in less than three seconds, the strap is tensioned,

The ergonomic and rugged design assists maximum operator comfort, with minimal effort. Packages such as boxes, pallets, bales and crates can be safely strapped. Strap feeding is extremely simple, with both straps being inserted together. The TVX has an exceptional tension range and applies up to 240kg (2400N) with ease. The flexible sealing mode allows you to choose from semi-automatic or single button fully automatic operation.

Specifications

> Strap width:

Strap type compatibility: Polyester: 0.4mm - 1.05mm Polypropylene: 0.7mm - 1.05mm 12/16mm - please specify when orderina

Adjustable up to 240kg (2400N) subject to strap specifications > Strap tension:

TVX12-Li

TVX16-Li 16mm strap width

TVXBAT-Li Replacement TVX batteru





BXT3

Friction Weld Battery Powered Strapping Tool

The BXT next generation battery powered strapping tool for 13-16mm PP and PET strapping have a number of revolutionary world firsts in manual strapping tools.











The BXT3 is designed to withstand the everyday rigours of industrial use over many years. New features include:

- Easy to use Digital tool HMI Interface touch pad controls with new highlights for simple operator use and reduced training needs.
- Secure packaging process Favourite cycle settings for
- process repeatability a world first!

 Exact load securement actual applied strap tension to the
- Exact todo securement actual applied strap tension to the load indicated in display- a world first in a hand tool!
 Easy to package sensitive products Single finger strap tension speed control through finger pressure, so easy to position load protection etc. when strapping again another world first!
- Light-weight the perfect balance to the tool makes it easy to use in all applications, vertically and horizontally without any operator fatigue issues.
- Industry-proven high quality tool and parts Swiss made for reliability, durability and lowest cost of ownership over the
- The heavy duty shock resistant tool housing ensures longevity and provides maximum protection for the battery.

400 to 800

Specifications

Strap requirements: Sealing method: PET or PP Strapping Friction Weld Applied tension force: 98-1200N Strap thickness range: 0.5 to 1.2mm Strap width range: Dimensions: 13-16mm 368 x 140 x 135mm Bosch 18v 2.0A Li-ion 15 to 30 minutes Battery type: Charge time:



BXT3 13-16mm strap width Including battery & charger

Cycles per charge:

BXT3BAT

18v Spare Battery for BXT3 Strapping Tool





BXTV2BAT

14.4v Spare Battery for BXT216 Strapping Tool







Optimax® Semi Automatic Strapping Machines

Our best-selling Optimax® semi-automatic strapping machine

Semi Automatic Strapping Machine







head



Simple control

- Compatible with 6-16mm polypropylene machine strapping on 200mm and 280mm internal diameter strapping cores
 > Safety interlocked stainless steel top plate
- > Enclosed cabinet
- > Fixed/swivel castors > External manual strap tension adjustment

- Simple and reliable to use
 Very mobile
 Sealing mechanism and coil protected from damage and contamination inside fully enclosed cabinet

Specifications

> Dimensions (W x D x H): > Machine weight: 920 x 595 x 785mm 100kg

> Max strappable package weight: 120kg > Min/max strap tension: 15-45ka

(depending on strap used) 2.5 seconds @ 50Hz > Cycle time:

> Power supply: > Power consumption: 230V 50Hz













- > Compatible with 6-15.5mm polypropylene machine strapping on 200mm and 280mm internal diameter strapping cores
- > Braking swivel castors > External manual strap tension adjustment
- > Adjustable table height (730-930mm)

Benefits

- Simple and reliable to use
 Very mobile
 Affordable, compact and mobile for general purpose use

Specifications

> Dimensions (W x D x H): > Machine weight: 982 x 586 x 760mm

> Max strappable package weight: 120kg

> Min/max strap tension:

15-45kg (depending on strap used)

2.5 seconds @ 50Hz 230V 50Hz

> Power supply:> Power consumption:



















Optimax® Semi Automatic Strapping Machines













- Compatible with 5-13mm polypropylene machine strapping on 200mm and 280mm internal diameter strapping cores
- > Height adjustable table > Lockable swivel castors
- Cockable swivel castors
 External manual strap tension adjustment
 Hinged stainless steel top plate
 Quiet, compact control head with sensor-controlled heater blade and direct-drive mechanism

- > Simple and reliable to use
- > Very mobile
- > Adjustable table height for more ergonomic use

Specifications Dimensions (W \times D \times H): 850 x 560 x 780-950mm

> Machine weight: 75kg > Max strappable package weight: 120kg

> Min/max strap tension: 15-45ka (depending on strap used)

2.5 seconds @ 50Hz 230V 50Hz > Cucle time: > Power supply: > Power consumption: 0.3kW

> Based on the reliable, energy-efficient TMS300 platform > 355mm table height

> Braking swivel castors > Safety interlocked stainless steel top plate > External strap tension adjustment > Uses 9-16mm, 200/280mm core strapping

> Simple and reliable to use > Very mobile









> Ideal for ergonomic strapping of large, bulky cartons

> Max strappable package weight: 120kg > Min/max strap tension: 15-45kn

(depending on strap used) 2.5 seconds @ 50Hz > Cucle time: > Power supply: 240V 50Hz > Power consumption: 0.25kW

PLR100

Semi Automatic Low Level Strapping Machine





- > Based on the reliable, energy-efficient TMS300 platform
- > Stainless steel cabinet
- Side sealing functionBraking swivel castorsAdjustable table height

Benefits

- Simple and reliable to use
 Stainless steel construction gives added protection against weather and corrosive environments
 Side sealing configuration protects mechanism from

 - particles and liquids
 > Ideal for timber yards and marine or horticultural

environments

Specifications

> Dimensions (W x D x H): 675 x 1045 x 1625mm > Machine weight: 125kg > Max strappable package weight: 120kg

15-45kg (depending on strap used) > Min/max strap tension: 2.5 seconds @ 50Hz 230V 50Hz > Cycle time:

> Power supply:



















Semi Automatic Side Seal Strapping Machine



Optimax® Automatic Strapping Machines









TRS600-9 | TRS600-12 | TRS600-12L **Automatic Strapping Machines**



Features

- Entry-level automatic strapping
 Two standard arch size options
- > Special arch sizes on request > Up to 27 cycles per minute
- > External strapping tension control
- > Short feed sensor

- > Simple and reliable to use
- > Suitable for high volume carton and package strapping

Specifications

> Dimensions (W x D x H): TRS600-9, TRS600-12 TRS600-12L

> Strap width: TRS600-9 TRS600-12, TRS600-12L

12mm 10-70kg > Min/max strap tension: 2.2 seconds @ 50Hz > Cucle time: 230V 50Hz 1.2kW > Power supply: > Power consumption:

TRS600-9 Arch size: 850 x 600mn (W x H)

TRS600-12 Arch size: 850 x 600mm (W x H)

TRS600-12L

1430 x 620 x 1540mm 1630 x 620 x 1740mm

Arch size: 1050 x 800mm (W x H)



machine

Free access to strap guides

Waist height quick coil

Robust &

mechanical











- > Auto strap feed> Short feed sensor and auto strap re-insertion
- > Electronic tension control
- > Auto loop ejector

- > One of the most advanced strapping machines in its class
- > Fast tension adjustment
- > Minimal downtime and coil changeover

Specifications

> Dimensions (W x D x H): > Min/max strap tension: 1630 x 620 x 1740mm 10-70ka > Cycle time: 2.6 seconds @ 50Hz 230V 50Hz > Power supplu: > Power consumption:

AFS900-9

Strap width: 9mm Arch size: 850 x 600mm (W x H)

AFS900-12 Strap width: 12mm Arch size: 850 x 600mm (W x H)

AFS900-12L Strap width: 12mm Arch size: 1050 x 800mm (W x H)















- > High speed automatic strapping machine> Waist height coil change

- > Auto strap feed > Auto strap ejector > Adjustable table height

- High-level control panel
 Integral front foot bar switch
 Other strap widths and arch sizes available

- > Ergonomic, user-friendly design
- > High speed up to 65 cycles per minute > Additional arch sizes/strap widths available on request

Specifications > Dimensions (W x D x H):

> Strap width:

HQS80-15 HQS80-15-12

5mm 12mm 1-25kg 0.92 seconds @ 50Hz 230V 50Hz 0.5kW

> Min/max strap tension: > Cycle time: > Power supply:

> Power consumption:

HQS80-15

Strap width: 5mm Arch size: 550 x 400mm (W x H)

HQS80-15-12

840 x 650 x 1305mm

Strap width: 12mm Arch size: 550 x 400mm (W x H)



HQS80-15 | HQS80-15-12 **Automatic Strapping Machine**















Arch strapping machines are supplied with the arch dismantled for protection and space reduction during transit.

Please advise your sales contact before ordering if assembly is required prior to delivery.

Optimax® Automatic Strapping Machines



TRS650R-12

Automatic Strapping Machine with Roller Driven Table



















Features

- > Electronic strap tension control
- Automatic strap loop ejector for accidental cycle activation
 Automatic strap feed for load-and-go reel changes

optima

- > Hinged top plates give easy access for cleaning and
- maintenance
 > Adjustable feet for uneven floors
- > Swivel castors for easy relocation

Benefits

- > Simple and reliable to use
- > Suitable for high volume carton and package strapping

Specifications

- > Dimensions (W x D x H): 1580 x 706 x 1540mm > Arch size (W x H): 850 x 600mm Maximum package weight: 100kg 12mm 0.55mm - 0.75mm > Strap width:
- > Min/max strap thickness: Min/max strap tension:Maximum cycle speed: 7-70kg (depends on strap) 29 per minute (@50Hz if applicable) 240V 50Hz

> Power requirement:

Options

- > Belt driven table> Stack pre-compression bar
- > 9mm strap width



High Speed Automatic Strapping

Machine with Belt Driven Table



strap

High quality

















Features

- > German brushless motor technology
- > Reliable, low-maintenance strapping head > Tool-free access to strapping head and strap guides
- > Automatic strap loop ejector for accidental cycle activation > Automatic strap feed for load-and-go reel changes
- > Adjustable table height (820-920mm) > Adjustable feet for uneven floors
- > Lockable swivel castors for easy relocation

- > One of the most advanced strapping machines in its class
- > Fast tension adjustment > Minimal downtime and coil changeover

Specifications

- Dimensions (W x D x H): 1400 x 650 x 1497mm 650 x 500mm
- > Arch size (W x H): > Maximum package weight:35kg > Strap width: 9mm
- > Min/max stran thickness: 0.35mm - 0.65mm
- 1-45kg (depends on strap) 65 per minute (@50Hz if applicable) > Min/max strap tension:> Maximum cycle speed:
- > Power requirement: 240V 50Hz 1kW > Power consumption:

Options

- Roller driven table
- Stack pre-compression bar
- > 5mm, 6mm and 12mm strap width
- > 550 x 500mm, 850 x 600mm
- 850×800 mm and 1050×800 mm
 - arch (W x H)





















- > Versatile and user-friendly PLC and touchscreen control
- > Up to 70 double-strapped pallets/hour on automated line > Production line integration
- > Choice of arch sizes
- Indexing strapping head for higher productivity and correct strap tension
 Telescopic strap lance permits easy pallet transfer

- > Ergonomic, user-friendly design > Additional arch sizes/strap widths available on request

- Specifications > Dimensions (W x D x H): > Strap widths: 1857 x 3000 x 2564mm 9-12-16mm
- > Min/max PP strap thickness: Min/max PET strap thickness:
- > Min/max strap tension:
- > Power requirement: > Power consumption:

0.75mm - 0.9mm 0.5mm - 0.8mm 110-300kg (depends on strap) (optionally 20-120kg) 415V 50Hz 3ph 1.35kW



Arch strapping machines are supplied with the arch dismantled for protection and space reduction during transit.

Please advise your sales contact before ordering if assembly is required prior to delivery.

Optimax® Pallet Stretch Wrap Turntables

Maximise your pallet stretch wrapping efficiency with an Optimax® Turntable





Simple to use



Order the additional PSWR ramp for pallet truck loading and unloading of the turntable





- > 1650mm turntable with 2000mm wrapping height
- > Spring brake activated film stretch mechanism
- Home position: the turntable always stops at the same position
- > Pallet height photo sensor > Choose between 3 bottom wraps and 2 top wraps or
- 2 bottom wraps and 1 top wrap
- > Adjustable tension
- > Soft start and stop
- Machine can be paused during cycle
 Magnetic brake holds turntable still during loading
- > Audible warning when running a cucle
- > Safety switch to prevent foot pinch

Specifications

- > Dimensions (W x D x H):
- > Max. wrapping height: > Max. turntable speed:
- > Max. loading weight: > Turntable diameter:
- > Power supply:
- > Power consumption:

1650 x 2465 x 2338mm

2000mm 10rpm 1650kg



PSW002

Semi-Automatic Powered Pre-Stretch

Advanced Soft Wrapping Feature

Advanced soft wrapping regulates the film tension as the pallet rotates to avoid over-tensioning on corners, which can cause carton damage.





Order the additional PSWR ramp for pallet truck loading and unloading of the turntable





- > 300% power pre-stretch 1 metre of film stretches to 4 metres
- > 1650mm turntable with 2000mm wrapping height
- > Home position: the turntable always stops at the same position
- > Pallet height photo sensor
- > Adjustable tension, turntable and carriage speed
- > Soft start & stop with cycle pause function
- Choice of automatic or manual modes
- > 180 degree rotating control box > Troubleshooting information displays on screen
- > Safety switch to prevent foot pinch > Manual reinforced strapping feature
- > Automatic film pin puncture
- > One way idling roller (keeps film tail outside carriage)

Specifications

- > Dimensions (W x D x H):
- Max. wrapping height:Max. turntable speed:
- > Max. loading weight: > Turntable diameter:
- > Power supply: > Power consumption:
- 1650 x 2400 x 2345mm 2000mm 12rpm
- 1650ka 1650mm 240V 13A 1.2kW



PSW003

Semi-Automatic Powered Pre-Stretch with Integrated Digital Weighing Scales

Advanced Soft Wrapping Feature







Order the additional PSWR ramp for pallet truck loading and unloading of the turntable





> Automatic film pin puncture > One way idling roller (keeps film tail outside carriage)

> Digital weighing scales on the turntable ramp

> Adjustable tension, turntable and carriage speed

> Soft start & stop with cycle pause function > Choice of automatic or manual modes > 180 degree rotating control box > Troubleshooting information displays on screen

> Safety switch to prevent foot pinch > Manual reinforced strapping feature

Increased load capacity of 2000kg
 300% power pre-stretch – 1 metre of film stretches to 4 metres
 1650mm turntable with 2000mm wrapping height

> Home position: the turntable always stops at the same position

Specifications > Dimensions $(W \times D \times H)$:

> Pallet height photo sensor

- > Max. wrapping height: > Max. turntable speed:
- Max. loading weight:Turntable diameter:
- > Power supply:
- > Power consumption:

2000mm

12rpm 2000kg 1650mm

1.2kW





Optimax® Pallet Stretch Wrap Turntables









Order the additional PSWR ramp for pallet truck loading and unloading of the turntable

Features

200% power pre-stretch – 1 metre of film stretches to 3 metres

optima

- > 1650mm turntable with 2200mm wrapping height > Home position: the turntable always stops at the same position
- Pallet height photo sensor
 Adjustable tension, turntable and carriage speed
- > Soft start & stop with cycle pause function
- > Choice of automatic or manual modes > 180 degree rotating control box
- > Troubleshooting information displays on screen > Safety switch to prevent foot pinch
- > Manual reinforced strapping feature > Automatic film pin puncture
- > One way idling roller (keeps film tail outside carriage)

Specifications

> Dimensions (W x D x H): 1650 x 2400 x 2545mm

> Max. wrapping height: 2200mm > Max. turntable speed: 12rpm 1650kg > Max. loading weight:

1650mm 240V 13A > Turntable diameter: > Power supply: > Power consumption: 1.2kW



PSWR

Ramp for Optimax PSW stretch turntables, with ramp fixer



> Fits all Optimax pallet stretch wrap turntables so pallets can be loaded and unloaded with a pallet truck









- > No maximum pallet weight, width or depth
- > Minimal clearance required around pallet
- > Easily relocated to where wrapping required > Powered film pre-stretching minimises film usage and creates a more stable pallet load
 > Password-protected touchscreen control panel features
- Independently adjustable top and bottom wrapping count and tension Two power pre-stretch ratios offering 230% and 300% film length increase
- Adjustable cart rotation speed
- Adjustable film carriage speed > Film carriage is easily reloaded and features an anti-drop mechanism for improved safety
 > One-way idling roller prevents entanglement in the event of
- film breakage and facilitates film re-feed

 > Soft-wrapping feature protects pallet contents from damage
- due to uneven film tension at corners

 > Automatic photocell pallet height detection
- > Automatic end of cycle film cutting
- > High capacity, zero maintenance batteries deliver up to 300 pallet wraps per charge

Specifications

> Batteries: 2x 12v100Ah non-maintenance

lead acid 0.7kW > Power consumption:

1175 x 1758 x 2570mm > Dimensions:

> Max. wrapping height: 2200mm > Cart rotation speed: > Film carriage speed: 20-90mtr/min. 1-5mtr/min.

> Min. pallet size: > Operation radius: 600 x 600mm 1150mm from edges of load

or pallet >300 pallets

> Wraps per charge: > Nett weight: 292kg





Optimax® Heat Shrink Chambers



- Features
 > Best-selling model in range
 > Seal and shrink in one operation
- Very low energy consumptionAdvanced electronic controls
- > 240V single phase will run off a standard 13A socket

Specifications
> Power supply: 220/230/240V, 50/60Hz, 13A

> Max. power consumption: 3.2kW > Effective power consumption: 1.3-1.9kW

Sealing dimensions:Max. height of package:

320mm x 460mm (D x L) 120mm > Max. fleight of package: 120/flfff
> Machine dimensions: 1120 x 660 x 550m (LxWxH)
> Max. dimensions of film roll: 400mm x Ø250mm











- Seal and shrink in one operation
 Very low energy consumption
 Advanced electronic controls
 240V single phase requires a minimum 16A power supply, will not run off a 13A socket.
 Requires 16A supply and connector (not included)

- 220/230/240V, 50/60Hz, 16A
- Specifications
 > Power supply:
 > Max. power consumption:
 > Effective power consumption:
 > Sealing dimensions:
 > Max. height of package:
 > Machine dimensions:
 > Max. dimensions of film roll: 3.77kW 1.6-2.3kW
- 420 x 550mm (D x L)
 - 250mm
- 1320 x 820 x 645mm (L x W x H)
- 600mm x Ø250mm

Optimax® Heat Shrink Chambers



- Features

 > Powerful, high-capacity model

 > Seal and shrink in one operation

 > Very low energy consumption

 > Advanced electronic controls

 > 415V 3 Phase Supply Required

Specifications

Power supply:Max. power consumption: 380/400/415V, 50/60Hz 5.3kW

> Effective power consumption: 2.3-3.4kW > Sealing dimensions: 620 x 800mm (D x L)

Max. height of package:Machine dimensions: 250mm 1575 x 1020mm x 645mm

optima

(L x W x H) 800mm x Ø250mm > Max. dimensions of film roll:

Shrink Chamber Spare Part Products

Code	Description	kg	Code	Description	kg
297F-0074	Teflon roll, 2mtr	0.01	702400161	Rubber strip (short) for SC346	0.06
297F-0075	Teflon roll, 10mtr	0.01	702400160	Rubber strip (long) for SC346	0.08
705100250	Sealing element for SC346	0.01	705000131	Rubber strip (short) for SC455	0.02
705000250	Sealing element for SC455	0.02	705000130	Rubber strip (long) for SC455	0.03
705200250	Sealing element for SC680	0.02	705200131	Rubber strip (short) for SC680	0.11
			705200130	Rubber strip (long) for SC680	0.13









Features

- > Separate sealer and shrink tunnel for faster throughput

- Powerful, high-capacity heat sealing
 Extendable weld cooling time
 The ST455 requires a 3.5 to 4.5kg/cm² compressed air supply.

Please contact our technical service centre for more information.

Specifications

Power supply:Max. power consumption:

Sealing dimensionsTunnel inlet dimensions:

> Working plate height: > Max. packing height: > Machine dimensions:

> Max. dimensions of film roll:

400V, 50Hz 9kW

400 x 550mm (D x L) 400 x 200mm (W x H)

900mm 150mm 2570 x 870 x 1600mm (LxWxH)

600mm x Ø300mm



Optimax® C-Type & CI-Type Impulse Heat Sealers



General specifications

- > Seal width: 2.5mm
- > Voltage: 230V 50Hz

- > Available in powder coated extruded aluminium (C-Type) and stainless steel (CI-Type)
 > Adjustable sealing time
- Sealing wire tension unitIntegral safety cutting knife
- > Usage guide: 100-400 seals per shift

- > No mechanical switches, for optimum reliability
- > Tension unit maintains consistent 2.5mm seal > Extruded base and arm construction (C-Type)
- increases strength and safety
 > Stainless steel construction (CI-Type) suitable for use in food handling and corrosive environments



800mm

468W

1050 x 100 x 175mm

200mm Sealers

- > Seal length:
 > Max. film width/cutting length:
- > Power consumption: > Dimensions of machine
- - 180W 450 x 100 x 175mm

200mm

300mm

218W

550 x 100 x 175mm

C220 Powder Coated

CI-220



CI-420 Stainless Steel



400mm Sealers

- > Seal length:
 > Max. film width/cutting length:
- > Power consumption:
- > Dimensions of machine
- C420 Powder Coated



400mm

248W

600mm

365W

850 x 100 x 175mm

650 x 100 x 175mm

800mm Sealers

- > Seal length:
 > Max. film width/cutting length:
- Power consumption:Dimensions of machine:

C820



300mm Sealers

- Seal length:Max. film width/cutting length:
- > Power consumption: > Dimensions of machine

C320 Powder Coated

CI-320



600mm Sealers Seal length:Max. film width/cutting length:

- Power consumption:Dimensions of machine:

C620 Powder Coated

CI-620 Stainless Steel



Powder Coated

- *Spares kits
- >Include: 1 x element wire 1 x lower teflon
 - 1 x upper teflon

HA001334 C220, CI-220 HA001335 C320, CI-320 HA001336 C420, CI-420

HA001337 C620, CI-620 HA005252 C820



Replacement Parts

powder coated finish for C-Type sealers)

Code	Size	kg
HA004352	C-Type cutting knife (complete assembly)	0.05
HA003308	C-Type front cap (magnet)	0.05
HA000427	C-Type silicon rubber (sold per metre)	0.05
HA004197	C-Type opening spring (assembly)	0.05
	Table & Film Holder	

Code	For Sealer Model	kg
HA000670	C220	4.5
HA000889	C320	5.4
HA000903	C420	6.4
HA000904	C620	6.8
HA911	CI-220	4.5
HA914	CI-320	5.4
HA915	CI-420	6.4
HA916	CI-620	6.8



Optimax® S-Type Impulse Heat Sealers

Heavy Duty Impulse Heat Sealers with Integral Cutter





- > Powder coated extruded aluminium sealing bar and pressed steel body
- > Separate, electronic adjustment of sealing and cooling times
- > 5mm sealing wire
- > Sealing wire tension unit
- > Gas spring controlled, electromagnetically locking sealing bar
 > Manual or footpedal actuation
- Integral safety cutting knife
 Usage guide: 200-400 seals per shift
- > No mechanical switches for optimum reliabilitu
- No mechanical switches for open formers
 Tension unit maintains consistent seal
 Extruded sealer bar and steel body increase strength and safety

Accessories & Spare Parts

Code	Size	kg
HG1374	420mm work table and bag support	8.4
HG1288	420mm stand, foot pedal & film holder	10.6
HG1353	620mm work table and bag support	10.8
HG1289	620mm stand, foot pedal & film holder	11.6
HG001354	820mm work table and bag support	12.4
HG001290	820mm stand, foot pedal & film holder	11.5
HG1375	1020mm work table and bag support	14.6
HG1291	1020mm stand, foot pedal & film holder	14.3
HA001228	5 metres of upper teflon	0.01
HA001229	5 metres of lower teflon	0.02
KA001065	5 metres of 5mm sealing wire	0.01
HA001383	S-Type cutting knife (complete)	0.02
HA000414	C/S-Type cutting blade	0.01
HA002025	S-Type sealing head return spring	0.02
HA002550	S-Type silicon rubber (per metre)	0.1/mtr

S420

Specifications

> Seal length: > Seal width: > Max. film width: 5mm 400mm > Max. cutting length: > Voltage*: 420mm 230V 50/60Hz > Consumption: 450W



optima

S620

Specifications

600mm Seal length: > Seal width: 5mm Max. film width: 600mm > Max. cutting length: 620mm > Voltage*: 230V 50/60Hz > Consumption: 650W



S820

Specifications

800mm > Seal length: > Seal width: > Max. film width: 5mm 800mm > Max. cutting length: > Voltage*: 820mm 230V 50/60Hz > Consumption: 850W



S1020

Specifications

1000mm Seal lenoth: > Seal width: > Max. film width: 5mm 1000mm 1020mm 230V 50/60Hz > Max. cutting length: > Voltage*: > Consumption: 950W





Maximum film sealing thicknesses (all models)

PE polythene 250mu bag (total thickness 500mu) PP polypropylene 200mu bag (total thickness 400mu) PVC 100mu bag (total thickness 200mu) Laminates, foil etc. 150mu bag (total thickness 300mu)



Optimax® VT-Type Vacuum Heat Sealers

V-HEAD Vacuum Sealer Control Head



VI-HEAD Stainless Steel Vacuum Sealer Control Head



Vacuum Sealer Base Unit, stainless steel finish. sealer bar sold separately

PLEASE NOTE

sealing performance Faster working cycle
 No regulation bag size

Compatible Film Types

> PE/aluminium/PE

High quality sealInterchangeable sealing bar widths

Any thermosealable laminations including:
 PET/paper/PE

> Small footprint > Low energy consumption

Both of these units are sold without the sealing bars, which are purchased separately

> Ideal for food, electronics, pharmaceutical and healthcare industries


> Reliable, consistent pre-seal evacuation, gas flushing and heat

- > Footpedal actuation
- > Automatic or manual operation
- > Bi-active upper and lower sealing
- > Ejector vacuum pump > Vacuum filter
- > Water discharge system > Sensor-activated vacuum control
- > Independent, incremental adjustment of primary and secondary vacuum pressures, gas flushing time and
- sealing/cooling time
 > Pneumatic sealing action
- > 5.7" colour LCD touchscreen control and operation > User-friendly multilingual menu

- > SMPS technology-derived intelligent power circuitry > Safety-conscious design including electrical circuit protection

Optimax® Vacuum System Sealing Bars

Suitable for use with both V-Head and VI-Head.



General specifications

> Seal width: 8mm 230V 50Hz > Voltage: > Delivered air pressure: max. 8bar

VT420

> Seal length: 420mm > Max. bag width: 400mm Power consumption: 1800W

> Dimensions: 560 x 550 x 260mm



VT620

> Seal length: 620mm > Max. bag width: 600mm > Power consumption: 2100W 620mm 600mm

760 x 550 x 260mm > Dimensions:



VT820

820mm > Seal length: > Max. bag width: 800mm > Power consumption: 2300W

> Dimensions: 960 x 550 x 260mm



VT1020

> Seal length: > Max. bag width: 1020mm 1000mm

> Power consumption: 2500W > Dimensions: 1160 x 550 x 260mm



VT1320 1320mm Seal length: > Max. bag width: 1300mr > Power consumption: 2800W 1300mm

> Dimensions: 1460 x 550 x 260mm



Note: Dimensions and weights include control head

FPED Flexible Foot Pedal

> Compatible with Optimax S-Type Sealers > Enables hands-free operation for improved productivity and ease of handling larger items

NOTE: If using the FPED footpedal, the sealer must overhang the front edge of the bench by 40mm and secured firmly to the bench.



Packaging Chute

- > The Optimax Packaging Chute places layflat tubing in a convenient position above the sealer and enables variable-sized bags to be created on demand.
- > Ideal for batch packing of small components.

For more information on the Optimax® Packaging Chute please contact our



PPEHMS

Mobile Heat Sealer Station



- > Developed for pick/pack despatch of random-sized products
- Creates bags on demand, to any length > Designed to accommodate the Optimax® S620 Impulse Heat Sealer*
- > Incorporates 2 mandrels for lauflat tubing up to 610mm (24") wide

 > Fitted with castors for full manoeuvrability
- Positions the S620 at the correct height for standard-height pack stations
- * Impulse Heat Sealer not included in the price



Optimax® Case Tapers







153kg

> Uniform case size (manually adjustable upper tape head height)

optima

- > Infeed/outfeed conveyors as standard > Castors as standard
- > 12 month parts or return to base warranty

- > 75mm wide tape head available > Safety guard
- > Upgrade to 12 months on-site parts and labour warranty
- > 100-110V, 60Hz available on request

Specifications

50mm 150-500mm 120-500mm > Standard tape width: > Min/max carton width: > Min/max carton height: > Min/max carton length: > Belt speed 23mtr/min: 120mm - ∞ (9-20 cartons/min) > Power supply:

200-240V, 50Hz (100-10V, 60Hz available

on request) 450W > Power consumption:

> Dimensions (L x W x H): 1637 x 756 x 1375mm



- Features > Random case taping (upper tape head auto-adjusts for carton height)
 > Infeed/outfeed conveyors as standard

- > Castors as standard > 12 month parts or return to base warranty

Options

- > 75mm wide tape head available > Safety guard
- > Upgrade to 12 months on-site parts and labour warranty > 100 -110V, 60Hz available on request

Specifications

Standard tape width:Min/max carton width:

> Min/max carton height: > Min/max carton length:

> Belt speed 23mtr/min: > Power supply:

> Power consumption: > Dimensions (L x W x H):

50mm 150-500mm

120-500mm 120 mm - ∞ (9-20 cartons/min) 200-240V, 50Hz

(100-10V, 60Hz available on request)

450W

1170 x 930 x 1550mm



Optimax® Cardboard Shredders



- > Turn small quantities of old cardboard into lots of packaging material within a short time
- > Create high-bulk void fill and protective matting material which reduces packaging costs and is ecologically beneficial.
- > Operator-friendly carton feed with punched measuring scale for precise packaging units.
- > Variable carton sizes automatically processed in a single step.
- > High motor torque for more powerful shredding action, even at low speeds.
- > Low maintenance reduces loss of productivity
- > Improved power consumption/performance ratio.
- > Standard dust extraction device built into most models.

Optimax shredders contribute cost-effectively to reducing carbon footprint and demonstrating eco-friendly credentials







High bulk void fill from Protective matting for waste cartons wrapping and layering

Standard dust extraction device built into most models

Fitted with IEC/EN 60204-1 compliant circuit breaker

Optimax puts operator safety first

Only the Optimax® range of cardboard shredders complies with BS EN ISO 13857:2008





Optimax is the first manufacturer to offer compliance with BS EN ISO 13857:2008 across its entire range of cardboard shredders.

This standard is the UK implementation of EN ISO 13857:2008 and stipulates that a 20mm-high opening to a blade mechanism must incorporate a minimum safety distance of 120mm.

As market leader in product innovation and operator safety, Optimax has exceeded these requirements to provide a safety distance of 140mm.



Optimax® Cardboard Shredders

CP333NTI

Optimax Table Top Cardboard Shredder

Produces void fill or protective matting material





Cuts 320mm wide

thick



No dust extraction device

optima







1-2m3/hr Feed rate



W: 460mm D: 580mm H: 620mm



Warrantu 12 months as standard

CP316S2-I

Single phase

Produces void fill or protective matting material

CP316S24MM

Single phase Produces 4mm-wide void fill strip















320mm



Output 12mm 1-2m3/hr Feed rate 10mtr/min



No dust extraction

D: 660mm H: 980mm



50Hz

W: 660mm





CP320S2-I

Single phase Produces void fill or protective matting material

CP320S24MM

Single phase Produces 4mm-wide void fill strip

















Output 2-3m3/hr thick Feed rate 12mtr/min



Dust extraction

D: 1060mm











Optimax® Cardboard Shredders

CP422S2-3PH

Three phase

Produces void fill or protective matting material

CP422S2-240V

Single phase with three phase inverter

Produces void fill or protective matting material

fill strip









wide

m

18mm

thick

Unlimited

Dust

50-60Hz 1.5kW

extraction device





W: 660mm

Warrantu

CP422S24MM-3PH

Three phase

Produces 4mm-wide void









as standard

CP428S2

Three phase

Produces void fill or protective matting material

CP428S24MM

Three phase

Produces 4mm-wide void fill strip















NUN

20mm thick

420mm



Output 6-9m3/hr 14mtr/min





W: 800mm D: 750mm H: 1100mm

12 months as standard

200V-400V 60Hz



Three phase

Produces void fill or protective matting material











420mm



Cuts

Output 7-10m3/hr 20mm thick Feed rate







W: 1100mm D: 750mm H: 800mm



400V 50-60Hz 4.0kW



Warrantu as standard



Optimax® Chipper and Dust Extractors

CP424C2-240V

Optimax Cardboard Chipper





Chipped cardboard has all the environmental and the environmental and cost-saving credentials of cardboard matting and void fill but is more easy-flowing and more effectively fills smaller cavities. It is also suitable for a wide range of applications from packaging void fill to pet and equestrian bedding.

optima



The high output chipper creates 1-2m³ of chipped cardboard per hour.



The hinged chute provides easy access for cleaning and maintenance.





Run time 4-5 hours



extraction device



230V 50-60Hz 1.1kW



Cuts 420mm

20mm



1-2m3/hr Feed rate 11mtr/min



D: 800mm H: 1350mm

0 12 months

200kg



Dust Extraction Unit Three Phase

> Reduce and collect airborne dust

Dust Extraction Unit

SFP100-1K


Single Phase

- > 3mtr connection hose > Compatible with the CP320S2-I
- single-phase shredder









- > Compatible with all Ecopax three phase shredders








Optimax® Service and Training

The Optimax® brand is a global standard that encapsulates the very best packaging equipment, innovation, engineering and consumables available to the packaging professional.



Optimax[®] offers a comprehensive technical advice service and training programme to ensure you maximise the full operating potential of your Optimax[®] packaging equipment.











Our highly trained technical team and nationwide network of authorised distributors can offer training either on-site or at an Optimax® training centre.

The Optimax® aftersales service offers complete peace of mind via our technical service centre, highly trained technicians and comprehensive parts and spares operation.



In addition to our large stock holding of spare parts, we have many years of experience in packaging equipment service and repair, which help to minimise the downtime in your packaging operation.





Please contact our sales team for more information on the Optimax® range of training and aftersales maintenance and service packages.

tamper evident and security packaging solutions

A range of high quality, reliable and innovative security products covering prevention and detection of mishandling and tamperage.

Sub-brands

- > Tegrabond® water activated tapes & tape dispensing systems
- > Tegralert® transit monitors
- $> Stickfast^{TM}$ hot melt glues & glue guns
- > Tegracheck® tamper evident tapes, labels & seals





Tegrabond® Water Activated Tape Dispensers





Largest tape capacity in the industry

- Features > High capacity water bottle sufficient for wetting 2,500-3,600mtr of 70mm wide tape

- Steel frame and rugged ABS casing construction
 Heavy duty, self-oiling blade
 Colour coded keys pre-set for popular tape lengths
- > Tape length adjustable in 0.5" (12.7mm) increments,

- up to 3050mm

 > Random length function dispenses tape to any length

 > Automatic function repeatedly dispenses tape lengths

 > Can be operated from either side of the machine

 > Manufactured to meet or exceed FCC, UL, CE and CSA (CUL) regulations

Benefits

- > Largest tape roll capacity in the industry
- Automatic functions for high productivity and versatility
 Excellent design and build quality for ease of use, long life and extended service intervals



Maximum tape width:

90gsm (excluding adhesive) Plain or reinforced WAT 220-240V AC, 50Hz, 500W Maximum tape weight: Tape compatibility: Power requirement:











- Steel frame and ABS casing construction
 Colour coded keys pre-set for popular tape lengths
 Tape length to 3050mm
- > UL, CE and CSA approved

- > Competitively priced > Excellent design and build quality for long life

Specifications Max. tape width:

Plain or reinforced WAT Tape compatibilitu: 220-240V AC, 50Hz, 500W









Manual Water Activated Tape Dispenser



- > Rugged design > Manual length adjustment > Max. 76cm tape length per stroke
- > Uniform wetting and clean cutting > Maximum tape roll diameter 190mm

- > Low investment for entry-level use> Simple maintenance
- > Easy to use
- > No power supply required

Specifications

Max. tape width:

Tape compatibilitu: Plain or reinforced WAT Water bottle capacity: Dimensions (L x W x H): 1.25 litres 533 x 267 x 241mm







Tegrabond® Water Activated Tape Dispensers



BP755

Electronic Water Activated Tape Dispenser







- > Colour coded keypad > Pre-set lengths (15-190cm) > Random key for infinite
- tape length
- > Dual water brushes > Heavy duty dual shear blades
- > Large enclosed water reservoir > Compatible with plain and reinforced WAT

 Benefits

> Extremely quiet operation Specifications

Min/max tape width: 25-100mm Power requirement: 240V 50Hz



EPS80

Bench Top Water Activated Tape Dispenser





Sturdy construction

Benefits
> Economical option for low volume usage and entry-level applications

Specifications Tape width: 80mm

Tape compatibility: Not suitable for reinforced tape



35

Bench Top Water Activated Tape Dispenser





> Excellent for low-volume

dispensers
> 25 - 75mm tape width

> Subway tape feed > Compatible with plain and

> Simple design, built to last **Specifications**



E-Z Pull Tab Tape



BP555-EZ

Electronic E-Z Pull Tab Tape Dispenser



> See BP555 for full details of features, benefits and specifications







BP333-EZ

Manual E-Z

Dispenser

Pull Tab Tape





> See BP333 for full details of features, benefits and specifications



Features





K7015B-EZPT E-Z Pull Tab Tape



- Strong, kraft paper tape > Water activated starch
- based adhesive
- > Integral tear strip > Compatible with BP333-EZ (manual) & BP555-EZ (electronic)

dispensers

- Benefits
 > Tear strip for easy,
- tool-free unpacking
 > Reduced risk of damage

to contents Specifications

Tape width: 70mm Tape length: 152mtr Rolls per case: 10



Accessories





Infra-red beam automatically calculates carton dimension. Dispenser creates perfect tape length.





Benefits
> Ideal for use in packing environments processing variable-sized cartons

every time

> Improves productivity by up to 20%

> Calculation of tape length

requirements based on infra-red beam measurement > Interfaces with Tegrabond®

dispensers to automatically create perfect tape lengths

> Reduces tape usage and wastage caused by incorrect

length dispensing

Specifications Length of lead: 10mtr



Provides hands-free versatility and improved productivity











Automatic Measuring Device



Tegrabond® Water Activated Tapes

Tegrabond® Plain Tapes

- > High quality Tegrabond® water-activated paper tape increases consignment integrity
- > Increased stock holding. All sizes available from stock

Code	Width	Loogth	Veaft weight	Kraft colour	Gummed side in/out	Rolls/case	
	vvidtii	Length	Kraft weight	Kiait Coloui	III/OUT	RUIIS/Case	
38mm Core							
K2420B-60GSI	24mm	200mtr	60gsm	Brown	In	48	
K3620B-60GSI	36mm	200mtr	60gsm	Brown	In	36	
K3620B-60GSO	36mm	200mtr	60gsm	Brown	Out	36	
K4820B-60GSI	48mm	200mtr	60gsm	Brown	In	30	
K4820B-60GSO	48mm	200mtr	60gsm	Brown	Out	30	
K7020B-60GSI	70mm	200mtr	60gsm	Brown	In	18	
K7020B-60GSO	70mm	200mtr	60gsm	Brown	Out	18	
K9620B-60GSI	96mm	200mtr	60gsm	Brown	In	12	
K9620B-60GSO	96mm	200mtr	60gsm	Brown	Out	12	
K4820B-70GSI	48mm	200mtr	70gsm	Brown	In	30	
K7020C38B-70GSI	70mm	200mtr	70gsm	Brown	In	18	
K7020B-90GSI	70mm	200mtr	90gsm	Brown	In	18	
K7020B-90GSO	70mm	200mtr	90gsm	Brown	Out	18	
K4820W-70GSI	48mm	200mtr	70gsm	White	In	30	
76mm Core							
K5020C76B-60GSO	50mm	200mtr	60gsm	Brown	Out	24	
K7020C76B-60GSO	70mm	200mtr	60gsm	Brown	Out	16	
K7020C76B-70GSO	70mm	200mtr	70gsm	Brown	Out	18	
K7015C76B-90GSO	70mm	150mtr	90gsm	Brown	Out	18	
K5020C76B-70GSO	50mm	200mtr	70gsm	Brown	Out	24	
K6020C76B-70GSO	60mm	200mtr	70gsm	Brown	Out	24	
K9620C76B-70GSO	96mm	200mtr	70gsm	Brown	Out	12	
K5020C76B-60GSI	50mm	200mtr	60gsm	Brown	In	24	
K7020C76B-60GSI	70mm	200mtr	60gsm	Brown	In	18	
K5020C76W-90GSO	50mm	200mtr	90gsm	White	Out	24	
K7020C76W-90GSO	70mm	200mtr	90gsm	White	Out	18	

Tegrabond® Reinforced Tapes

Code 38mm Core	Width	Length	Tape weight (combined)	Kraft colour	Gummed side in/out	Rolls/case	kg/ case
KR4810B-GSI	48mm	100mtr	125gsm	Brown	In	24	7.9
KR7010B-GSI	70mm	100mtr	125gsm	Brown	In	16	15.0
KR7010BW-GSI	70mm	100mtr	125gsm	Oyster	In	16	15.1
KR7015B-GSI	70mm	152mtr	125gsm	Brown	In	6	8.6
KR7015BW-GSI	70mm	152mtr	125gsm	Oyster	In	6	8.6
76mm Core							
KR7010C76B-GS0	70mm	100mtr	125gsm	Brown	Out	16	15.0
KR7615SW-GSI	76mm	152mtr	125gsm	Snow White	In	6	10.5

Tegrabond® Pre-Printed Reinforced Tapes

- KR7015-SENSEAL is printed with the SENTRY SEAL' brand, which highlights the tamper-proof properties of the tape
 KR7015B-CAUT is printed with a 'CAUTION IS THIS PACKAGE DAMAGED?' message, which encourages recipients to check for damage before opening the package

 > KR7015B-IMPA is printed with an 'IMPORTANT CAUTION' print, which alerts personnel to the need for careful handing

- Printed tapes send a clear deterrence that the consignment requires appropriate care and will be subject to scrutiny on arrival
 Pre-printed messages are available from stock and without the extra MOQs and costs of custom-printed tape

Code	Width	Length	Printed message	in/out	Rolls/case	kg/ case
KR7015-SENSEAL	70mm	152mtr	SENTRY SEAL	In	6	8.7
KR7015B-CAUT	70mm	150mtr	CAUTION IS THIS PACKAGE DAMAGED?	In	6	8.6
KR7015B-IMPCA	70mm	150mtr	IMPORTANT CAUTION	In	6	8.6



Tegrabond®

The ultimate tape-applied security seal



Go to www.xtegraproducts.com to view the new Tegrabond® brochure for more details

Consider the advantages...



An Integral Closure

The adhesives in Tegrabond® water activated tape penetrate into the fibres of the carton, creating a total bond. As the tape becomes an integral part of the carton this adds considerable strength and security to the closure. Adhesives used on conventional pressuresensitive packing tapes remain 'wet' and will lose adhesion with time or when subjected to extremes of temperature or humidity.

2



Tamper Evidence

Tegrabond® uses a permanent adhesive which prevents removal of the tape without clearly visible proof of tamperage or damage to the carton. Glassfibre reinforced Tegrabond® further enhances security. Cartons sealed with conventional packing tape can be easily compromised, as application of gentle heat will soften and reactivate the adhesive, permitting entry to the carton and resealing with no visible trace of disturbance.

3



100% Recyclability

Tegrabond® is made entirely from renewable natural resources, which enables it to be easily recycled along with cardboard waste and suitable for landfill. Packaging research associations have all given Tegrabond® recyclability accreditation, making it the environmentally-friendly choice for the packaging professional. Tegrabond® water activated tape shows the customer that you care for the environment.

4



Temperature Tolerant

Even with extreme variations of temperature and humidity, Tegrabond® retains its seal strength and remains highly resistant to ageing, making it the ideal solution for long-term storage.

5



Improved Packaging Presentation

Tegrabond® outperforms plastic tape on presentation.

Available in natural, oyster and white kraft, it blends naturally with cardboard cartons and is perfectly suited to personalised printing. With its greater rigidity and adhesion, Tegrabond® avoids the ripples, bubbles, creasing, multiple layers and incomplete adhesion that are common with conventional tapes.

6



Cost Savings

Independent studies have proven that as Tegrabond® uses less tape and creates a more secure seal, it provides more cost-effective carton sealing than conventional tape, particularly when used in conjunction with a Tegrabond® electronic dispensing system

7



Increased Productivity and Reduced Operator Fatique

The same independent studies also revealed that the combination of Tegrabond® water activated tape and Tegrabond® tape dispensing systems results in increased productivity and reduced incidence of operator fatigue. By switching to Tegrabond®, medium-high volume users of packing tapes soon recoup the moderate costs of investment and create a happier, healthier and more productive working environment.

Tegralert®

High visibility indicators of in-transit mishandling

Innovative transit monitors that deter and detect mistreatment











Consider the advantages...



Clear Deterrent

Tegralert® monitors display a consignment's handling requirements either on the monitor or on a companion label, and act as a clearly visible deterrent to mishandling of packaged goods in transit or in storage.

2 Sold The Mass occurrents of the second of the second occurrence occurrence occurrence of the second occurrence oc

Clear Exposure

If consignment handling requirements are not observed, Tegralert® monitors will detect and permanently display evidence that mishandling has occurred. Recipients will therefore be alerted to the need to check a consignment for damage prior to accepting delivery.



Clear Accountability

By using Tegralert® monitors the consignor will ensure that in the event of a claim for in-transit damage, there will be clear evidence that can be used to establish the cause of damage and expedite compensation from the responsible party.

Xtegra® Tegralert® Transit Monitors





- > Detects potential damage by activating when a pre-set level of G-force is exceeded on impact
- Suitable for monitoring impact ranging from 5G to 100G
- > Can be applied to consignment with adhesive backing, nails or screws
- > Supplied with companion labels

Renefits

- > Permanent, irreversible evidence
- > Easy to apply to any surface > Highly visible
- > Will not activate before use

DNT-IB Drop'n'Tell Monitors



Packed 100/hox

Pack weight	Container Area in Cubic Metres							
(kg)	0.00-0.028	0.028-0.142	0.142-0.425	0.425-1.416	1.416+			
0.00-4.53	DNT-LB100	DNT-LB100	DNT-LB50	DNT-LB50	DNT-LB25			
4.53-11.34	DNT-LB100	DNT-LB50	DNT-LB50	DNT-LB25	DNT-LB25			
11.34-22.68	DNT-LB50	DNT-LB25	DNT-LB25	DNT-LB25	DNT-LB25			
22.68-45.36	DNT-LB50	DNT-LB25	DNT-LB25	DNT-LB15	DNT-LB15			
45.36-113.4	DNT-LB25	DNT-LB25	DNT-LB15	DNT-LB15	DNT-LB15			
113.4-453.6	DNT-LB15	DNT-LB10	DNT-LB10	DNT-LB10	DNT-LB10			
453.6+	-	-	DNT-LB10	DNT-LB10	DNT-LB10			

This chart should only be used as a basic guide. Drop'n'Tell activation depends upon the type and amount of cushioning used to protect a product in transit. Drop height will also affect activation.




- > Monitor incorporated in label
- > Five colour-coded sensitivitu levels
- > Applied to consignment with self adhesive backing

- Permanent, irreversible evidence
- > Highly visible, requires no companion label
- Colour-coding facilitates correct monitor selection

Packed 100/box

SWL

Shockwatch Monitors



DELIVERY:

Due to the sensitivity of Shockwatch, deliveries are made direct to

Due to the Sensioning of Indexword, jewelles are index direction you and charges will apply to cover for special transit packaging and carriage. Shockwatch orders will be treated as separate orders from all other products you order and Shockwatch monitors cannot be returned or refunded.

This chart should only be used as a basic guide, as the choice of monitor should take into account product fragility and the type and degree of cushioning used.

Field trials are recommended prior to use.

CAUTION!

CAUTION!
Claims cannot be accepted if signed for as received in good condition.
Drop/nTell monitors are an ideal alternative as they are only activated by removing the special pin.



Features

- > Activates when tilted 80° from vertical (+5°)
- > Can be applied to consignment with adhesive backing, nails, screws or
- > Moisture-proof

Benefits

- > Permanent, irreversible evidence
- > Easy to apply to any surface > Highly visible
- > Ideal for export consignments

Packed 30/box

SWL-C

Shockwatch Companion Labels



Used in combination with SWL Shockwatch monitors, these labels highlight the additional measures being used to ensure careful handling and detect if mishandling has occurred.

Packed 200/roll



TIITW

Tiltwatch Monitors

Non-Stack Cones



NSC

A simple to use, effective and highly visible deterrent to pallet stacking where this might damage the consignment or the integrity of its packaging.

Tegralert® Non-Stack Cones are supplied flat-packed and are quickly assembled. They can be attached to a palletised consignment either by taping down the feet of the cone or by running pallet strap through the pre-cut slots.

Sold in bundles of 25









- > Activates at 80° from vertical (±5°) > Can be applied to consignment with adhesive backing, nails, screws or
- > Supplied with companion labels

- > Permanent, irreversible evidence
- > Easy to apply to any surface
- > Hiahlu visible > Will not activate before use





Stickfast®

The pinnacle of effective, modern glue gun design

Stickfast Glue Guns are suitable for many adhesive applications, from creating a secure tamper evident seal on carton consignments to multiple manufacturing and industrial uses.











All Stickfast glue guns are designed for regular industrial use and feature a wide range of benefits:









Xtegra® Stickfast Glue Guns

GX80LT **GX80**

240V 80W

FSS12/HSS12

MPS12/LT12

8g/min

Light Duty 12mm | Low Temperature Light Duty 12mm

- > Fine nozzle
- > Pre-set temperature > Removable stand
- > Comfortable grip
- > Long trigger > Low temperature operation (GX80LT)

Benefits

- > Entry-level industrial quality > High dispensing accuracy > Comfortable use

Specifications

- > Power requirement:
- > Operational temperature 193°C CX80. GX80LT:
- > Glue type (12mm stick): GX80: GX80LT:
- > Maximum glue output:



Fine nozzle for accurate glue application



Comfortable grip and long trigger for added operator comfort



Removable gun stand



GX120

Light Duty 12mm

Features

- > Fine nozzle
- > Pre-set temperature
- > Removable stand > Comfortable grip
- > Long trigger

Benefits

- > Entry-level industrial quality > High dispensing accuracy > Comfortable use

Specifications

- > Power requirement: 240V: > Operational temperature: 193°C 240V 120W 12mm stick
- > Glue type: > Maximum glue output: 13g/min



Fine nozzle for accurate alue application



Comfortable grip and long trigger for added operator comfort



Removable gun stand



/off switch



GX300

Medium Duty 12mm

Features

- > Temperature adjustment > Glue flow-rate adjustment
- > Removable stand > Rubberised grip
- > Long trigger > Illuminated on/off switch

- > High output industrial quality
 > High dispensing accuracy
 > Comfortable use

Specifications

> Power requirement: 240V 300W > Operational temperature: 120-230°C > Glue type: 12mm stic > Maximum glue output: 25g/min



Glue adjuster screw to control amount of glue dispensed.



Comfortable rubberised grip and long trigger



Temperature control dial to suit glue application



Illuminated on



Xtegra® Stickfast Glue Guns

GX600

Heavy Duty 18mm

- > Temperature adjustment
- > Glue flow-rate adjustment > Integral stand
- > Rubberised grip
- Long triggerIlluminated on/off switch

Benefits

- > Extra high output
- High dispensing accuracyComfortable use

Specifications

- > Power requirement: 240V 600W > Operational temperature: 140-230°C 2/10// 600///
- > Glue type: > Maximum glue output:

18mm stick

42a/min

Comfortable rubberised grip and long trigger

Glue adjuster screw to

control amount of glue dispensed





off switch



SL120

Slimline Light Duty 12mm

Features

- > Ergonomic styling
- Rubberised grip and long trigger
 Glue output adjustment
 Illuminated on/off switch

- > Removable stand

Benefits

- High output industrial qualityHigh dispensing accuracyComfortable use

Specifications

- > Power requirement: 240V 2 > Operational temperature: 193°C 240V 220W > Glue type: 12mm sticks
 > Maximum glue output: 20g/min



Fine nozzle for accurate alue application



Comfortable grip and long trigger for added operator comfort



Glue adjuster screw to control amount of glue



Illuminated on/



SL300

Slimline Medium Duty 12mm

Features

- > Ergonomic styling > Rubberised grip and long trigger
- > Temperature and glue flow-rate adjustment
- > Illuminated on/off switch > Removable stand

Benefits

- > Extra high output > High dispensing accuracy
- > Comfortable use

Specifications

- > Power requirement: 240V 300W > Operational temperature: 120-230°C > Glue type:
- > Maximum glue output: 30g/min



Glue adjuster screw to control amount of glue dispensed.



Comfortable rubberised grip and long trigger



Temperature control dial to suit glue application.



Illuminated on



Xtegra® Stickfast Glues and Accessories

HGS06

19-hole Nozzle

HGS00-HGS05



HGS00

HGS01

HGS02

hotmelt glue guns

Compatible with Stickfast

HGS05

Used with Stickfast hotmelt alue auns to spread alue

evenlyover a wide area.



Hotmelt Adhesives

Precision extruded to fit Stickfast glue guns and compatible with most glue guns on the market.









Ideal for bonding heat sensitive

materials e.g. polystyrene without damage. Also use on

fabrics, paper, card etc. Use in



Product Name
Suitability

FSS Fast Set

Fast setting stick for bonding card & paper. Ideal for carton sealing & packaging.

Superior fast setting hotmelt

Sticks 12mm x 300mm **(FSS12)**

Multipurpose

The most popular glue stick. Use for fabrics, upholstery, plastics etc. Long set time.

All purpose hotmelt with medium to long set time. Ideal for a wide range of industrial and general-use applications.

20-30 sec

Sticks 18mm x 300mm (MPS18)

White Sticks 12mm x 300mm (MPS12) Sticks 12mm x 300mm (LTS12)

LTS12

LTS12

Special hotmelt applied at lower temperature. Ideal for heat sensitive products and reduced risk of accidental burns.

Low Melt

low temp guns.

15-20 sec

All low temp. models

HSS High Strength

Higher strength for assembly. Excellent on many plastics, metal & wood.

set time set colour

description

sizes (mm)

Sticks 18mm x 300mm (FSS18) Slugs 43mm x 43mm (FSS43) applicator gun* All models

for rapid closing and sealing of cartons. Ideal for all packaging applications. 5-10 sec

All models

0

0

0

0

MPS12

MPS12

MPS18

MPS18

MPS43

MPS43

Slugs 43mm x 43mm (MPS43)

'difficult' surfaces. Excellent adhesion and high molten tack for quick fixing of tile displays, carpet fitting etc.

Assembly grade hotmelt for

20-30 sec Amber

Sticks 12mm x 300mm (HSS12) Sticks 18mm x 300mm (HSS18) Slugs 43mm x 43mm (HSS43)

All models

materials bonded:

plastic	
wood	0
textile	0
polystyrene	0
cardboard	•
metal	

ceramic 12mm Sticks (Price per box)

18mm Sticks (Price per box) 43mm Slugs

(Price per box)

Quantity and weight per box 12mm = 34 sticks per kg, 170 sticks per box, 5kg per box 18mm = 14 sticks per kg, 70 sticks per box, 5kg per box 43mm = 17 slugs per kg, 170 slugs per box, 10kg per box 85 slugs per box, 5kgs per box

FSS12

FSS12


FSS18

FSS18

FSS43

FSS43

(● = Recommended 1st choice; \bigcirc = Recommended alternatives) *Please specify correct stick size for your gun when ordering.



0

HSS12 HSS12 HSS18 HSS₁₈ HSS43

HSS43

All other codes



Xtegra® Tegracheck® Tapes and Security Labels

Tegracheck®

Fast identification of product contamination

Essential for the food, pharmaceutical, manufacturing and logistics industries.









Consider the advantages...



Visible Deterrent



Easily Identifiable

Huge Range of Applications

Xtegra® Tegracheck® Tapes and Security Labels

Tamper Evident Security Tape

Features

- Warning message on top surface
 Printed OPEN VOID message adheres firmly to
 most surfaces and cannot be easily removed without leaving visible traces or damage

 > Available in TSR50 high-visibility red and TSB50 food
- industry blue

- > Deters theft of valuable or sensitive contents
- > Deters tamperage and deliberate contamination of food and pharmaceutical products
- > Clearly exposes where unauthorised access to contents has occurred

Specifications

- > Tape width: 48mm > Tape length: 50mtr
- > Rolls per case: 48





Code	Text	kg/ case
TSB50	OPEN VOID - Blue Adhesive	14.7
TSR50	OPEN VOID - Red Adhesive	14.7
		-

Tamper Evident Labels

Total Transfer Labels

- > High quality label and print
- Permanent OPEN VOID message left on surface following removal of the label

- Ideal for applications requiring a high level of presentation
 Combine with Tegrabond® water activated tape for highly secure and presentable packaging
- 250 labels per roll



Code	Size	Colour	kg/ case
TSLR4040	40mm dia.	red	0.12
TSLR5020	50 x 20mm	red	0.12
TSLR8540	85 x 40mm	red	0.24

Non-activated label



Tamper Evident Labels

Non-Transfer Labels


- > High qualitu label and print
- > OPEN VOID message retained within label on activation
- > Leaves no residue on removal

- > Suitable for pharmaceutical, medical, hospitality, catering, electronics and law enforcement sectors
- > Tupical uses:
- security sealing reusable packaging containers
- temporary bonding of aircraft and vehicle doors, hospital and
- catering trolleys

 restricting access to controlled areas of buildings or equipment

250 labels per roll





Ideal for applications requiring a high level of presentation Non-activated label



Activated label

TSPT175R

Pull-Tight Security Seals

- > Rapid, secure knurled-tail locking system > Sequentially numbered tag

- > Easy to use with bags, sacks, crates and cages
- > Numbering allows security tracking

Specifications

- > Material: Polypropylene > Tag size: 35 x 20mm
- > Useable length: 175mm > Burst strength: 15kg > Pack quantity: 100 seals



TSPT430R

Bag Security Seals

- > Rapid, secure flat-tail locking system
- > Sequentially numbered tag > Higher burst strength

Benefits

- > Easy to use with bags, sacks, crates and cages
- > Longer length tail ideal for wider bag necks
- > Numbering allows security tracking

Specifications

- Material: Polypropylene > Tag size: > Total length: 22 x 68mm > Useable length: 310mm > Burst strength: 35kg
- > Pack quantity: 100 seals









- > kraft edge boards
- > plastic corner protectors
- > plastic pallets
- protective sleeving
- stretch wrap dispensers and films
- industrial das shrink sustems and films
- > assorted pack room products
- tarpaulins and ratchet straps
- > anti-slip sheets

Sub-brands

- > Kraftek® kraft edge boards
- > Slipquard™ anti-slip sheets



Transpal® Parcel Labels & Silica Gel

Parcel Labels



COM-LB1 Combination **Shipping Labels**



- Save time and money with these multi-instruction labels
 Label size 102mm x 102mm
- > 500 labels/roll



Code	Size (mm)) Qty/roll	Description	l kg/a
SG45GFR	45 x 60	500	FAGILE	0.24
SG80AS	80 x 35	1,000	CHIEF CANDING CONTROL OF CONTROL	0.50
SG89FR	89 x 32	1,000	FRAGILE	0.50
SG89GL	89 x 32	1,000	GLASS	0.50
SG89UR	89 x 32	1,000	URGENT	0.50
SG89S0	89 x 32	1,000	SOLD	0.50
SG89HA	89 x 32	1,000	HANDLE WITH CARE	0.50
SG89D0	89 x 32	1,000	DOCUMENTS ENCLOSED	0.50
SG89DN	89 x 32	1,000	DO NOT BEND	0.50
SG148FR	148 x 50	500	FRAGILE	0.70
SG148GL	148 x 50	500	GLASS WITH	0.70
SG148HA	148 x 50	500	HANDLE WITH	0.70
SG148D0	148 x 50	500	DO NOT CRUSH	0.70
SG148NS	148 x 50	500	DO NOT USE SHARPS OPEN WITH CARE	0.70
SG148HV	148 x 50	500	CAUTION HEAVY PACKAGE	0.70
SG108FR	108 x 79	500	FRAGILE	0.70
SG108HA	108 x 79	500	MARKE. WITH CLOSE	0.70
SG108TH	108 x 79	500	THIS THAT OP	0.70
SG108NS	108 x 79	500	DO NOT STACK	0.70
SG108LI	108 x 79	500	LIQUID INSIDE	0.70

PD611T

Bench Label Dispenser



- > Can be secured to bench for added stability
- > 160mm maximum roll width> 210mm maximum roll diameter
- > Ideal for use with Transpal® Parcel Labels







Transpal® Hazard Labels & Tags

Hazard Warning Labels

- > Self-adhesive printed vinyl
- > Label size 100 x
- > 250 labels per roll
- > Price per roll

Other hazard warning labels available on request.













Code	Label size (mm)	kg/ roll
HAZ211	100 x 100	0.4
HAZ220	100 x 100	0.4
HAZ230	100 x 100	0.4
HAZ231	100 x 100	0.4
HAZ310	100 x 100	0.4

Code	Label size (mm)	kg/ roll
HAZ411	100 x 100	0.4
HAZ810	100 x 100	0.4
HAZ910	100 x 100	0.4
HAZ2000	125 x 110	0.7

White Plastic Tags

- > Solid plastic
- > Rounded corners > Pre-punched for stringing
- > Water/oil resistant

				_
Code	Size (mm)	Thickness (mu)	Qty per pack	kg/ pack
WPT45	100 x 45	250mu	500	0.5
WPT55	110 x 55	250mu	500	0.6
WPT70	120 x 70	250mu	500	1.5



Paper and Paper Faced Tags & Labels

White card tags with reinforced eyelets							
Code	-	-		Otroposalo	kg/ pack		
	Size (mm)		Wires	Qty per pack			
WPL6-1000		White	-	1,000	0.6		
WPL6-1000V	V 80×38	White		1,000	0.9		
WPL4	82 x 41	White	10" Wire	500	0.5		
STCR4	82 x 41	White	10" String	1,000	0.9		
WPL7-1000	110 x 51	White	-	1,000	0.9		
WPL7-1000V	V 110×51	White	10" Wire	1,000	1.3		
WPL5	120 x 60	White	10" Wire	500	1.1		
WPL5-1000	125 x 63	White	-	1,000	1.5		
WPL8-1000V	V 125 x 63	White	10" Wire	1,000	1.9		
WPL9-1000	140 × 70	White	-	1,000	1.8		
WPL9-1000V	V 140×70	White	10" Wire	1,000	2.1		
Coloured care	d tags with re	inforced	eyelets				
BPL5	125 x 63	Blue	-	1,000	1.5		
BPL5-W	125 x 63	Blue	10" Wire	1,000	1.9		
GPL5	125 x 63	Green	-	1,000	1.5		
GPL5-W	125 x 63	Green	10" Wire	1,000	1.9		
RPL5	125 x 63	Red	-	1,000	1.5		
RPL5-W	125 x 63	Red	10" Wire	1,000	1.9		
YPL5	125 x 63	Yellow	-	1,000	1.5		
YPL-5W	125 x 63	Yellow	10" Wire	1,000	1.9		
Paper faced r	metal labels v	vith strap	ping slots				
WLM6	115 x 60	White	-	250	2.2		



Kraftek® Edgeboards

Kraftek® Edge Boards

- Choose from 40 types
 Protection of box edges against damage from strapping
 Enhanced load stability and void bridging for uniform palletisation
- > 100% recyclable




Additional sizes now available



Code	Length (mm)	Flange widths (mm)	Thickness (mm)	Qty per pack	kg/ pack	Qty per pallet
KVB35.2.1000	1000	35 x 35	2.0	50	4.5 5.4	6,300
KVB35.2.1200		35 x 35 35 x 35	2.0	50	9.0	2,700
KVB35.2.2000			2.0	25		2,100
KVB35.3.475	475	35 x 35	3.0	50	2.5	8,000
KVB35.3.500-40		35 x 25	3.0	40	2.64	2,000
KVB35.3.910	910	35 x 35	3.0	50	5.8	6,000
KVB35.3.1000	1000	35 x 35	3.0	50	6.6	5,100
KVB35.3.1200	1200	35 x 35	3.0	50	8.2	4,200
KVB35.3.1500	1500	35 x 35	3.0	50	8.4	4,200
KVB35.3.1750	1750	35 x 35	3.0	50	11.9	4,200
KVB35.3.1800	1800	35 x 35	3.0	50	13.6	4,200
KVB35.3.2000	2000	35 x 35	3.0	50	13.9	4,200
KVB35.4.532	532	35 x 35	4.0	50	2.5	5,100
KVB45.3.1000-50	1000	45 x 45	3.0	50	9.17	3,000
KVB50.2.1000	1000	50 x 50	2.0	50	5.6	5,400
KVB50.3.500-40		50 x 50	3.0	40	4.12	3,000
KVB50.3.900	900	50 x 50	3.0	50	9.17	6,300
KVB50.3.1000	1000	50 x 50	3.0	50	10.3	2,700
KVB50.3.1200	1200	50 x 50	3.0	50	10.1	3,000
KVB50.3.1500	1500	50 x 50	3.0	50	14.3	3,000
KVB50.3.1750	1750	50 x 50	3.0	50	15.7	2,700
KVB50.3.1800	1800	50 x 50	3.0	50	17.9	2,700
KVB50.3.2000	2000	50 x 50	3.0	50	20.8	2,700
KVB50.35.580	580	50 x 50	3.5	50	3.8	3,150
KVB50.35.780	780	50 x 50	3.5	25	4.5	2,500
KVB50.35.1280	1280	50 x 50	3.5	50	14.11	2,500
KVB50.4.1000	1000	50 x 50	4.0	50	12.59	5,400
KVB50.4.1200-40	1200	₹ 50 x 50	4.0	40	12.09	4,000
KVB60.2.1300	1300	60 x 60	2.0	50	10.67	6,000
KVB60.3.1000	1000	60 x 60	3.0	25	5.65	2,700
KVB60.3.2000	2000	60 x 60	3.0	25	11.3	2,700
KVB75.25.1000	1000	₹ 75 x 75	2.5	25	8.13	2,000
KVB75.3.800	800	75 x 75	3.0	25	7.8	2,500
KVB75.3.1800	1800	75 x 75	3.0	25	13.5	2,000
KVB80.6.500-40	500	80 x 80	6.0	40	12.09	1,000
KVB80.6.1000-40	1000	80 x 80	6.0	40	24.18	1,120
KVB80.6.1500-20	1500	80 x 80	6.0	20	18.14	960
KVB100.3.1000W	1000	№ 100 × 100	3.0	25	6.9	1,250
KVB100.5.1000W	1000	100 x 100	5.0	20	9.2	1,120
KVB100.5.1830W	1830	100 x 100	5.0	20	16.8	1,120

Kraftek® Moisture Resistant Edge Boards

- > Use for applications that are exposed to moisture, including outdoors
- > 100% recyclable



Kraftek® Corner Protectors & Transpal® Edge Protectors

Perforated Edge Boards

- > Good impact absorption qualities > A cost-effective use of most economic lengths > 15mm thick, 6-ply corrugated board > Perforated at 200mm intervals





Code	Length (mm)	Flange widths (mm)	Qty per pack	kg/ pack
CP80120	1200	80 x 80	50	12.5
CP50120	1200	50 x 50	50	10.0

Corrugated Corner **Protectors**

- > Good impact absorption qualities
- > 15mm thick, 6-ply corrugated board



Code	Dimensions	Qty	kg/
	(mm)	per pack	pack
CPC80	80 x 80 x 80 (internal)	290	14.25

Expanding Corner Protectors

> Versatile size-adjustable profile protection

Size Medium	Qty per box 1000	kg/ box 7.8
-	250	6.0
		Size per box Medium 1000 suit 16 - 40mm 250



Open Corner Protectors

> Perfect for protection of exposed corners on picture frames, worktops, board products etc.

Code		Flange depth (mm)	Qty per box	kg/ box
CPRO-1	60 x 60	28	1,000	10.5



Closed Corner Protectors

> Optimum corner protection for wood and laminated products

















Code	Flange widths (mm)	depth		Qty per box	kg/ box
CCP15	60 x 60	15	Regular	1,000	9.42
CCP18	60 x 60	18	Regular	1,000	9.56
CCP22	60 x 60	22	Regular	850	8.3

Code	Flange widths (mm)	depth		Qty per box	kg/ box
CCP28	60 x 60	28	Regular	700	7.9
HDRC28	3 60 x 60	28	Heavy Duty	800	10.9
HDRC40	0 60 x 60	40	Heavy Duty	600	11.5

Transpal® Silica Gel Sachets and Protective Sleeving

Silica Gel Sachets

An essential product for all moisture sensitive products whilst in-transit and storage










Fashion Accessories

Electrical Goods

Pharmaceuticals

Optical Industry



> Ideal for: electronics, precision equipment, leathergoods, pharmaceuticals etc.. > Recommended application: 5g per cubic foot, ensuring package is airtight

> Price per pack



	1	-4/1	alac
Code	Sachet weight (g)	Sachet size (mm)	Sachets per pack
SGS1	1	18 x 33	500
SGS5	5	37 x 52	250
SGS10	10	36 x 74	500
SGS25	25	47 x 122	500
SGS50	50	86 x 127	250
SGS100	100	71 x 158	200
SGS250	250	113 x 181	100
SGS500	500	108 x 253	50





Protective Sleeving



Features

- > Colour coded sleeve diameters
- > Low-density polyethylene
- > Resistant to acids and solvents
- > Unaffected by oils and greases

Benefits

- > Can be reused many times over
- > Flexible protection of irregular shapes
- > Holds itself in place without need for adhesive tape etc.
- > Ideal for use in harsh industrial and outdoor environments

Applications

- Protection of machined parts during manufacture
 Protection of painted or varnished furniture legs
- > Protection of items made of glass or ceramic during storage and transit
- > Protection of finished components e.g. window furniture prior to installation





Code	Colour	Min ø	Max ø	Length	Qty/ box	kg/ box
TP5	Clear	7mm	15mm	200mtr	4	11.1
TP10	Violet	10mm	20mm	200mtr	4	13.8
TP20	Blue	25mm	50mm	200mtr	4	22.0
TP50	Yellow	35mm	70mm	200mtr	2	16.8
TP75	Brown	50mm	75mm	200mtr	2	19.6
TP100	Red	50mm	100mm	200mtr	2	21.2
TP150	Orange	75mm	150mm	50mtr	2	10.5

Transpal® Stretch Film Dispensers

SR80

Standard Dispenser



BWR4050

Bow Wrapper



Features

- > Suitable for 400mm and 500mm wide stretch film
- > Suitable for 38mm, 50mm and 75mm cores
- > 6 dispensers per case

DPD38

Dispenser

- Features
 > Hand grip dispenser
 > Lightweight plastic
 construction
- > Suitable for any stretch film on
- 38mm core > 32 dispensers per case



DPD50

Dispenser

- Features
 > Hand grip dispenser > Lightweight plastic construction
- > Suitable for any stretch film on 50mm core > 32 dispensers
- per case



TMW

Heavy Duty Telescopic Dispenser

> Handle position gives more balanced tension across film

> Reduced back and wrist strain > 4 dispensers per case

- Features > Suitable for 400mm wide stretch film on
- 38mm, 50mm and 75mm cores > Suitable for 500mm wide stretch film on
- 50mm and 75mm cores > 6 dispensers per case



HSAV38

Handsavers

Features


- > Insert into core ends to protect hands from friction > Suitable for all 38mm core stretch films
- > Low cost and lightweight
- > 75 pairs per case



SSX12 Stretchsaver

Features

- > Ergonomic stretch film dispenser
- > Automatic tensioning
- > Suitable for 250 610mm wide stretch films on 50mm cores





HW38

Handy Wrap Dispenser

- Features > For Handy Wrap stretch film on 38mm core > 12 per box, 144 per outer



Handy Wrap Film

- Features > 100mm film width, 150mtr roll length > 140 x 38mm extended core

> 140 x 38mm extended core			Rolls per	Д
Code	Colour	Thickness		kg case
HWF100	Clear	15mu	36	8.0
HWF17	Clear	17mu	40	9.86
PS1116B	Black	17mu	36	12.38

HWSC

Handy Wrap Dispenser

- Features > For Handy Wrap stretch film on 38mm core
- > 12 per box



HWF6K Handy Wrap Kit

- Features > 1 x HWSC Dispenser > 6 rolls of HWF100 film



HWFKI

Handy Wrap Starter Kit

- > 2 x HW38 dispensers > 10 x HWF100 rolls
- > Convenient carry box





Cast Stretch Film



Code	Film width	Film length	Film thickness	Core	Rolls /case	kg
CCE417	400mm	300mtr	17mu	38mm ext core	6	12.7
CCS417	400mm	300mtr	17mu	38mm std core	6	12.5
CCE420	400mm	300mtr	20mu	38mm ext core	6	15.7
CCS420	400mm	300mtr	20mu	38mm std core	6	14.4
CCS520	500mm	300mtr	20mu	50mm std core	6	20.6

Blown Stretch Film

Code	Film width	Film length	Film thickness	Core	Rolls /case	kg
BCE417	400mm	300mtr	17mu	38mm ext core	6	13.1
CBE417 (Blue Tint)	400mm	300mtr	17mu	38mm ext core	6	12.74
BCE420	400mm	300mtr	20mu	38mm ext core	6	14.84
BCS520	500mm	300mtr	20mu	50mm std core	6	19.0
BCS5234	500mm	200mtr	34mu	50mm std core	6	15.9

Black Opaque Stretch Film



Code	Film width	Film length	Film thickness	Core	Rolls /case	kg case
BBKS-525	500mm	250mtr	25mu	50mm standard core	6	13.1
BBKS-4317	400mm	300mtr	17mu	38mm extended core	6	13.1

Power Machine Stretch Film Cast 300%





Code	Film width	Film length	Film thickness	Core	kg roll
MSF520	500mm	1700mtr	20mu	76mm ID standard core	17.7
MSF523	500mm	1550mtr	23mu	76mm ID standard core	18.6

Pre-stretched Hand Film

> 240 rolls/pallet

Code	Film width	Film length	Film thickness	Core	Rolls /case	kg
PSH468	400mm	600mtr	8mu	40mm ID 530mm ext. length	6	12.3

Pro-stratched Machine Film

> 63 rolls/pallet

LIE-2016	יו טשווט	יוטכוווווי			· 03 / 0(13) politice	
Code	Film width	Film length	Film thickness	Core		kg
PSM438	440mm	2800mtr	8mu	100mm ID		10 14

463mm ext. length

Benefits of pre-stretched film






8mu pre-stretched film



Pre-stretched uses up to 50% less film than standard film to secure a load to the same standard, resulting in up to 50% cost savings and packaging waste reduction.







Gas Shrink Systems and Accessories

GSG100 Gas Shrink Gun System

PFD-1

Shrink Film Roll Dispenser

Features:

- > Lockable castors
- > Expands to up to 2mtr wide roll capacity
- > Holds and dispenses up to 3 roll products simultaneously
- Supplied with one spindle as standard (additional spindles available on request)
- > Dimensions: 870 x 2000 x 660mm (HxWxD)





Additional Telescopic Spindle

Features:

- > Low cost system
- > 32kW power
- > Complete system including 8mtr hose & safety regulator valve
- > Uses propane gas

Transpal GSG100 Genuine Spares Part No. Description 0.12 GSG/3 Gas Tap GSG/5 Spark Generator 0.04 0.01 GSG/9A Electrode - Spark Plug GSG/10 0.19 Flame Cowl GSG/14 Regulator 0.38 1.15 GSG/15 Hose 8 mtr GSG/2

Gas Cylinder Trolley

Features:

- > Securely holds propane cylinder
- > Creates highly mobile gas shrink system > Safely stores gas shrink gun at
- convenient height
- > Protects gun from accidental damage
- > Reduces risk of damage or injury from hot nozzle
- > Cylinder & gun not included



Ripack® Gas Shrink Systems The market leader in gas shrink systems

R2200

Propane Gas Shrink System

Features:

- > Powerful 68kW performance
- > Instantaneous single-stage ignition
- > Large, rotating nozzle > Patented Cold Nozzle® technology
- > Automatic safety gas shut off valve
- > Double safety regulator
- > Swivel gas connector
- > Safety guard and dead man's handle
- > Ergonomic design > Gun weight only 1.2kg

- > Up to 20% higher performance than other systems
- > Fast, even shrinkage across wide areas > Highly controllable heat
- Nozzle angle easily adjusted
- No risk of burns from nozzle
- Overheating prevention extends gun life and reduces maintenance costs
- > Light and easy to handle



R3000

Propane Gas Shrink System

The R3000 offers all the features of the R2200 plus:

- > Additional 15% performance power
- > Ergonomic soft-grip handle> Spare igniter stored in handle
- > Fast, tool-free igniter change process
- > Large suspension ring for attachment to retractable tool balance
- > Carry case doubles up as convenient 27cm-high footboard



The R3000-10 is supplied in a carrying case



Ripack® (Genuine Spares	Compatible With	A
Part No.		R2000 R2200 R3000	kg each
134025	Regulator	• • •	0.75
250023	Hose	• • •	1.13
148043	Swivel Connector	• • •	0.05
131003	Piezo Igniter	• • •	0.02
236022	Ignition Wire (2000)	•	0.01
232061	Spark Plug (2200)	• •	0.01

Ripack® G	ienuine Spares	Com	patible \	Vith		h
Part No.		R2000	R2200	R3000	kg eac	h
243044	Neck Casing (2200**)	-	•	-	0.0	1
243056	Neck Casing (2200***)) -	•	-	0.0	12
233258	Ignition Wire (2200**)	-	•	-	0.0	1
233385	Ignition Wire (2200***) -	•	-	0.0	1
248113	Gas Tap	•	•	•	0.9	5
131072	Piezo Igniter*	-	•	•	0.0	12


Only for use with extensions Serial number 197868 or earlier * Serial number 197869 or later

Polythene Shrink Film in Centre Fold, Gusset Tubing and Bag on Roll configurations




Select the right film for the right application









For awkward shaped items...

CS1225 Centre Fold Polythene Shrink Sheeting


Roll width	Film thickness	Roll	kg
1250mm folded (2500mm unfolded)	125mu	85mtr	25.9

PS004 Multi Fold Poluthene Shrink Sheeting

500 Finata rota rotgarene similik sheeting							
Roll width	Film thickness	Roll	kg roll				
1000mm folded	tilicitiic55	tength	roll				
(4000mm unfolded)	200mu	25mtr	16.0				



For pallet loads of varying height...



Tubing Size

Perforated on the roll

Film Roll

GS1012 Gusseted Polythene Shrink Tubing

1250/2250mm (Ideal for	UIICKIICSS	terigui	roll
	125mu	50mtr	28.5
GS1223 Gusseted Polythe	ene Shrink	Tubing	
Tubing Size	Film thickness	Roll length	kg
1200/2200mm	200.001	20mts	217

For loads of approx 1200mm height...



SB1280 Ready-made Shrink Covers on a Roll

Load size	Film thickness	Covers /roll	kg roll	
1200 x 800mm (Pallet cove size 1300/2150 x 1850mm	ı 125mu (500g	30	31.0	

SB1210 Ready-made Shrink Covers on a Roll

Load size	Load height	Film thickness	Covers /roll	kg
1200 x 1000mm (Pallet cov	er			1011
size 1300/2350 x 1950mm)) 1200mm	125mu (500g)	30	35.3

SB1212 Ready-made Shrink Covers on a Roll

Load size	Film thickness	Covers /roll	kg
1200 x 1200mm (Pallet cover size 1300/2550 x 2050mm)	125mu (500g)	25	34.4

Polythene Sheeting





- > Dust and moisture protection for a wide range of applications > For horizontal storage and
 - dispensing, use PFD-1 Roll Dispenser (see page 92)

Polythene Top Covers

- > Convenient, perforated covers
- > 150 per roll
- > 900mm width roll
- > 1800 x 1800mm open size
- > Fit popular pallet sizes > Used with stretchwrap, top covers provide high moisture and dust protection
- For horizontal storage and dispensing, use PFD-1 Roll Dispenser (see page 92)

Code	Film type/ thickness	Colour	kg
PTSH-1	LDPE 50mu	Clear	17.6
BKPTSH-2	LDPE 50mu	Black	17.6
HSTSH-1	HDPE 24mu	Clear	17.6

> Multi-fold (4mtr open width)

Code	Film thickness	Roll length	Colour	kg
PS002	65mu	75mtr	Black	14.9
PS003	80mu	50mtr	Clear	19.0
PS004	200mu	25mtr	Clear	16.0

> Centre-fold (2mtr open width)

Code	Film thickness	Roll length	Colour	kg
PS006	80mu	100mtr	Clear	17.3
PS007	200mu	50mtr	Clear	17.2

Transpal® Packaging Papers

WKP40 Waxed Kraft Paper

- > Roll width 900mm > Roll length 100mtr
- > Paper weight 55gsm> Priced per roll, sold in 2-roll packs



MG Pure Ribbed **Kraft Paper Sheets**

- > 70gsm pure ribbed kraft
- > Priced and sold per ream (c. 480-500 sheets)



Code	Sheet size	kg ream
PKP01	700 x 1150mm	14.1
PKP02	900 x 1150mm	16.8

VCI-100 Rust Inhibitor Paper

- > Contains volatile corrosion inhibitor
- > Roll width 1000mm
- > Roll length 200mtr
- > Paper weight 50gsm



MG Pure Ribbed **Kraft Paper Rolls**

- > Roll length 70gsm = 285mtr
- > Roll length 88gsm = 225mtr





Code	Width	Weight	kg roll
PKP03	450mm	70gsm	12.0
PKP04	500mm	70gsm	12.8
PKP05	600mm	70gsm	14.6
PKP06	750mm	70gsm	17.3
PKP07	900mm	70gsm	20.0
PKP08	900mm	88gsm	20.0
PKP09	1200mm	70gsm	25.4

Kraft Union Paper

- > Bituminised laminated kraft
- > Superior water resistance
- > Roll length 100mtr
- > Kraft weight 120gsm



Code	Roll width	kg roll
KUP6	600mm	6.8
KUP9	900mm	14.8
KUP12	1200mm	18.2
KUP18	1800mm	31.1

MF Imitation Kraft **Paper Sheets**

> A cheaper alternative to pure kraft paper



Code	Sheet size	Weight	Pack qty.	kg
IKP02	900 x 1150mm	90gsm	1 ream (480-500 sheets)	24.4
IKP11	750 x 1150mm	70gsm	50 sheets	1.58
IKP12	900 x 1150mm	70gsm	50 sheets	1.90

Tissue Paper

- > 18gsm bleached or acid-free tissue > Priced per ream (480 sheets)



Code	Sheet size	Туре	kg ream
BTP47	450 x 700mm	Bleached	2.7
BTP57	500 x 750mm	Bleached	2.5
AFT57	500 x 750mm	Acid-free	2.5

MF Imitation Kraft Paper Rolls

> imitation kraft





Code	Roll Size	Weight	kg
IKP03	600mm x 200mtr	90gsm	15.7
IKP04	750mm x 200mtr	90gsm	18.3
IKP05	900mm x 200mtr	90gsm	22.0
IKP06	1150mm x 200mtr	90gsm	26.4
IKP09	500mm x 300mtr	70gsm	17.4
IKP10	900mm x 300mtr	70gsm	33.0
IKP13	750mm x 300mtr	70gsm	26.0



News Off Cuts





Slipguard® Anti-Slip Sheets

- > Unique anti-slip coating on 100gsm paper
- > Best-performing load stabilisation sheet system
- > Highly effective up to 45° tilt
- > Water repellent coating also restricts water through consignment > Stabilises palletised sacks, bags and cartons
- > Reduced secondary packaging requirements (stretch film/strapping)
- > Sold in boxes of 200 sheets

Code	Sheet Size (mm)	Qty per box	kg/ box
ASL0812-10-BOX	800 x 1200	200	22.0
ASL1012-10-BOX	1000 x 1200	200	28.0
			0
Code	Sheet Size (mm)	Qty per pallet	kg/ pallet
ASL0812-10	800 x 1200	5,000	22.0
ASL1012-10	1000 x 1200	5,000	28.0



Protective Layer Sheets

> Place on a pallet bed and between layers of cartons for added protection and load stability




				4 -
Code	Dimensions (mm)		Qty per pallet	kg/ 1,000
LS170-1077-91	6 1077 x 916	170gsm	3,000	167

Green PVC Coated Sack Ties



Code	Size	kg bundle
ST6-C	150mm (6")	1.8
ST8-C	200mm (8")	2.0
ST9-C	225mm (9")	2.1
ST10-C	250mm (10")	2.7
ST12-C	300mm (12")	2.8
ST14-C	350mm (14")	3.5

Sack Tying Tool > Use with sack ties to quickly









Code		Approx. length		
S2PLY	2.5kg	750mtr	10	54kg
CSDIA	2 5kg	500mtr	10	92ka



Strong, tear resistant sacksIdeal for heavy or sharp fabricated products and engineering parts > Sold in packs of 100

Code	Size	kg case
WSP1520	381 x 508mm	1.3
WSP1824	457 x 610mm	5.0
WSP1932	483 x 813mm	2.3

Cotton String



> Natural material

Code		Approx. length		
FCS125	125g	150mtr	12	8kg
FCS250	250g	130mtr	6	18kg
FCS500	500g	130mtr	6	29kg

Polypropylene Twine

> Good weather-resistance

Code		Approx. length			kg case
PT3	2.25kg	1575mtr	8	50kg	18.0
PT4	2.25kg	1012mtr	8	80kg	18.0
PT6	4.50kg	1260mtr	4	125kg	18.0
PT8	4.50kg	765mtr	4	205kg	18.0

Transpal® Logistics Products & Plastic Pallets

> Water and dust protection

Industrial Tarpaulins

- during transit and storage
- > Fully eyeleted
- > Durable industrial quality> Suitable for outdoor
- storage applications

Code	Size (mtrs)	kg/ each
TP4102	3 x 2	0.5
TP4103	5 x 4	1.7
TP4104	8 x 5	3.4
TP4105	10 x 6	5.1
TP4106	12 x 8	8.5

Industrial Gloves

- > Suitable for a number of applications
- > Sold only in whole pack quantities even when priced per pair*

GLBDN-L & **GLBDN-M**



Code	Description	Size	Pairs per pack	Packs per case	kg/ pack
GLBDN-L	Navy seamless knit with gripper dots	Large	10	12	1.0
GLBDN-M	Navy seamless knit with gripper dots	Medium	10	12	1.0


Ratchet Strap

- > Two-part ratchet strap > Double hooks
- > Fast, positive load securement
- > 25mm woven strap
- > Breaking strain of 500kg
- > Ideal for lighter applications





GLHWC-M



Plastic Pallets

Our open deck, lightweight plastic pallets provide an excellent alternative to traditional wooden pallets

- > More cost-effective
- > Longer useable life
- > Don't splinter or disintegrate
- > No heat treatment required for international shipping
- > Easy wash-down
- > Lighter, particularly when wet
- > Good chemical and moisture resistance
- > Reduced risk of harbouring contamination
- > Easily recyclable

GLPU-GS & GLPU-GL

*sold only as full packs of 10 pairs

Code	Description	Size	Pairs per pack	Packs per case	kg/ pack
GLPU-GS	Grey seamless	Size 8	10	24	0.31
	knit PU coated	(female)			
GLPU-GL	Grey seamless	Size 9	10	24	0.31
	knit PU coated	(male)			

6040BK



6080BK









Code	Description	Size (mm)	Weight	Dynamic load	Static load	Colour
6040BK	Plastic nestable display pallet	600 x 400	1.0kg	N/A	150g	Grey
6080BK	Plastic half euro pallet	600 x 800	3.3kg	400kg	1200kg	Black
1208BK	Plastic nestable pallet	1200 x 800	5.7kg	800kg*	2500kg	Black
1210BK	Plastic nestable pallet	1200 x 1000	6.5kg	800kg*	2500kg	Black

*1000kg when flat loaded

Plastic Runners

- > Set of three

> Increa:	ses dynamic load by 200kg per pallet	1210PR	(II)	1208PR
Code	Description	Weight	-	
1208PR	Plastic runners for 1208BK pallet, set o	f 3 1.2kg/set of 3		
1210PR	Plastic runners for 1210BK pallet, set of	f 3 3.0kg/set of 3		



order fulfilment and warehousing products

- > bespoke and modular pack bench systems
- > materials handling tote bins, storage racks and bins etc.
- > paper void fill systems
- > anti-fatigue matting
- > floor marking and hazard warning products
- > janitorial products

Sub-brands

- > Technik[™] bespoke bench systems
- > Ergoline™ modular bench systems
- > Marcwell® floor and hazard marking systems
- > Voidstar™ paper void fill system





Pacplan® Consulting and Design

Bespoke Pack Station System

The Pacplan® Technik™ system is designed to provide entirely bespoke workstations that perfectly match customers' requirements, ranging from single benches to complete fulfilment centre pack bench systems.





Our designers and engineers work closely with other contractors to ensure seamless integration with other materials handling and stock control systems so that productivity and use of space are optimised.




Materials storage locations are designed to minimise operator movement, streamlining processes and reducing the risk of operator fatigue and repetitive strain injury.



Pacplan® Technik™ distributor support services include site survey, CAD design, fabrication and installation.



Benches are constructed from 30 x 30mm and 40 x 40mm heavy duty steel section, with fully welded joints and durable powder coated finishes that can be colour matched to customers' specifications.









Attention to detail, design innovation and manufacturing quality have made Pacplan Technik™ a respected name in the fulfilment centre industry.

We have considerable expertise in creating bespoke, turnkey workstations for a variety of despatch applications. Call our sales team to discuss your workstation project.







Introducing the next generation of air cushion machines:

acplan AirWave

Features & Benefits


- > Produces pillows and quilts from the same machine
- > Programmable one-key technology
- > Ergonomic design > Powerful performance
- > Power saving mode > Lock function

- > CE and RoHS approved > Bluetooth connectivity (optional)

Specifications

- > Power supply: 230v 5oHz > Power consumption: 115W (20W on standby)
- 316 x 413 x 232 mm (W x D x H) (extending base increases width to 466 mm) > Dimensions:
- > Weight:
- 5.6 kg 8-10 metres/min
- > Output:
- > Film thickness: 16-40 mu
- > Roll capacity: > Noise level: 200-2000 mtr ≤ 60 dB

Pacplan Air Wave Films









PWF4-4245



PWF8-4245

Code	Description	Roll Width		Film Thickness	kg/ roll
PWF1-1021	Single 100mm chamber	210mm	700mtr	20mu	5.5
PWF1-1521	Single 150mm chamber	210mm	700mtr	20mu	5.5
PWF1-2021	Single 200mm chamber	210mm	700mtr	20mu	5.5
PWF4-4245	Four chambers across roll	420mm	450mtr	20mu	7.5
PWF8-4245	Eight chambers across roll	420mm	450mtr	20mu	7.5

X-FILLTM

Paper Void Fill System

Paper void fill is a fast, cost-effective and environmentally friendly way to secure consignments within oversized cartons.

Using patented new-generation technology, the X-FILL outperforms all comparable products.

- > Anti-jamming paper feed and "load and go" paper packs almost eliminate downtime.
- At 1.7 metres per second it is up to 21% faster than the nearest equivalent machine on the market.
- Its modular construction has been designed so that it can be assembled and ready to run in less than five minutes.
- Mounted on a height-adjustable stand with lockable castors, its compact design and small footprint mean it can be easily deployed to any location requiring instant, on-demand paper void fill.
- Output is further increased by foot pedal operation and auto cutting, which cuts the paper stream to the required length rather than the operator having to

Specifications

- > Output type
- > Output rate
- > Paper stock
- > Power supply
- > Power usage
- > Weight

pre-set/continuous void fill

> 1.7 m/s

XF-P001 (single-ply 50gsm Kraft) XF-P002 (single-ply 70gsm Kraft)

230v 50Hz

100W

26kg (52kg inc. stand)



Simple to use digital control



Ouick and easy paper feed



The X-FILL head can be tilted to precisely align the outfeed where



Lockable castors for extra stabilitu



discuss your system requirements

X-FoldTM

Paper Void Fill Packs

Patented X-Fold™ paper packs produce the maximum degree of three-dimensional cushioning in proportion to paper usage. The design of the pack's leading edge also makes it easy to feed into the X-FILL and multiple fan-folded paper packs can be spliced for continuous feed.

XF-P001 50gsm X-Fill Paper 9.53Kg





> Paper type

> Paper width Paper length single-ply 50gsm kraft 381mm 500mtr

280 x 381 x 140mm > Pack Dimensions

XF-P002 70gsm X-Fill Paper



Paper type

> Paper width Paper length

> Pack Dimensions

single-ply 70gsm kraft 381mm





Paper padding offers increased cushioning and impact absorption for carton contents whilst in transit and storage. It can be used to line cartons and be wrapped around or layered between products.

Using patented second-generation technology, the X-PAD outperforms all comparable products.

- > Anti-jamming paper feed and "load and go" paper packs almost eliminate downtime.
- At 0.9 metres per second it is up to 75% faster than the nearest equivalent machine on the market.
- The Mitsubishi touch screen control panel allows the operator to programme and store frequently used pad sizes.
- Its modular construction has been designed so that it can be assembled and ready to run in less than five minutes
- The X-PAD is mounted on a freestanding, height-adjustable stand for rapid deployment to any location requiring instant, on-demand paper void fill.
- Output is further increased by foot pedal operation and auto cutting, which cuts the paper stream to the required length rather than the operator having to tear it.

Specifications

> Output type pre-set/continuous void fill

> Output rate > 0.2-0.9m/s

XP-P001 (2-ply 70/70gsm Kraft) > Paper stock

> XP-P002 (2-ply 5070gsm Kraft) XP-P003 (1-ply 70gsm Kraft) XP-P004 (1-ply 90gsm Kraft)

230v 50Hz > Power supply > Power usage 200W 48kg > Weight



Ouick and easy X-PAD paper reloading



The X-PAD head can be tilted to precisely align the outfeed where required



Lockable castors for



faster than nearest

equivalent machine

on the market!

Digital touch screen control panel

Remote foot

pedal operation

Contact your account manager to discuss your system requirements

X-Fold™

Patented X-Fold™ paper packs produce the maximum degree of three-dimensional cushioning in proportion to paper usage. The design of the pack's leading edge also makes it easy to Paper Void Fill Packs feed into the X-PAD and multiple fan-folded paper packs can be spliced for continuous feed.

XP-P001

70/70gsm X-PAD Paper

Features

- > Paper type
- > Paper width > Pack dimensions
- > Paper length 300mtr
- 280 x 381 x 480mm
- 2-ply 70/70gsm kraft
- > Paper type

XP-P002

> Paper width > Pack dimensions

Features

- 2-ply 50/70gsm kraft

50/70gsm X-PAD Paper

- > Paper length 350mtr
- 280 x 381 x 350mm

XP-P003 70gsm X-PAD Paper

- Features
- > Paper tupe
- 1-ply 70gsm kraft > Paper width
- > Paper length
- 360mtr 280 x 381 x 290mm > Pack dimensions

XP-P004

90gsm X-PAD Paper

Features

- > Paper type
 - > Paper width
- > Paper length
 - 360mtr
- 280 x 381 x 330mm > Pack dimensions



1-ply 90gsm kraft



Voidstar™ System, Pillopax™ Film & Kinetix® Workstations



Pacplan® VSTR60 Voidstar Dispenser

- > Rugged construction > Wall or bench mounting
- 600mm roll width Paper braking system
- > Integral rip jaws

Benefits

> Low footprint (wall-mounted)



Pacplan® VSP60 Voidstar Paper Roll

- 55gsm white kraft600mm roll width, 400mtr length

- Selected for use with the VSTR60
- Easy tearabilityExcellent void fill properties100% recyclable





KXWS001

Pack Station 1600mm x 800mm



The KXWS001 from the Kinetix® range of packaging products is an entry-level, professional workstation for the low- to medium-volume user.

Its sturdy, powder-coated square section steel frame supports an 820mm high, 1600×800 mm melamine coated work surface and includes a number of space-saving and handy features designed to maximise its versatility.

Two mandrels are situated above and below the workbench for convenient dispensing of kraft, bubble and corrugated packaging products.

Two high-level steel storage shelves store accessories clear of the bench but within easy reach. One shelf is perforated with a series of cut-outs to hold commonly used packaging equipment such as tape dispensers and handy wrap rolls.

GTL400-3

Pacplan® Flexible Outfeed Conveyor



Ergoline™ Workstations and Roll Dispensers

Modular Pack Station System





Heavy duty 25mm worktons and shelves designed to withstand regular use in industrial



Postformed table too profile for increased operator comfort and safety



Robust steel and MDF shelf construction for strength and durability



Adjustable 50mm leg sections enable the work surface to be set at any height between 750mm and 900mm.

PPE1600

- Packing Table > 1600 x 800mm laminate
- on MDF work surface 750-900mm adjustable bench height Powder coated steel
- frame and work surface edging
- > Up to two PPE1601 shelf units may be fitted to the PPE1600 table



PPE1604

Small Box Divider

250 x 300mm Fits on PPE1601 shelf to create segregated storage



PPE1605

Large Box Divider

> 300 x 400mm > Fits on PPE1601 shelf to create segregated storage



PPF1606

- Bench Mounted Cutter Brackets
 > Secure BMC bench mounted cutters (page 99) to PPE1600 packing table
- > Sold as a pair





PPE1601

Shelf Unit

- > 1600 x 300mm laminate on MDF shelf
- > Powder coated steel edging
 > 2 upright supports
- /brackets > Up to 2 shelf units may be fitted to a PPE1600 table



PPE1602

Under Table

- Mandrel > Powder coated steel
- > Fits PPE1600 table > Holds rolls of bubble film, corrugated or foam, up to 1200mm wide



PRC Counter Roll Dispensers > Powder coated steel

- Takes rolls up to 200mm diameter
- PRD60 600mm roll width

PRD 100 900mm roll width



PPEHMS

Mobile Heat Sealer Station > Ideal for on-demand

- production of mailing bag > Positions an S620 seale at correct height for a PPE1600 table
- > Holds 2 rolls of 640mm (24") layflat tubing > Powder coated steel
- > Fixed/swivel castors








Bench Mount





Under Mount



- > Can be bench, wall or under-mounted











PPD



Polaris Paper Roll Dispensers

> Bench mounted

> Takes up to 200mm diameter rolls

PPD800 800mm roll width PPD1000 1000mm roll width



PPD750-155



Single Paper Roll Dispenser > Bench mounted

- > Roll width 750mm > Max. 150mm roll diameter



DPPD750-155



- > Bench mounted
- > Roll width 750mm > Max. 150mm roll diameter

PRD750



Ribbon Dispenser

- > Used for displaying and dispensing assorted ribbons for presentation packaging
- > Mandrel width 750mm



Ergoline™ Roll Dispensers & **Pacplan®** Trollies







Pacplan® Cutter Stands

> Dispense and cut foam, foil, bubble film, kraft and corrugated paper, PVC film etc.

- > Cutter units supplied with two cassette cutters; a 'V'shaped blade for most materials and a rotary cutter specially for corrugated paper > Maximum roll/cut width of 1500mm

PLU001 PLU002



Single dispenser with cutter

- > 1880 x 830 x 1250mm (W x D x H)
- > Max. outer roll diameter 800mm > Can be fitted with casters (sold separately)





Dual dispenser without cutters

- 1860 x 810 x 1170mm (W x D x H)
- > Max. outer roll diameter 800mm > Can be fitted with casters (sold separately)



PLU003



Dual dispenser with cutters

- 1880 x 830 x 1610mm (W x D x H)
- > Max. outer roll diameter 800mm > Can be fitted with casters
- (sold separately)





PLU004

- Bench Mounted Cutter > 1760 x 100 x 210mm (W x D x H) > Fixes to a PPF1600 table with PLLI009
- brackets (will extend beyond table)



PLU005

- Brackets > Fix a PLU004 bench mounted cutter to a PPE1600 table
- > Set of two



PCUT04

PLU006

- > Braking swivel casters > Fit all Pluto stands
- > Set of four



PCUT01 Polestar Mobile

PCUT02

Cutter & Stand for 1200mm rolls

Polestar Mobile 1500mm rolls

- > Hold, dispense and cut most packaging products on the roll

 > Durable, powder coated construction
- > Precision cutting unit with 2 blades (standard and serrated)
- > Standard blade suitable for bubble film, corrugated paper, foam and all similar
- packaging material

 > Extended-life serrated blade only suitable for corrugated paper

PCUT01 800 x 1500 x 1130mm (W x D x H)

PCUT02 800 x 1850 x 1130mm (W x D x H)





PCUT03

Polestar Combi 1200mm rolls

Polestar Combi 1500mm rolls

- > Based on the PCUT01/PCUT02
- > Holds two different roll products
- > Separate precision cutting unit for each roll holde
- > Standard blade suitable for bubble film. corrugated paper, foam and all similar packaging material
- Extended-life serrated blade only suitable for corrugated paper

PCUT03 800 x 1500 x 1630mm (W x D x H)

PCUT04 800 x 1850 x 1630mm (W x D x H)



LST-200

- > Max loading 100kg > Footplate depth 180mm
- > Wheel diameter 250mm > 1100 x 490 x 460mm (H x W x D)



AST-200

Aluminium Hand Truck

- > Max loading 80kg > Footplate depth 125mm
- > Wheel diameter 250mm > 1120 x 490 x 490mm (H x W x D)







Pacplan® Mats & Marcwell® Floor Marking System

Anti-Fatigue Mats

Pacplan® anti-fatique mats are practical, safe and comfortable, proven to reduce fatigue and pressure on the feet, legs and spine caused bu prolonged standing at static work locations.


PFM-2 Super Mat



- > Dual fused lauer for superior comfort and durability
- Suitable for more demanding locations
- > Mat dimensions 900 x 1500mm > Mat thickness 12.5mm



PFM-1 Safety Mat



- Raised diamond pattern surface for
- underfoot ario
- High visibility edging to reduce trip hazard
- > Mat dimensions 900 x 1500mm
- Mat thickness 9.0mm





- > Hard-wearing, soil resistant PVC
- > Raised diamond pattern surface for grip > High visibility edging to reduce trip hazard
- > Cushioned backing for enhanced fatigue relief Mat dimensions 900 x 1500mm
- > Mat thickness 14mm



The innovative, simple to operate floor marking system TL001

Lane Marking Applicator

Features

- > Applies tape evenly to floor
- > Reduces operator back strain > Accepts tapes up to 100mm wide







Code

I MT75W

LMT75R

LMT75Y

LMT75G

Colour

White

Red

Yellow

Green





60

6.0

6.0

6.0



LMT50

50mm Floor Marking Tapes

- > Heavy duty self adhesive vinyl
- > Solid colours
- > Premium industrial quality
- > 50mm width
- > 33mtr length > 18 rolls per case


Code	Colour	kg/ case
LMT50W	White	7.2
LMT50B	Blue	7.2
LMT50Y	Yellow	7.2
LMT50R	Red	7.2
LMT50OR	Orange	7.2
LMT50G	Green	7.2
LMT50LB	Light blue	7.2
LMT50BLK	Black	7.2



LMT75

75mm Floor Marking Tapes

- > Heavy duty self adhesive vinyl
- > Solid colours
- > Premium industrial quality
- > 75mm width
- > 33mtr lenath > 12 rolls per case
- HWT50



- > Heavy duty self adhesive vinyl
- > Solid colours
- > Premium industrial quality
- > 50mm width
- > 33mtr length > 18 rolls per case

Code Colour HWT50GW Green/white HWT50YB Yellow/black 72 HWT50RW Red/white 72





Essential for all warehouse and despatch area operations

Pacplan® Pallet Trucks



- > The Pacplan® PLT-01 is designed for use with Europallets, where its narrower forks will fit into the short end of the pallet, and has a 2000 kg load capacity.
- > The Pacplan® PLT-02 is identical to the PLT-01 but with an increased load capacity of 2500 kg.
- > The Pacplan® PLT-03 has wider forks for improved sideways stability, and a 2500 kg load capacity.
- > The Pacplan® PLT-04 is identical to the PLT-03 but with longer forks for improved front to back stability.

PLT-01

Specifications

> Fork Width: > Fork Length:

> Load Capacity:

540mm 1150mm 2000kg

PLT-03

Specifications

> Fork Width: > Fork Length: > Load Capacity: 685mm 1150mm 2500kg

PLT-02

Specifications

> Fork Width: > Fork Length:

> Load Capacity:

540mm 1150mm 2500kg

PLT-04

Specifications

> Fork Width: > Fork Length: > Load Capacity: 685mm 1220mm 2500kg

Pacplan® Small Part Bins



To help maintain a tidy and ordered work area, you need

Pacplan® Small Part Bins

These durable polypropylene bins are designed for easy access to contents when used with louvre storage panels or stacked. They feature a deep top lip to keep them stable when stacked and a front panel for contents labelling.

Sold only in full pack quantities



Specifications

- > Colour:
- > Size (w x d x h): 54 x 105 x 88mm
- > Volume (litres): 0.4
- > Pack Qty:
- > Pack Weight: 0.046kg





- > Colour:
- > Size (w x d x h): 85 x 105 x 167mm
- > Volume (litres): 1.0
- > Pack Qty:
- > Pack Weight: 0.11kg



- > Colour: Blue
- > Size (w x d x h): 123 x 144 x 237mm
- > Volume (litres): 4.5
- > Pack Qty:
- > Pack Weight: 0.23kg

PSB4-E

Specifications

- > Colour: Blue
- > Size (w x d x h): 164 x 205 x 345mm
- > Volume (litres): 12.0
- > Pack Qty:
- 0.64kg > Pack Weight:

PSB5-B Specifications

- > Colour: Blue
- > Size (w x d x h): $189 \times 298 \times 485$ mm
- > Volume (litres): 30.0
- > Pack Qty:
- > Pack Weight: 1.23kg



- > Colour: Green
- > Size (w x d x h): 250 x 372 x 600mm
- > Volume (litres): 65.0
- > Pack Qty:
- 1.75kg > Pack Weight:

Centre Feed Rolls

C-Fold Hand Towels

- > Price per case
- > Perforated rolls



> Price per case

Code	Description	kg/ case
CFR7306	1 ply blue x 20cm x 300mtr	7.5
CFR7321	1 ply white x 20cm x 300mtr	7.5
RC6506	2 ply blue x 20cm x 150mtr	7.5
CFR7309	2 ply white x 20cm x 150mtr	7.5

Luxury Toilet Rolls


> Paper wrapped, bulk packed

> Price per case of 36 rolls



Industrial Wiper Rolls


> 1,000 sheets per roll > Price per case of 2 rolls



Code Description FC8501 1 ply blue x 2880 sheets 23cm x 33cm 8.5 FC5804 2 ply white soft x 2400 sheets 23cm x 33cm 11.2

Mini Jumbo Toilet Rolls

F19202 1 ply green interfold towels x 3600 sheets



umbo Toilet Rolls

> Price per case of 6 rolls

Code	Description	kg/ case
RT3522	2 ply white x 410mtr x $2^1/4$ " core	7.7

Rag Replacement Wipes

> Ultra strong, lint-free with solvent use and excellent wet strength. Ideal for engineering, printing press wipes etc.

> Price per case of 2 rolls

Code	Size (mm)	Wipes/roll	Roll/length	kg/ case
RN1508	200 x 400	400	160mtr	12.5

Paper Dispensers

> Please note: Colour of dispensers may vary from those shown



Code	Description	kg
HTD-50688	3 C-Fold Dispenser (BC528W)	1.0
HTD-50688	4 Centre Feed Dispenser (BC8311)	1.2
TRD-50688	9 Jumbo Toilet Roll Dispenser 21/4" core (BC335W)	1.0

Wiping Rags

> Price per 10kg case



Latex Gloves

> 100 ambidextrous gloves per box

> Packed 10 boxes per outer

Code	Size	kg/ box
LTXL-M	Medium	0.8
LTXL-L	Large	0.8


Refuse Sacks

RS005 18" x 29" x 39" x 120g

WBL-049 30" x 46" x 54" x 17mu*

ARG2030 20" x 30" x 480g**

* Wheelie Bin Liners



200

250

Bin Liners

> 1,000 per box

11.7

8.7

6.7

115

Code	Description	kg/ box
WSBL	13" x 23" x 29" Swing Bin Liners White High Density (10 x 100)	4.5
SBL-1	15" x 24" x 24"x7mu Square Bin Liners	4.6
PBL-1	11" x 17" x 18"x7mu Pedal Bin Liners	2.4



stapling tools, staples and accessories

- > hand staplers and tackers
- > pneumatic staplers
- > carton and general purpose staples
- > stapling accessories



Stronghold® Staplers



General Purpose Plier Stapler

- > Ideal for general stapling use in the post room, shop, store and office Recommended staples:
- 24-6S S24-8

- S26-6 S26-8



> Ideal for sealing padded mailer bags, sacks and small SHR31 Heavy Duty

- cartons
 > Includes 3 anvil profiles
 for different stapling configurations
- > Recommended staples: 73-8S
- 73-10S



SHR11

Hammer Tacker

- Also used for fitting carpets, insulation material etc.
- > Recommended staples:
- S140-8 S140-10





Plier Stapler









SHR50

General Purpose Tacker

- > Robust, chrome plated allmetal construction
- Ergonomic soft-grip lockdown handle
- > Suitable for textiles, canvas, leather, upholstery or up to 50 sheets of paper > Recommended staples:
- \$23-6 \$23-8 \$23-10



SHR60

Heavy Duty Tacker

- > Lightweight, high-impact ABS body > Metal lockdown handle
- Adjustable pressure controlSuitable for plastic sheeting, cardboard insulation material or up to 80 sheets of paper
- > Recommended staples:
- S140-6
- S140-8 S140-12



MAN27

Carton Stapler

- > Heavy duty construction > Secures filled carton top flaps > Recommended for use with SHBS9 or SHBS18 box support
- > Recommended staples:
- 32-15S 32-18S















AIR27 Pneumatic Carton Stapler

- > Air-powered for high-volume
- usage
 > Heavy duty construction
 > Use for securing the top flaps of filled cartons
 > Recommended for use with
- SHBS9 or SHBS18 box support > Recommended staples:
- 32-15S 32-18S



TRED27

Manual Treadle Stapler

- > Use for stapling carton base flaps > Treadle action leaves both
- hands free to accurately align and hold carton > Recommended staples:
- 32-15S
- 32-18S



TRED27AIR

Pneumatic Treadle Stapler

- > Use for stapling carton base flaps
- flaps > Treadle action leaves both hands free to accurately align and hold carton > 50-100 cartons/hour output
- > Safety foot pedal > Recommended staples:

 • 32-15S

 • 32-18S









Stronghold® Pneumatic Staplers

SP50-5B-A

Pneumatic Anvil Stapler



- > Compresses material for strong, tight closure without damaging material
- > 6"x 1" throat > Ideal for corrugated cartons, vegetable tray boxes, postage tube end caps, pallet boxes, container inserts etc.

 > See staples usage guide for compatible sizes on page 113

SP50-10B-A

Pneumatic Anvil Stapler



STRONG

- > Compresses material for strong, tight closure without damaging material
- > 6"x 1" throat
 > Ideal for corrugated cartons, vegetable tray boxes, postage tube end caps, pallet boxes, container inserts etc.

 > See staples usage guide for compatible sizes on page 113



SP50-5B-K

Pneumatic Anvil Stapler including 4 anvils



- > Compresses material for strong, tight closure without damaging material
- > Ideal for corrugated cartons, vegetable tray boxes, postage tube end caps, pallet boxes, container inserts etc.
 > See staples usage guide for compatible sizes on page 113

Includes:









1 x 'CR' anvil



SP50-10B-K

Pneumatic Anvil Stapler including 4 anvils



- > Compresses material for strong, tight closure without damaging material
- > Ideal for corrugated cartons, vegetable tray boxes, postage tube end caps, pallet boxes, container inserts etc.
 > See staples usage guide for compatible sizes on page 113

Includes:

1 x SP50-10B stapler









1 x 'CR' anvil



SHBS **Box Supports**









- Competitively priced, all metal box supportsUse with AIR27and MAN27
- staplers for professional, easy stapling of carton base flaps prior to filling
- > Table sizes SHBS9 229 x 229mm SHBS918 229 x 457mm





Staplers, Tackers & Staple Remover



- > Anvil rotates for stapling/
- pinning
 > Suitable for the post room,
- store, shop and office

 > Staples up to 50 sheets of paper

 > Chrome plated finish
- > Compatible staples:
- S24-6 S24-8



Rapid 26 Series Stapler



- > Anvil rotates for stapling/



Plier Stapler with Dual Anvil



- Versatile and powerful
 Fingerstop
 Suitable for padded mailing bags, sacks and small cartons
- > Compatible staples: \$73-8 \$73-10 \$73-12



Rapid Plier Stapler



- > Handy plier stapler for home and office
- > Comfortable grip > All-steel construction
- > Powder coated finish > Compatible staples:



- > Suitable for stapling labels to pallets and crates > Also used for fitting carpets, insulation material, roof paper
- > Compatible staples:
- \$140-6 \$140-8 \$140-10



Rapid High-Impact Hand Tacker

(6-14mm staples)



- Suitable for decorative work, reupholstering etc.
 See staples usage guide for compatible sizes on page 113



- > Suitable for decorative work, reupholstering etc.
- > See staples usage guide for compatible sizes on page 113



Rapid Staple Remover



- > Quickly and safely removes staples from paper, cartons, mailing bags etc.
 > Reduced risk of injury or
- damage to material



- > Suitable for fastening plastic film,insulation material, carpets etc. to all kinds of wood
- > Adjustable impact force
- > See staples usage guide for compatible sizes on page 113



STRONGHOI

Stronghold® Staples

Code	Size	Leg length (mm)	Staples per box	kg/ box
24-65	24/6	6mm	5,000	0.3
32-155	32/15	15mm	20,000	15.8
32-185	32/18	18mm	20,000	17.3
35-15S	35/15	15mm	20,000	18.3
35-18S	35/18	18mm	20,000	15.4
73-85	73/8	8mm	5,000	0.6
73-10S	73/10	10mm	5,000	0.7
73-125	73/12	12mm	5,000	0.8

Unbranded Staples

Code	Gauge (mm)	Width (mm)	Leg length (mm)	Staples per box	kg/ box
SB501912	1.27	12.85	12.0	5,000	0.9
SB501914	1.27	12.85	6.0	5,000	0.6
SB501938	1.27	12.85	9.5	5,000	0.7
SB501958	1.27	12.85	16.0	5,000	1.0
SB10302012	2.6	12.95	12.0	2,500	0.9
SB10302038	2.6	12.95	9.5	2,500	0.8
SB10302058	2.6	12.95	16.0	2,500	1.1

Rapid Staples

Code	Size	Leg length (mm) Staples per box	kg/ box
S13-4	13/4	4	5,000	0.2
S13-6	13/6	6	5,000	0.3
S13-8	13/8	8	5,000	0.4
S13-10	13/10	10	5,000	0.4
S13-14	13/14	14	5,000	0.5
S21-4	21/4	4	5,000	0.5
S23-6	23/6	6	1,000	0.7
S23-8	23/8	8	1,000	0.1
S23-10	23/10	10	1,000	0.1
S24-6	24/6	6	5,000	0.3
S24-8	24/8	8	5,000	0.3
S26-6	26/6	6	5,000	0.2
S26-8	26/8	8	5,000	0.2
S73-8	73/8	8	5,000	0.6
S73-10	73/10	10	5,000	0.8
S73-12	73/12	12	5,000	0.6
S140-6	140/6	6	5,000	0.5
S140-8	140/8	8	5,000	0.6
S140-10	140/10	10	5,000	0.7
S140-12	140/12	12	5,000	0.8
S140-14	140/14	14	5,000	1.0

Staples Usage Guide

Staptes Usage Guide																									
						B-A	-0B-A	8-5	9-80	B-CL	SP50-10B-CL	B-CR	SP50-10B-CR				7AIR								
	SHK1	SHR31	SHR11	SHR50	SHR60	SP50-5B-A	SP50-10B-A	SP50-5B-5	SP50-108-B	SP50-5B-CL	P50-1	SP50-5B-CR	P50-1	MAN27	AIR27	TRED27	TRED27AIR	^도	K124-8	R31	551	R11	R23	R33	R34
Stronghold® Staples	S	S	S	\ \mathcal{O}	S	S	v	S	\(\mathcal{O} \)	\(\mathcal{O} \)	S	, v	v		Ø.	-	-	×	¥	Œ	S	Œ	Œ	Œ	Œ
24-6S	•																		•						
32-15S														•	•	•	•								
32-185														•	•	•	•								
35-15S										No	o comp	atible	staple	_	ur rand	_									
35-18S												atible			_	1									
73-8S		•																		•					
73-10S		•																		•					
73-12S		•																		•					
SB501912		_				•		•		•		•								_					
SB501912 SB501914						•		•		•		•													
SB501938						•		•		•		•													
SB501958						•		•		•		•													
SB10302012				-			•	_	•		•		•												
SB10302012 SB10302038				-			•		•		•		•												
SB10302058									•				•												
Rapid Staples																									
S13-4		I		I						1		I				I				I			•		
S13-6																								•	
S13-8																									
S13-10																									
S13-10				-																				•	
S21-4																					•				
S23-6				•																					
S23-8																									
523-8 523-10																									
S24-6				_															•						
S24-8	•			-						-		-				-			•						
S24-8 S26-6				-						-									_						
S26-8	•																								
																				_					
S73-8				-						-		-				-				•					
S73-10																				•					
S73-12				-																•					
S140-6			•	-	•					_												•			
S140-8			•		•																	•			•
S140-10			•							-												•			•
S140-12					•																				•
S140-14																									•

Index

A		> tape, pistol grip	6, 10	Hotmelt cord polyester strapping	41
	00	> tape, bag neck	8		
Air pillow void fill systems Aluminium foil tapes	99 12	> tape, water activated	72		0.4
Anti-fatique mats	105	> plastic strapping, static and m	obile 36 23	Imitation kraft Impulse heat sealers	94 15, 62
Anti-slip sheets	95	> pouch tape > ribbon	103	<u> </u>	13,02
Anti-static		> shrink film	17	K	
> bags	29	> steel strapping, mobile	47	Kits	
> bubble pouches	29	> steel strapping, narrow aisle	47	> handy wrap (stretch wrap)	90
> grip seal bags	29	> stretch film, hand	90	> plastic strapping	38
> layflat tubing	17	> void fill, air	99	> steel strapping	48
Automatic case sealing machines	65		, 101, 102		.8, 19, 20
В		Documents enclosed wallets	22	Kraft	
Bag neck sealers	8	Documents enclosed wallets, biodegr	adable 22	> edge boards	87
Bags	0	Double-sided	12	> edge boards - moisture resistan	
> anti-static grip seal	29	> foam pads	13 13	> imitation	94 94
> bin liners	108	> foam tapes > PET tape	13	> pure ribbed > tapes, self-adhesive	12
> bubble lined	30	> transfer tapes	13	> water activated tapes	73
> drawstring	25	Drawstring bags	25		75
> grip seal	24	Dust extraction units	69	Ш	
> mailing, polythene	30			Label dispensers, bench mounted	85
> open ended polythene	26	E		Labels	
> padded	30	Edge protection		> combination shipping	85
> polythene gusseted	27	> kraft edge boards	87	> companion, Shockwatch®	77
polypropylene self sealrefuse sacks	28 108	> perforated cardboard	88	> hazard warning	86
> retuse sacks > self seal	108 25	> plastic corner protectors	88	> OPEN VOID security	83
Bale press strapping	41	> plastic edge protectors	43 43	> paper faced metal	86 85
Ball pein hammer	50	> plastic snap-off protectors	43	printed parcel warningtamper evident	85 83
Banding machine	14	Envelopes > documents enclosed	22	> tamper evident Lane marking tape applicator	105
Banding tapes	14	> packing list	22	Lanyards	20
Barrier tapes	11	> polythene mailing	30	Latex gloves, powder-free	108
Bench mounted tape dispensers	8		30	Layer sheets, paper	95
Bin liners	108	F		Lauflat tubing	
Bins		Film sealers		> anti-static	17
> stackable small parts (tote bins)	107	> chamber shrink wrappers	60, 61	> dispenser	17
Blades		> constant	15	> standard	17
> knife and cutter, replacement	20	> hand held	15	M	
> rotary (combi cutter & stand),	103		15, 62, 63		
replacement > tape dispenser, replacement	6	> L-bar	15	Machine roll tape, polypropylene	11
Box cutters	18	<pre>> vacuum > work tables (for C-type)</pre>	64 62	Machine strapping, polypropylene Mailing	39
Box supports, for carton stapling	111	Film unrollers	17	> bags, polythene	30
Bubble box	29	Films	17	> sacks, paper	30
Bubble pouches		> PVC and polyolefin shrink	17	> bubble lined bags	30
> standard	29	> stretch wrap	91	Masking tapes	12
> anti-static	29	Finger lift tape, double-sided	13	Mats, anti-fatique floor	105
C		Flaps, tape dispenser replacement	6	Mill wound steel strapping	48
		Floor marking tape system		Mobile heat sealer station	103
Cardboard shredding machines	68	> tape applicator	105	Moisture resistant edge boards	87
Carton openers Case tapers	18 65	> floor marking tapes	105	N	
Centre feed tissue roll dispenser	108	Foam pads, double-sided	13 13	News offcuts	94
Centre feed tissue rolls	108	Foam tapes, double-sided Friction weld strapping tools	52, 53	Non-stack cones	94 77
C-fold hand towel dispenser	108		32, 33	Nozzles, hotmelt glue gun	81
C-fold hand towels	108	G			01
Cloth tapes		Gas cylinder trolley	12	P	
> double-sided	13	Gas shrink systems	92	Pack station systems	
> laminated polycoated	12	Gloves		> bespoke	98
Combination shipping labels	85	> industrial	96	> modular	102, 103
Combination tools	25	> powder-free latex	108	Packing list envelopes	22, 23
> plastic strapping	35 46	Glue guns, hotmelt	79	Packing list envelopes, biodegradable	
> steel strapping Composite polyester strapping	46 41	Glues, hotmelt	81	Pallet trucks	106
Cones, non-stack	77	Grip seal bags > standard	24	Pallet(s)	93
Constant heat sealers	15	> standard > anti-static	24 29	cover sheets, polytheneprobes	93 42
Conveyor, flexible outfeed	102	Gummed paper tape	73	> shrink covers on a roll	93
Corner protectors			75	> strapping machines	57
> edge boards	87	H		> stretch wrapping turntables	58
> perforated card	88	Hand tape dispensers	6	> plastic, nestable	89
> plastic	88	Hand towels	108	> runners, for plastic pallets	89
Cotton string	95	Hand trucks	104	> trucks	106
Cutters	401	Hazard warning		Paper	
> bench mounted	104	> floor tapes	105	> mailing sacks	30
hand held safetymobile, with stand	18 104	> labels	86	> news offcuts	94
> modile, with stand > steel strapping	104 47	Heat sealers		> rust inhibitor	94
> stretch film	18, 20	chamber shrink wrappers 60constant	15	> tissue > void fill systems 100,	94 101, 102
	_0, _0	> hand held	15 15	> void fill systems 100, > waxed kraft	101, 102 94
D		> I-bar	15, 62	Paper roll dispensers	103
Dispensers		> L-bar	15, 62	Parcel labels, printed warning	85
> janitorial paper	108	> vacuum	64	Parking charge notice envelopes	23
> label, bench mounted	85	> work tables (for C-type)	62	Perforated edge boards	88
label, bench mountedlane marking tape	85 105				88 6, 7
label, bench mountedlane marking tapelarge roll product	85 105 103	 work tables (for C-type) Hook & loop coins and tapes Hot air gun and stand 	62	Perforated edge boards Pistol grip dispensers Plastic edge protectors	6, 7 43
 label, ben'ch mounted lane marking tape large roll product layflat tubing 	85 105 103 17	> work tables (for C-type) Hook & loop coins and tapes Hot air gun and stand Hotmelt	62 14 15	Perforated edge boards Pistol grip dispensers Plastic edge protectors Plastic pallets	6, 7 43 89
label, bench mountedlane marking tapelarge roll product	85 105 103	 work tables (for C-type) Hook & loop coins and tapes Hot air gun and stand 	62 14	Perforated edge boards Pistol grip dispensers Plastic edge protectors	6, 7 43